

3M™ Digital Projector X35N

The 3M Digital Projector X35N features 3,000 lumens of brightness and a 2000:1 contrast ratio for exceptional picture quality. Backed by the 3M brand for superior performance and reliability, the X35N features network functionality which allows effective management of assets to reduce cost of ownership, limit downtime and avoid unnecessary maintenance. Coupled with a new hybrid filter that operates for up to 4,000 hours under normal conditions the X35N is ideal for education and business organisations who are looking for minimal running costs over the lifetime of the projector.




3M X35N Projector
78-9236-7715-3

Features

- 3000 lumens*
- 2000:1 contrast ratio
- Auto Vertical Keystone Adjustment
- Quick Start and Instant Off
- Network Control and Management
- 16W Audio Out sound
- Whiteboard and Blackboard Modes
- Easy change top lamp door
- Hybrid filter with longer maintenance intervals
- Light weight: 9 lbs (4.1kg)

*Indicates maximum lumens rating



Optical

Resolution

Native: True XGA (1024 x 768)
Maximum: UXGA (1600 x 1200)

Imager set

0.63", P-Si TFT Panel

Aspect Ratio

native 4:3, 16:9 and 14:9 letterbox

Colors

16.7 million true colors (24 bit)

Contrast Ratio

2000:1

Brightness

3000 lumens (maximum), 2100 lumens (eco mode)

Projection Lens

F1.67-1.91 (f=19-23mm)

Vertical Lens Shift

9:1 Fixed

Screen Size (range)

30-300 inches

Zoom/Focus

Manual

Zoom Ratio

1.2:1

Throw Ratio (distance:width)

1.5:1 - 1.8:1

Optional Lenses

NA

Lamp

UHB 210W (normal mode), 140W (eco mode)

Lamp Life*

Up to 3000 hours (normal mode)

Up to 6000 hours (eco mode)

* Lamp life may vary due to environment and usage.

Lamp brightness decreases over time.

Size

Dimensions (W x H x D)

12.5 x 4.6 x 11.3 in. (317 x 118 x 288mm)

Weight

9 lbs (4.1kg)

Warranties

Projector

3 years or 2500 hours

Lamp

1 year prorated

Ultra Value Enhanced Warranty (optional)

Includes 1 free lamp, free loaner while unit is being repaired and expedited service.

Not available outside U.S.

System Specifications

Video Compatibility

NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM

SDTV/HDTV

525i (480i), 525p (480p), 625i (576i)/ 750p (720p@60Hz), 1125i (1080i@60Hz)

Digital Keystone Correction

Vertical ±30 degrees

Mouse Emulation

USB

Audio

1 x 16 Watt

Startup Screen

Customizable

Noise Level

Normal 37dB; Eco 30dB

Feature Set

Auto off, 4x digital magnification, image blank

Horizontal Scan

31.5 - 106 kHz

Vertical Scan

56 - 120 Hz

Power Consumption

330W

Power Supply

AC 110~120V /220~240V (50/60 Hz)

Regulatory Approvals

UL, cUL, FCC Part 15 Subpart B, Class B, EN60950-1, CE

Operating Temperature

41° - 95°F (5° - 35°C)

Storage Temperature

-4° - 140°F (-20° - 60°C)

Altitude

Sea level to 6000 ft. (1,829m)

Technical Support

- Free unlimited software downloads and updates available on our website at www.3m.com/meetings
- Toll free 24/7 Technical Support by calling 800.328.1371

Connections

Computer

Computer 1, 2 15 pin HD-Sub – Analog Computer Input

USB Type B – Mouse Emulation

Monitor Out 15 Pin HD-Sub – Analog Computer Output

Control 9 Pin D-Sub – RS-232 Control Port

Audio in 1, 2 3.5mm Stereo mini jack – PC Audio input

Video

Component 3xRCA (Y, Cb/Pb, Cr/Pr) – Component Video input

S-Video 4 Pin Mini-Din – S-Video Input

Video RCA – Composite Video Input

Audio in 3, 2xRCA (red, white) – Right and Left Channel Input

Audio Out 2xRCA (red, white) – Right and Left Channel Output

Wired LAN

Standard: 10 BASE-T / 100 BASE-TX

Connection: RJ-45

Featuring:

PJCtrl: Control a projector via the network

PJImg: Create MyImage file and send it to the projector

PJMan: Control multiple projectors via the network

PJMessenger: Transmit and display a message on a projector via the network

Accessories Included

Network Control and Management Software

Power cords (US, UK, Europe)

Remote control without laser (with AA batteries)

RGB cable

Multi-Language Operator's Guide CD

Lens cap

Optional Accessories

Ultra Value Enhanced Warranty

(X35) U.S. only

78-6972-0010-9

Lamp replacement kit

78-6972-0008-3

Universal ceiling mount

78-6969-9874-5

Soft rolling bag

78-6969-9716-8

Screen Size Diagonal [inch (m)]	Image Size 4:3		Image Size 16:9	
	Projection Distance		Projection Distance	
	Min. [inch (m)]	Max. [inch (m)]	Min. [inch (m)]	Max. [inch (m)]
30" (0.8)	34" (0.9)	41" (1.0)	38" (1.0)	45" (1.1)
60" (1.5)	70" (1.8)	83" (2.1)	77" (1.9)	91" (2.3)
80" (2.0)	94" (2.4)	112" (2.8)	102" (2.6)	122" (3.1)
100" (2.5)	118" (3.0)	140" (3.6)	128" (3.3)	153" (3.9)
150" (3.8)	177" (4.5)	211" (5.3)	193" (4.9)	229" (5.8)
200" (5.1)	237" (6.0)	281" (7.1)	258" (6.6)	306" (7.8)
300" (7.6)	356" (9.0)	422" (10.7)	388" (9.9)	460" (11.7)

Note: These sizes are ±10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

800.328.1371 | www.3m.com/meetings

Specifications subject to change without notice.

Hg—LAMP CONTAINS MERCURY. Manage in accordance with disposal laws. See www.lamprecycle.org or call 1-800-328-1371(USA), 1-800-364-3577 (Canada). For product disposal see www.eiae.org (USA) or www.epsc.ca (Canada).



3M Projection Systems

Building A147-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000
USA

3M Canada

PO Box 5757
London,
Ontario, Canada
NGA 4T1

3M Mexico, S.A. de C.V.

Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty, Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years or 2500 hours from the time of purchase. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.

3M, and the 3M logo are trademarks of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.