

## EX665UT – Ultra Short Throw

- Native XGA, 60" image from just 46cm away
- Shadow-free images on interactive whiteboards
- Bright images, vivid colours – 3000 ANSI Lumens
- Crystal-clear images – HDMI connectivity
- Crestron RoomView® – RJ45 network control and monitoring
- Impressive sound quality – integrated 10W speaker
- 3D-capable technology – DLP®-Link™ enabled
- Environmentally friendly design – less than 1W standby mode
- Optoma EX665UT filter-free design – reduced maintenance costs



### 3D projection in the smallest of rooms with the EX665UT

The XGA ultra short throw, 3D-capable EX665UT is designed to display bright, rich, colourful, crystal-clear images for both the education and business environments. Perfect for installations with interactive whiteboards ensures teaching and business environments have the right tools for engaging and presenting to their audience without shadows and screen glare. The EX665UT at 3000L incorporates extensive connectivity, powerful 10W stereo speakers and RJ45 control to maintain and monitor the projectors over the network.

The environmentally friendly EX665UT has energy saving features including less than 1W standby mode and auto power off saving you both time and money. Long lamp life of 4000hrs combined with our unique Optoma Colour and Imager guarantees ensure hassle-free, long-lasting projection.

### SPECIFICATIONS

Brightness	3000 ANSI Lumens
Contrast Ratio	3000:1
Native Resolution	XGA 1024 x 768
Compatible Resolutions	UXGA, SXGA+, SXGA, WXGA, XGA, SVGA
Display Technology	0.55" XGA DC3 DLP® chip, Technology by Texas Instruments
Lamp Life	4000/2500 hours (STD/BRIGHT mode)
Remote Control	Full function remote with mouse control and direct source selecting

### INPUTS

HDMI (HDCP)		
2 x 15 Pin D-Sub VGA		SCART via adaptor Component via adaptor
S-Video 4 Pin Mini Din		
Composite RCA Jack		
3 x Audio In		3.5mm Audio Mini Jack RCA L&R

### CONTROL

USB (remote control)  
RS232 9 Pin  
RJ45

### OUTPUTS

PC 15 Pin D-Sub VGA (monitor loop-through)  
Audio Mini Jack  
+12v Trigger

### PROJECTION LENS

	F Number	-
	Focus Length	-
	Focus / Zoom	Manual Focus / Digital Zoom ??
	Throw Ratio	0.377 (Projection Distance:Image Width)
	0.5 – 2.5m	
Projection Distance	60" @ 46cm - Diagonal 4:3	
Image Size	127% ±5%	
Offset	10W Speaker	
Audio	4:3 Native, 16:9 compatible	
Aspect Ratio	19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish, Romanian, Farsi and Arabic	
On Screen Display	PAL SECAM 625/576i/p, NTSC 525/480i/p HD 720p/1080i/p	
Video Compatibility	± 35° Vertical	
Keystone Correction	15 – 97kHz / 25 – 85Hz	
Horizontal / Vertical Scan Rate	100 – 240V, 50 – 60Hz	
Power Supply	5 - 35° C, 80% Humidity (Max), 3000m Altitude (Max)	
Operating Conditions	Security Bar, Kensington Lock Port, Password Protection	
Security	Compliant	
RoHS	6 months or 1000 hours – whichever comes sooner	
Lamp Warranty	Warranty will vary by country. Please see <a href="http://www.optomaeurope.com">www.optomaeurope.com</a> or ask your local supplier for details	
Warranty	5 Years	
Colour Guarantee	5 Years	
Imager Guarantee		

