

### Highlights

- Ideal for Home Entertainment
- Easy setup
- Easy Maintenance

<b>Projection System</b>	<b>DLP</b>		
<b>Native Resolution</b>	1080p(1920x1080)		
<b>Brightness</b>	2000 ANSI lumens		
<b>Contrast Ratio</b>	5000:1		
<b>Display Color</b>	1.07 Billion Colors		
<b>Lens</b>	F=2.50~2.76, f=23.5~28.2mm		
<b>Aspect Ratio</b>	Native 16:9 (5 aspect ratio selectable)		
<b>Throw Ratio</b>	1.59-1.9 (56.8"@2m)		
<b>Image Size (Diagonal)</b>	28" to 300"		
<b>Zoom Ratio</b>	1.15:1		
<b>Lamp Type</b>	190W		
<b>Lamp (Normal/Economic Mode)*</b>	4500/6000 hours		
<b>Keystone Adjustment</b>	1D, Vertical +/- 40 degrees		
<b>Projection Offset</b>	130%+-5%		
<b>Resolution Support</b>	VGA(640 x 480) to 1080p(1920 x 1080)		
<b>Horizontal Frequency</b>	31K~90KHz		
<b>Vertical Scan Rate</b>	48~86Hz		
<b>Compatibility</b>	HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p	
	Video Compatibility	NTSC, PAL, SECAM	
<b>Interface</b>	Computer in (D-sub 15pin)	x 1	
	Composite Video in (RCA)	x 1	
	S-Video in (Mini DIN 4pin)	x 1	
	Component Video in	x 1 (RCA x 3)	
	Audio in (Mini Jack)	x 1	
	Audio L/R in (RCA)	x 2	
	Audio out (Mini Jack)	x 1	
	Speaker	10W x 1	
	HDMI V1.3	x 2	
	USB (Type Mini B)	x 1 (USB Download & Page up/down)	
	RS232 (DB-9pin)	x 1	
<b>Dimensions</b>	Dimensions(W x H x D)	330 x 247 x 150 mm	
	Weight	3.6 kg (7.9lbs)	
<b>Power</b>	Power Supply	100 to 240 VAC, 50 to 60 Hz	
	Power Consumption	270W, Standby<1W	
<b>Audible Noise</b>	31/28 dBA (Normal/Economic mode)		
<b>On-Screen Display Languages</b>	Bulgarian/ Croatian/ Czech/ Danish/ Dutch/ English/ Finnish/ French/ German/ Greek/ Hungarian/Italian/ Indonesian/ Japanese/ Korean/ Norwegian/ Polish/ Portuguese/ Romanian/ Russian/ Simplified Chinese/Spanish/ Swedish/ Turkish/ Thai/ Traditional Chinese (26 Languages)		
<b>Picture Modes</b>	Bright/Living Room/Gaming/Cinema/User 1/User 2/User3		
<b>Accessories</b>	<b>Standard</b>	<b>Optional</b>	
	Remote Control w/ Battery	Spare Lamp Kit	P/N: 5J.J5405.001
	Power Cord (by region)	Ceiling Mount	P/N: 5J.J2K01.001
	User Manual CD		
	Quick Start Guide		
	Warranty Card (by region)		
	VGA(D-sub 15pin) Cable		

\*Lamp life results will vary depending on environmental conditions and usage. Actual product's features and specifications are subject to change without notice.

**Distance Chart**

will add in at next version

**Wall mount/Ceiling mount Chart**

will add in at next version

**Dimension**



**BenQ**