



## The All-Round Multi-Media Projector

The Vivitek D851/D853W digital projectors combine the best features, performance and value for money. The Vivitek D851/D853W include multiple connectivity options, including DVI-I and HDMI, and thanks to its DLP® technology and BrilliantColor™ they can display outstanding picture quality and saturated colors. Also thanks to its long-life lamp with up to 6000 hours operations, they're low in maintenance cost.

### Features

- Native XGA (D851) and WXGA (D853W) resolution and able to display up to UXGA (1600 x 1200)
- 3000 ANSI lumens (D851) and 3200 ANSI lumen (D853W) of brightness and a 3000:1 contrast ratio
- 3D-Ready via DLP® Link™
- High-efficiency lamps that last up to 6000 hours (in economy mode)
- VGA-output for display on a secondary monitor
- Keypad lock prevents accidental system adjustments
- Enhanced color and display adjustments
- Network-ready for integration and system administration via RJ45

Specifications	
Brightness	D851: 3000 ANSI Lumen, D853W: 3200 ANSI Lumen
Native Resolution	D851: XGA (1024 x 768), D853W: WXGA (1280x800)
Max. Resolution	UXGA (1600 x 1200)
Contrast Ratio	3000:1 (Full On/Off)
Lamp Life and Type	6000/4000 Hours (Standard/Boost Mode), 220W
Lamp Part #	5811116713-S
Throw Ratio	D851: 1.60-1.92, D853W: 1.52-1.76 (Distance/Width)
Image Size (Diagonal)	30" to 300"
Projection Distance	1 to 5m
Projection Lens	D851: F = 2.52 - 2.73, D853W: F = 2.55 - 2.72
Zoom Ratio	1.2x
Aspect Ratio	4:3 Native, 16:9 Compatible
Offset	128%
Keystone Correction	±15° Vertical
Color Spectrum	16.7 Million
Horizontal Scan Rate	15, 30 to 90 KHz
Vertical Scan Rate	43 to 85 Hz
Speaker	10 Watt Mono
Projection Method	Table Top or Ceiling Mount (Front or Rear)
Uniformity	85%
Computer Compatibility	UXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized; VESA Standards; PC and Macintosh Compatible
Video Compatibility	SDTV (480i), EDTV (480p), HDTV (576i, 720p, 1080i) thru RGB, NTSC/NTSC 4.43, PAL B/G/H/I/M/N 60, SECAM
I/O Connection Ports	HDMI v1.3, DVI-I, VGA-In, VGA-Out, Composite Video, Mini-Jack Audio-In, Mini-Jack Audio-Out, RCA Stereo-In, RJ45, RS-232c, USB (Service), microphone, 12V trigger
Security	Kensington® Lock Port
Weight	2.7 kg
Dimensions (W x H x D)	305 x 109 x 216 mm
Noise Level	33dB/36dB (Standard/Boost Mode)
Power	Supply: AC 100-240V, 50/60Hz Consumption: TBA (Standard Mode), 280W (Boost Mode), <1W (Standby Mode)
Warranty	3-Year Warranty, 1-Year or 1,000h on Lamp
Standard Accessories	AC Power Cord, VGA Cable, Remote Control, Batteries for Remote, Carrying Case, User's Manual (CD), Lens Cap, Warranty Card
Optional Accessories	Replacement Lamp, Remote, Carrying Case, ViviNet dongle for wireless presentations
UPC	D851: 814964335166, D853W: 814964335173

