

# NEC UM330Wi

Order Code: 60003428

## NEC UM330Wi Professional Interactive Ultra-Short-Throw Projector

Get great performance while saving the environment. Advanced Eco features help to substantially lower your operating cost without compromising on quality and flexibility. Less shadow and glare gives the presenter more space to engage with his audience and enhances the experience when using the integrated interactive whiteboard function.

The UM330Xi is particularly suited for classrooms and small to medium sized meeting rooms.



**HDMI™**  
HIGH DEFINITION MULTIMEDIA INTERFACE



NEC Factory Preset  
**DICOM**  
SIMULATION

### DELIVERING GENUINE BENEFITS

**Integrated interactivity** - based on eBeam® technology including application software for business and corporate users.

**Get Great Performance** - while not compromising on quality and ease of use.

**Less Shadow and Glare** - not standing in the light beam gives you more space to engage with your audience when presenting.

**Wall-mount included** - for quick and easy installation, compatible with height adjustable systems.

**Peace of Mind** - with future-proof connectivity.

**Save the Environment** - with latest Eco technology by minimizing your power consumption and consumables replacements.

**Works with various NEC Software Tools** - Including Image Express Utility Lite (WIN,MAC,iOS), Virtual Remote Tool (WIN /IOS), PC Control Utility Pro 4 / 5, Viewer PPT Converter and DisplayNote.

### OUTSTANDING PERFORMANCE

- **Integrated interactivity** transforms any flat surface into an interactive workspace
- **Ultra Short-Throw Projection** with 0.36:1 throw ratio
- **Minimized Cost of Ownership** due to long lamp life and filter cleaning intervals
- **Innovative ECO Functions** to reduce power consumption
- **Great Connectivity** due to numerous analog and digital connection terminals, network capability as well as optional wireless connection



**SPECIAL CHARACTERISTICS**

AMX Beacon, Auto Eco Mode, Auto Power ON/OFF, Carbon Savings Meter, Colour Management, Content Transmission via Network, Contrast Ratio 3000:1 with Iris, Crestron RoomView, DICOM Simulation, Direct Power-Off Function, High Altitude Mode, Including interactive module and pen, Kensington security slot, Keypad Lock, Magnify, Manual vertical Keystone Correction (V= ±10°), Off-Timer, Optional User Logo, Optional WLAN, OSD with 29 languages, Password Security System, PJ LINK, Quick On/Off, Remote control and administration via LAN and RS232, Security Bar, Test Pattern, USB Display, USB Viewer for JPEG, Virtual Remote for direct PC control, Wall Colour Correction



**ECO Innovation** Auto ECO Mode; Green one touch ECO and AV mute button; 75% AV mute function

**Energy Efficiency** ECO scheduler; Intelligent Power Management; Longer lamp life; Reduced power consumption. Only 0,4W stand-by; Software scheduling

**Ecological Materials** 100% recyclable packaging; Downloadable manuals; ECO packaging

**Ecological Standards** RoHs compliant; ErP compliant

Technical Specification NEC UM330Wi	
<b>IMAGE</b>	
Display	3 x 1.5 cm (0.59") p-Si LCD Panel with MLA
Native Resolution	1280 x 800 (WXGA)
Aspect Ratio	16:10
Brightness <sup>1</sup>	3300 ANSI Lumen (approx. 75% in Normal, 60% in Eco Mode)
Contrast Ratio <sup>1</sup>	3000:1
Lamp	265 W High Bright / 195 W Normal / 160 W Eco Mode
Lamp Life [hrs]	6000 Eco / 3500 Normal / 3000 High Bright Mode
Lens	F= 1.8, f= 4.78 mm
Projection Factor	0.36 : 1
Projection Angle [°]	53.6
Projection Distance [m]	0.46 – 0.77
Screen Size (diagonal) [cm]	Minimum: 160 / 63"; Maximum: 269.2 / 106"
Zoom	1.4 x Digital Zoom
Focus Adjustment	Manual
Supported Resolutions	1920 x 1080 (HDTV 1080i/60; HDTV 1080i/50); 1680 x 1050 (WSXGA+); 1600 x 1200 (UXGA); 1600 x 900 (WXGA++); 1440 x 900 (WXGA+); 1400 x 1050 (SXGA+); 1366 x 768 (WXGA); 1360 x 768 (WXGA); 1280 x 1024 (SXGA); 1280 x 1024 (MAC 23"); 1280 x 960 (SXGA); 1280 x 800 (WXGA); 1280 x 768 (WXGA); 1280 x 720 (HDTV 720p); 1152 x 870 (MAC 21"); 1152 x 864 (XGA); 1024 x 768 (XGA); 832 x 624 (MAC 16"); 800 x 600 (SVGA); 720 x 576 SDTV 480p/480i; 720 x 480 SDTV 576p/576i; 640 x 480 (VGA/MAC 13")
Frequency	Horizontal: 15–100 kHz (RGB: 24 kHz– 100 kHz); Vertical: 50 – 120 Hz
<b>CONNECTIVITY</b>	
RGB (analog)	Input: 1 x Mini D-sub 15-pin, compatible to component (YPbPr) Output: 1 x Mini D-sub 15 pin
HDMI™	Input: 2 x HDMI™ (Deep Color, Lip sync)
Video	Input: 1 x RCA
S-Video	Input: 1 x Mini DIN 4-pin
Audio	Input: 1 x 3.5 mm Stereo Mini Jack; 2 x RCA Stereo Output: 1 x 3.5 mm Stereo Mini Jack (variable)
PC Control	Input: 1 x D-Sub 9 pin (RS-232) (male)
LAN	1 x RJ45
USB	1 x Type B; 2 x Type A (USB 2.0 high speed)
Video Signals	PAL; PAL60; NTSC; NTSC 3.58; SECAM; NTSC 4.43; PAL-N; PAL-M
<b>REMOTE CONTROL</b>	
Remote Control	Aspect Ratio; Audio Control; Auto Adjust; AV Mute; Digital Zoom; Direct Source Select; Freeze; Help Eco Mode; Help-function; ID set; Picture Adjust; Presentation and Mouse Control
<b>ELECTRICAL</b>	
Power Supply	100-240 V AC; 50 - 60 Hz
<b>MECHANICAL</b>	
Dimensions (W x H x D) [mm]	378 x 112 x 428 (without lens and feet)
Weight [kg]	5.2
Fan Noise [dB (A)]	30 / 36 (Eco / High Bright)
<b>ENVIRONMENTAL CONDITIONS</b>	
Operating Temperature [°C]	5 to 40
Operating Humidity [%]	20 to 80 non-condensing
Storage Temperature [°C]	-10 to 50
Storage Humidity [%]	20 to 80 non-condensing
<b>OPTIONAL ACCESSORIES</b>	
Optional Accessories	Lamp (NP17LP-UM); Mouse Receiver (NP01MR); Wireless LAN module (NP02LM2/3)
<b>ERGONOMICS</b>	
Safety and Ergonomics	CE; TÜV GS; RoHS; Gost-R
Speakers [W]	1 x 16 (mono)
<b>WARRANTY</b>	
Projectors	3 years pan-European service
Lamp	6 months, max. 1000 hrs
<b>SHIPPING CONTENT</b>	
Shipping Contents	IR Remote Control (RD-448E); Mini D-SUB Signal Cable; Power Cord (3 m); Security Sticker; Interactive Module (NP02Wi); Wall-mount kit NP04WK; Users Manual on CD-ROM; Quick Setup Guide

<sup>1</sup> Compliance with ISO21118-2005