

S302

Big projection

- Bright projection 3000 ANSI Lumens
- SVGA resolution, 15,000:1 contrast ratio
- Low ownership costs up to 10,000 hours² lamp life
- Lightweight and portable, carry bag included















S302

Ideal for use in a meeting room or classroom, the S302 has a bright 3000L and 15,000:1 contrast allowing you to project bright, crystal clear images with superb colours using DLP® and BrilliantColor™ technologies. Incredible lamp life of up to 10,000 hours combined with Eco+ technology provides energy and money saving features. Installed or on the move with the included carry bag, the versatile S302 incorporates a built in speaker, 120Hz 3D Readv technology and optional wireless capabilities that are easy to use.

Bright Images

Project in ambient light conditions with the ultra bright 3000 ANSI Lumens. Ideal for meeting rooms and classrooms.

Cost Saving - Long Lamp Life

Reduce the number of lamp changes with lamp life of up to 10,000 hours² using the Education Cycle.



Clear, Focused Images

Produce a stunning 15,000:1 contrast ratio for pin sharp graphics and crystal clear text using the unique Dynamic mode feature.

Combined with DarkChip3 technology for Texas Instruments, Dynamic mode automatically adjusts the lamp output, based on the brightness information of each frame; to create a stunning high contrast ratio. Bright scenes are crisp and clear, while dark scenes remain detailed with deep blacks which gives exceptional light and shade detail.






Green Solutions



Eco⁺ technology from Optoma increases our commitment to reducing the impact we all make on the environment

Eco⁺ Mode

Saving energy saves money! Eco⁺ technology reduces the power consumption to as little as 30%. This intelligent feature can more than double your expected lamp life, lowering the total cost of ownership and reducing maintenance.



Auto Power Off

There may be instances when the projector is left running when not in use. To help save energy if the projector is left running and no source is detected, the "Auto Power Off" feature automatically turns off the projector after a set period of time.

Eco AV Mute

Stay in control of your presentation with the Eco AV mute feature. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also instantly reduces the power consumption to 25%, further prolonging the life of your lamp.



Eco AV mute off 100% power consumption

Eco AV mute on 25% power consumption



We know that improving our products is the best way to reduce our impact on the environment. That's why at Optoma we design our products to have a long usable life, use fewer materials, ship with the minimum packaging and be free of all possible toxic substances. Naturally, energy efficiency and being recyclable are built in at the design stage. With each new product, we strive towards minimising our environmental impact.

Audio Capability

Built-in 2W speaker offers excellent audio support. The S302 is easy to set up without the need for costly external speakers.



Control

RS232 Compatibility - The S302 comes with an extensive RS232 command set making it simple and easy to control with any control system. AMX Compatibility - Dynamic Discovery Protocol is incorporated into the S302. This feature allows for easy installation with AMX control systems.



Amazing Colours

The S302 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

Colour Guarantee



We are so confident that the S302 image colour quality will remain as good as the day you bought it that we will guarantee it for five years.

BrilliantColor™



The S302 incorporates BrilliantColor™ multi-colour processing technology to bring stunning, vibrant colour to your screen. Using six separate primary and secondary colours to produce a new level of colour performance and control; BrilliantColor™ increases colour brightness by up to 50% over other technologies to create accurate true to life images.

Rapid Off

It takes less than 10 seconds for the projector to power up and shutdown, saving both time and energy.

Quick Resume

Save time by not waiting for the projector to cool down before it can power up again. If the projector is accidentally turned off, this feature allows the projector to be instantly powered on again, if selected within a period of 100 seconds.



Easy Lamp Replacement

Top loading lamp cover allows easy access to replace lamps without having to remove the projector from the mount.

3D Ready

Using the inherent speed of DLP technology, The S302 can output video and images at an astonishing rate of 120Hz, allowing you to show full screen, full colour, stereoscopic 3D. Perfect for Business and Education.



Remote Mouse

Keep your audience's attention focussed on the right things using the simple, yet powerful remote with USB mouse control.

Wireless Presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the S302. Using the Wireless Adapter you can connect and display presentations and video material wirelessly from a laptop, PC or mobile device. (Additional power required)



S302 Specification

Display Technology	Single 0.55" SVGA DC3 DMD chip DLP® Technology by Texas Instruments					
Native Resolution	SVGA 800 x 600					
Brightness ¹ (Bright Mode)	3000 ANSI Lumens					
Contrast	15.000:1					
Noise Level (Eco mode)	26dB					
Weight (kg)	2.21					
I/O Connectors	2 x VGA (YPbPr/RGB), S-Video, Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out, RS232, USB (Remote Mouse)					
Preset Mode						
1 TOOCE WOOD	PC: For computer or notebook (Brightest image)					
	Movie: Maximum contrast and Colour accuracy					
	Game: Bright vivid colour					
	sRGB: For Standard PC Colour (Best Colour Reproduction)					
	User: Memorises user's settings					
Maximum Resolution	UXGA 1600 x 1200					
Computer Compatibility	UXGA, SXGA, XGA, SVGA, VGA, Mac					
Video Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)					
Displayable Colours	1073.4 Million					
Projection Lens	F/2.51~2.69; f=21.95~24.18mm, 1.1x Manual Zoom					
Throw Ratio	1.97 - 2.17:1					
Projection Screen Size	0.69 – 7.62m (27.24" - 300.04") Diagonal 4:3					
Projection Distance	1.2 - 12m					
Zoom Type	1.1x Manual					
Aspect Ratio	4:3 Native, 16:9 Compatible					
Offset	115%					
Horizontal Scan Rate	15.3 - 91.1kHz					
Vertical Scan Rate	24 - 85Hz					
Lamp Type	190W					
Lamp Life ² (hrs) (Eco mode)	6500					
Keystone Correction	± 40° Vertical					
Audio	2W					
Dimensions (W x D x H)	316 x 224 x 124					
Remote Control	Full function remote with remote mouse and direct source selecting					
Power Supply	100-240V, 50-60Hz					
Power Consumption	226W BRIGHT mode < 0.5W Standby mode, 194W Eco+ mode < 0.5W Standby mode					
Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m					
Uniformity	85%					
Security	Security Bar, Kensington Lock, Password Protection					
Standard Accessories	Carry Bag, AC Power Cord, VGA Cable, Infra Red Remote Control with Batteries, Quick Start Card, CD User Manual, Warranty Card					
Optional Accessories	Ceiling Mount Kit					
RoHS	Compliant					
3D Support	The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems.					
3D Viewing	Requires the Optoma DLP-Link shutterglasses - available separately.					
3D Compatibility	Side-by-Side: 1080i50 / 60, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60					
Speaker	2					
On Screen Display	19 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian/Danish, Hungarian, Czech, Turkish, Romanian, Farsi & Arabic					
Optional Wireless	Yes					
Features	Eco+, Up to 10,000 hours I amp I i fe Educati					

Easy To Use Remote

S302 Remote Control

- 1. Power
- 2. Mouse select
- 3. Source
- 4. Re-sync
- 5. Left mouse click
- 6. Right mouse click
- 7. Mouse control
- 8. Display mode
- 9. Page up/down control
- **10.** Vertical keystone correction
- 11. Volume control
- 12. Brightness
- **13.** Menu
- **14.** Direct input source select
- 15. Eco AV mute
- **16.** Eco+
- 17. 3D control



S302 Connections

- 18. Audio In (VGA)
- 19. S-Video
- **20.** VGA 1
- 21. VGA Out
- **22.** RS232
- 23. USB (Remote Mouse)
- 24. Audio In (S-Video/Video)
- 25. KensingtonTM Lock
- 26. Audio Out
- **27.** Video
- **28.** VGA 2



Projection Distance 1.2 - 12m (4:3 Aspect Ratio)											
Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Min Diagonal Image Size (m)	Max Diagonal Image Size (m)	Min Diagonal Image Size (inch)	Max Diagonal Image Size (inch)	Max. Image Offset (m)		
1.20	0.61	0.55	0.46	0.42	0.69	0.76	27.24	30.00	0.07		
2.00	1.02	0.92	0.76	0.69	1.15	1.27	45.40	50.01	0.11		
2.50	1.27	1.15	0.95	0.87	1.44	1.59	56.75	62.51	0.14		
3.00	1.52	1.38	1.14	1.04	1.73	1.91	68.10	75.01	0.17		
4.00	2.03	1.84	1.53	1.39	2.31	2.54	90.80	100.01	0.23		
5.00	2.54	2.30	1.91	1.73	2.88	3.18	113.50	125.02	0.29		
6.00	3.05	2.76	2.29	2.08	3.46	3.81	136.19	150.02	0.34		
7.00	3.55	3.23	2.67	2.43	4.04	4.45	158.89	175.03	0.40		
8.00	4.06	3.69	3.05	2.77	4.61	5.08	181.59	200.03	0.46		
9.00	4.57	4.15	3.43	3.12	5.19	5.72	204.29	225.03	0.52		
10.00	5.08	4.61	3.82	3.46	5.77	6.35	226.99	250.04	0.57		
11.00	5.58	5.07	4.20	3.81	6.34	6.99	249.69	275.04	0.63		
12.00	6.09	5.53	4.58	4.16	6.92	7.62	272.39	300.04	0.69		

