

W319UST

Ultra Short Throw Projector

- WXGA, super bright 3300 lumens
- Powerful 16W built-in speaker
- Large shadow-free images from a short distance
- Multiple connections including two HDMI inputs, RJ45 control and monitoring





















W319UST

The W319UST, is perfect for businesses, schools and colleges. It is bright (3300 lumens) and a throw ratio of 0.27:1 means that it can project a 100" image from less than 0.5m away. And having the projector installed so close to the screen avoids any shadows being cast across the screen from the presenter(s).

It provides a complete package for engaging learning with many new features, including two HDMI inputs, powered USB port, powerful 16W built-in speaker, improved lamp life, compact chassis and a completely new mounting system for a fast and simple set-up.

Ultra short throw



With an ultra-short throw lens, you can project an impressive image greater than 100" from just 55cm away. This allows you to place the projector closer to the wall, reducing shadows so you can present with ease; perfect for interactive applications.

High Contrast

Add more depth to your image with a high contrast projector; with brighter whites and ultra-rich blacks, images come alive and text appears crisp and clear - ideal for business and education applications.

Full 3D

Optoma projectors can display true 3D content from almost any 3D source, including 3D Blu-ray players, 3D broadcasting and the latest generation games consoles. Support for 144Hz rapid refresh rate provides ultra-smooth flicker free images.



Integrated Speaker

The built-in speaker offers excellent audio support. Easy to set up without the need for costly external speakers

Eco+



Eco+ technology brings together high contrast, improved lamp life and energy saving features that are easy to use while reducing power consumption.

Energy Saving

Using the specially designed lamp modes, you can reduce the power consumption by up to 70%. Each mode also has a positive effect on the lamp life, while lowering the total cost of ownership and reducing maintenance.

Quick Resume

This feature allows the projector to be instantly powered on again, if it is accidentally switched off.

Auto Power Off

There may be instances when the projector is left running when not in use. To help save energy, the "Auto Power Off" feature automatically turns off the projector after a set period of time if it is not being used

Eco AV Mute

Stay in control of your presentation with Eco AV mute. Direct your audience's attention away from the screen by blanking the image when no longer needed. This also reduces the power consumption by up to 70%, further prolonging the life of your lamp.

Long Lamp Life

Reduce the number of lamp changes with lamp life of up to 6500 hours.

EPSON® replacement adapter

Update your EPSON® ultra short throw projector with an Optoma UST projector without changing your existing mount or white board.



Remote Mouse

Keep your audience's attention focussed on the right things using the simple, yet powerful remote with USB mouse control.

Networking and Control

Featuring a wide range of options you can remotely control and monitor the projector.

 RS232 - Optoma projector's come with an extensive set of RS232 commands making it simple and easy to manage

- using any control system.
- AMX Compatibility Dynamic discovery protocol is incorporated into the projector allowing for easy installation with AMX control systems.
- LAN Control Using the compatible RoomView® software you can power on/off, monitor, manage and control up to 250 projectors at the same time from any computer.
 - Schedule the projectors to power on/off.
 - Control and alter the projector settings using the simple web browser.
 - Emergency text broadcast capabilities for urgent or important announcements.
 - Automatically receive email updates for lamp maintenance.







Colour Guarantee

Enjoy dazzling colours for years to come; guaranteed by Optoma for five years' consistent performance.





Amazing Colours

For vibrant, natural looking images, Optoma projectors incorporate BrilliantColor™ multi-colour processing technology.





Wireless Presenting (optional extra)

Making presentations couldn't be easier using the optional wireless features of the WPS Wireless Adapter (sold separately) - you can connect and display presentations wirelessly from a laptop, PC or mobile device.



USB Power

Use the USB-Power to power an HDMI dongle, such as Google Chromecast or the Optoma WHD200 wireless HDMI device.

W319UST Specification

Native Resolution WXGA 1280 x 800 Brightness ¹ (Bright Mode) 330 a ANSI Lumens Contrast 18,000:1 Lamp Life ² Eco+/Dynamic/Eco/Bright/Education cycle 7000/Eso00e0004500/10000 (hrs) Throw Ratio 0.27:1 Zoom Type Fixed I/O Cornectors 2 x HDMI (1.4 as D support), 2 x VGA (YPPPr/RGB), Composite, 2 x Audio in 3,5mm, Audio Out 3,5mm, VGA Out (Shared with VGA), R45, R5232, USB remote mouse/service, 12V trigger, Mic in, USB-A Power, 3D-Sync Speaker 16 Keystone Correction 2 2V Vertical Weight (Kg) 4,57 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:10 Native, 16:94-3 Compatible Offset 115% Projection Screen Size 2.16 - 2.29m (85* - 115*) Disgonal 16:10 Projection Distance 0.49 - 0.66m Projection Lines F1.24; F3.27mm, Fixed Zoom Uniformity 85% Computer Compatibility UXSA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL, 6, 0, G, H, IM, N, 576/lp), NTSC (M, 4.43:55 MHz, 480/lp), SECAM (B, D, G, K, K1, L) HD (1080), 720p) 3D Support Film 30 Features of Optiona projectors	Display Technology	Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments
Contrained Con	Native Resolution	WXGA 1280 x 800
Contrast	Brightness ¹ (Bright Mode)	3300 ANSI Lumens
cycle Notestable 0.27:1 Zoom Type Fixed IVO Connectors 2 x HDMI (1.4 a 30 support), 2 x VGA (YPbPrRGB), Composite, 2 x Audio in 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction 4 20* Vertical Weight (kg) 4.57 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:10 Native, 16:94:3 Compatibile Offset 115% Projection Screen Size 2.16 – 2.92m (85* - 115*) Diagonal 16:10 Projection Lens Fiz.4; 163.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, WGA, Mac Video Compatibility VAL, (B, D, G, H, I, M, N, 576l/p), NTSC (M, 4.43/3.58 MHz, 480l/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D 17 broadcast systems, (SYY in the UK), Blu-ray 3D** and 3D games from the S		18,000:1
Throw Ratio 0.27:1 Zoom Type Fixed I/O Connectors 2 x HDMI (1 4a: 30 support), 2 x VGA (YPPP/RGB), Composite, 2 x Audio in 3.5mm, Audio Out 3.5mm, VGA Out (Shared with VGA2), RJ45, RS232, USB remote mouse/service, 12V trigger, Mic In, USB-A Power, 3D-Sync Speaker 16 Keystone Correction ± 20° Vertical Weight (kg) 4.57 Dimensions (W x 0 x H) (mm) 385 x 310 x 120 Aspect Ratio 16:10 Native, 16:94:3 Compatible Offset 115% Projection Screen Size 2.16 − 2.9m (85° − 115°) Diagonal 16:10 Projection Distance 0.49 + 0.66m Projection Distance 0.49 + 0.66m Video Compatibility UXGA, SXGA, WXCA, HD, XGA, SVGA, VGA, Mac Uniformity 85% Computer Compatibility UXGA, SXGA, WXCA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 30 - The 3D Teatures of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 30 educational or 30 design and modelling systems. 3D 17 broadcast systems, (SYr in the UX). 3D Compatibility Side-Sy-Sidect 108007 60 7, 72		7000/6500/6000/4500/10000 (hrs)
Zom Type		0.27:1
Connectors		
Keystone Correction ± 20" Vertical Weight (kg) 4.57 Dimensions (W x D x H) (mm) 365 x 310 x 120 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 2.16 – 2.92m (85" – 115") Diagonal 16:10 Projection Lens F124, 1fe3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H. I, M. N., 576/lp), NTSC (M, 44/3/3.58 MHz, 480/lp), SECAM (B, D, G, K. K1, L) HD (10801, 720p) 3D Support Full 3D - The 3D features of Optional projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems. (SKY in the UK), Blu-ray 3D ™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080150 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Userical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 268B		2 x HDMI (1.4a 3D support), 2 x VGA (YPbPr/RGB), Composite, 2 x Audio In 3.5mm, Audio Out 3.5mm, VGA Out (Shared with
Weight (kg) 4.57 Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 2.16 − 2.92m (85° − 115°) Diagonal 16:10 Projection Distance 0.49 − 0.66m Projection Lens Fiz.4; F3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (8, D, G, H, I, M, N, 576/p), NTSC (M, 4.43/3.58 MHz, 480/p), SECAM (8, D, G, K, K1, L) HD (1080), 720p) 3D Support Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 30 educational or 30 design and modelling systems. 3D TV broadcast systems (KRY in the UK), Blu-ray 3D ™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side: 1080/60 / 60, 720,p50 / 60 Frame-pack: 1080/p24, 720,p50 / 60 Fortier Scan Rate 15.3 - 91 TkHz Vertical Scan Rate 15.3 - 91 TkHz Vertical Scan Rate 16.3 - 91 TkHz Vertical Scan Rate 10.7 Billion Noise Level (Eco mode) 266B Po	Speaker	16
Dimensions (W x D x H) (mm) 385 x 310 x 120 Aspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Size 2.16 − 2.92m (86" − 115") Diagonal 16:10 Projection Lens F.72.4; F.3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576!p), NTSC (M, 4.43/3.58 MHz, 480!r), SECAM (B, D, G, K, K1, L) HD (10801, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1980150 / 60, 720p50 / 60 Vertical Scan Rate 15.3 - 91 fkHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Usiplayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)	Keystone Correction	± 20° Vertical
Āspect Ratio 16:10 Native, 16:9/4:3 Compatible Offset 115% Projection Screen Size 2.16 – 2.92m (85" – 115") Diagonal 16:10 Projection Distance 0.49 - 0.66m Projection Lens F/2.4; +3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling syems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080160 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)		4.57
Offset 115% Projection Screen Size 2.16 − 2.92m (85" − 115") Diagonal 16:10 Projection Distance 0.49 − 0.66m Projection Lens F72.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576ip), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D − The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK). Bilu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i60 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Vertical Scan Rate 15.3 • 91.1kHz Vertical Scan Rate 15.3 • 91.1kHz Vertical Scan Rate 16.3 • 91.1kHz Vertical Scan Rate 16.3 • 91.1kHz Power Consumption 26MB Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)	Dimensions (W x D x H) (mm)	385 x 310 x 120
Projection Screen Size 2.16 − 2.92m (85" − 115") Diagonal 16:10 Projection Distance 0.49 - 0.66m Projection Distance Fi2.4; f=3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 30 - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side-1080150 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 86Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)	Aspect Ratio	16:10 Native, 16:9/4:3 Compatible
Projection Distance 0.49 - 0.66m Projection Lens F72.4; F∈3.72mm, Fixed Zoom Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)	Offset	115%
Projection Lens	Projection Screen Size	2.16 – 2.92m (85" – 115") Diagonal 16:10
Uniformity 85% Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576/jp), NTSC (M, 4.43/3.58 MHz, 480/jp), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems (SKY in the UK), Blur-ay 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 23SW Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar. Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Warranty 3		0.49 - 0.66m
Computer Compatibility UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.437,58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080160 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Fore-Pack: 1080p24, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Vertical Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Supply 190-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)	Projection Lens	F/2.4; f=3.72mm, Fixed Zoom
Video Compatibility PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p) 3D Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby)	Uniformity	85%
Support Full 3D - The 3D features of Optoma projectors can only be used with compatible 3D content. Typical applications include use with 3D educational or 3D design and modelling systems, 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D ™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24. + 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Wireless Ves Warranty 3	Computer Compatibility	UXGA, SXGA, WXGA, HD, XGA, SVGA, VGA, Mac
with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a specification. 3D Compatibility Side-by-Side:1080i50 / 60, 720p50 / 60 Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories Yes Warranty 3	Video Compatibility	PAL (B, D, G, H, I, M, N, 576i/p), NTSC (M, 4.43/3.58 MHz, 480i/p), SECAM (B, D, G, K, K1, L) HD (1080i, 720p)
Frame-pack: 1080p24, 720p50 / 60 Over-Under: 1080p24, 720p50 / 60 Horizontal Scan Rate 15.3 - 91.1kHz Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories Yes Warranty 3	3D Support	with 3D educational or 3D design and modelling systems. 3D TV broadcast systems, (SKY in the UK), Blu-ray 3D™ and 3D games from the Sony® PS3 or Microsoft® Xbox 360 are now supported as part of the HDMI v1.4a
Vertical Scan Rate 24 - 85Hz (120Hz for 3D) Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security ber, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	3D Compatibility	Frame-pack: 1080p24, 720p50 / 60
Displayable Colours 1.07 Billion Noise Level (Eco mode) 26dB Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories Optional Wireless Yes Warranty 3	Horizontal Scan Rate	15.3 - 91.1kHz
Noise Level (Eco mode) Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories Optional Wireless Yes Warranty 3	Vertical Scan Rate	24 - 85Hz (120Hz for 3D)
Power Supply 100-240V, 50-60Hz Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	Displayable Colours	1.07 Billion
Power Consumption 235W Bright mode / 200W Eco mode (< 0.5W Standby) Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	Noise Level (Eco mode)	26dB
Lamp Type 190W Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3		100-240V, 50-60Hz
Operating Conditions 5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	Power Consumption	235W Bright mode / 200W Eco mode (< 0.5W Standby)
Security Security bar, Kensington lock, password protection On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	Lamp Type	190W
On Screen Display 25 Languages: English, German, French, Italian, Spanish, Portuguese, Swedish, Dutch, Norwegian/Danish, Polish, Russian, Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	Operating Conditions	5°C - 40°C, Max. Humidity 85%, Max. Altitude 3000m
Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Simplified Chinese, Japanese, Korean, Thai, Turkish, Farsi, Romanian, Slovenian Standard Accessories AC power cord, VGA cable, remote control, battery, quick start card, CD user manual Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	Security	
Optional Accessories 3D glasses, wireless, wall mount, interactive module Optional Wireless Yes Warranty 3	On Screen Display	Finnish, Greek, Hungarian, Czech, Arabic, Traditional Chinese, Šimplified Chinese, Japanese, Korean, Thai, Turkish, Farsi,
Optional Wireless Yes Warranty 3	Standard Accessories	AC power cord, VGA cable, remote control, battery, quick start card, CD user manual
Warranty 3	Optional Accessories	3D glasses, wireless, wall mount, interactive module
	Optional Wireless	Yes
RoHS Compliant	Warranty	3
	RoHS	Compliant



Optoma Europe Ltd. 42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ www.optoma.co.uk

¹Lamp based projectors brightness and lifetime will vary depending on selected projector mode, environmental conditions and usage. As is common with all lamp based projectors, brightness will decrease over the lamp lifetime. LED projectors do not have a replaceable lamp and the brightness does not decay significantly over the product lifetime.

 2 Typical lamp life achieved through testing. Will vary according to operational use and environmental conditions

15/04/2016 07:31