

Key Features

SuperColor: Amazing Color Accuracy | 3,600 Lumen

Brightness | Energy Efficient SuperEco | Reduced Input

Latency



Product Description

The ViewSonic® PA503W price-performance projector features 3,600 lumens, native WXGA 1280x800 resolution, and an intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wider color range for lifelike image projection. The PA503W also features extensive connectivity including HDMI, 2 x VGA In, Composite Video, 1 x VGA output, and Audio In/out. An energy-saving SuperEco™ feature reduces power consumption by up to 70%, and extends the lamp life by up to 10,000 hours*. With advanced audiovisual features, flexible connectivity options, and an affordable price, the PA503W is ideal for use in education and small business environments.


*Energy consumption and lamp life may vary based on actual usage and other factors.



- | | |
|------------------------|------------------|
| 01. Projection lens | 05. VGA x2 |
| 02. IR remote sensor | 06. HDMI |
| 03. Elevation foot | 07. Audio In/Out |
| 04. Focus / zoom rings | 08. AC In |




- | | |
|-------------------|---------------------|
| 09. Control Panel | 13. Video In |
| 10. Monitor Out | 14. USB type Mini B |
| 11. Kensington* | 15. RS232 |
| 12. Lock Slot | |



1280 x 800
RESOLUTION



3,600
LUMENS



1.55~1.70
THROW RATIO

Contact Sales

- call: [888.881.8781](tel:888.881.8781)
- email: salesinfo@viewsonic.com
- visit: viewsonic.com

Display:

Type:	DLP
Resolution Type:	WXGA
Resolution:	1280 x 800
Brightness (ANSI Lumens):	3,600
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	3.28 - 36.02 ft / .99 - 10.98 m
Throw Ratio:	1.55~1.70
Keystone:	Vertical (± 40°)
Lens:	1.1x optical zoom
Light Source (watt):	200
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22,000:1
Aspect Ratio:	16:10

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120MHz

Compatibility:

PC Resolution (max):	VGA(640 x 480) to FullHD(1920 x 1080)
Mac® Resolution (max):	VGA(640 x 480) to FullHD(1920 x 1080)

Connector:

3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI(1), VGA In(2), VGA Out(1), Composite RCA Video In(1), Mini USB(1)

Audio:

Internal Speakers:	2W
--------------------	----

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
--------------	-----------------------

Weight (imperial):

Net (lbs):	4.9
Gross (lbs):	7.1

Weight (metric):

Net (kg):	2.2
Gross (kg):	3.2

Dimensions (imperial) (WxHxD):

Packaging (in.):	14.4 x 7.4 x 11.8
Physical (in.):	11.6 x 4.3 x 8.6

Dimensions (metric) (WxHxD):

Packaging (mm):	365 x 188 x 300
Physical (mm):	294 x 110 x 218

General:

Regulations: FCC (including ICES003), cTUVus, NOM, TUV-Rheinland S Mark
PACKAGE CONTENTS: PA503W projector, power cable, VGA cable, laser remote control with batteries, Quick Start Guide, ViewSonic Wizard CD (with User Guide)
Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp. 1st year free Express Exchange® service. (One year Express Exchange Service requires product registration).
Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.
UPC: 766907904918

Accessories:

PGD-350, PJ-CASE-008, PJ-WMK-006, PM-FCP, RLC-109
