

PJD6240

LIGHT, BRIGHT AND PORTABLE PROJECTOR

with BrilliantColor™

Digital clarity in a portable projector.

The PJD6240 is the lightweight BrilliantColor™ projector that is a feature-rich performer delivering more vibrant colors and crisp, sharp images. The high brightness and contrast ratios, combined with key-stone correction and zoom lens ensure this projector delivers your presentation perfectly. Enjoy network control through the RJ-45 input, while the extensive input options and integrated 2x5-watt stereo speakers offer a truly dynamic multimedia experience. This projector even features closed captioning for the hearing impaired. Mount this projector on the ceiling for use in classrooms or meeting rooms or use on a table top. The conveniently placed lamp access makes maintenance a breeze on the PJD6240. The PJD6240 is ideal for use in classrooms and corporate settings.



VERSATILE PRESENTATIONS MADE EASY

- > **Network control through RJ-45**
Schedule, manage and monitor the projector remotely and receive e-mail alerts of projector and lamp status.
- > **Bright in virtually any setting with 3,200 lumens**
Packs 3,200 lumens in just 6.7 lbs. It's the bright choice for mobile presenters.
- > **BrilliantColor technology**
DLP® projectors with BrilliantColor™ feature multi-color processing to produce nearly 50% brighter colors for a vibrant image on the screen that won't fade over time.
- > **Closed captioning**
Integrated closed captioning decoder for the hearing impaired.
- > **Easy lamp replacement**
Convenient top loading allows for quick and easy lamp replacement.
- > **Eco-mode extends lamp life**
Extend the life of your lamp up to 4,000 hours* and reduce noise output.
- > **Industry leading warranty**
3-year limited warranty on parts, 1-year or 1,000 hours (whichever comes first) on lamp, and first year Express Exchange® service.



PJD6240



LIGHT, BRIGHT AND PORTABLE PROJECTOR WITH BrilliantColor™



Optional Accessories

- > Replacement lamp RLC-037
- > Universal ceiling mount kit WMK-005
- > Wireless G presentation gateway WPG-150
- > 2nd & 3rd year extended warranty PRJ-EE-03-03

Projection Distance 4:3 Screen		Screen Size 4:3 Screen	
m	feet	m	Inch
1.2	3.94	1.0-0.8	27.3-30.1
2	6.56	1.2-1.3	45.6-50.0
3	9.84	1.7-1.9	68.4-74.9
5	16.4	2.9-3.2	113.9-124.9
10	32.81	5.8-6.4	227.8-249.8



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by the British Standards Institution.



DISPLAY	Type	0.55" Digital Micromirror Device (DLP®)
	Resolution	XGA 1024x768 (native) / SXGA 1280x1024 (compressed)
	Lens	1.1x Manual Optical Zoom / Manual focus
	Keystone	Vertical Digital keystone correction: +/- 40 degrees
	Size	30"-300" (Diagonal) / 0.8m-7.6m
	Throw Distance	1.2m-10m (47"-393")
	Throw Ratio	1.97:1~2.16:1
	Lamp	260 watt
	Lamp Life (Normal / Eco Mode)	3500 / 4000* (hours)
	Brightness	3,200 Lumens
	Contrast Ratio	2000:1 (typ)
	Aspect Ratio	4:3 (native) / 16:9
	Color Gamut	85% NTSC (CIE 1931)
AUDIO	Speakers	2 x 5w
INPUT SIGNAL	Computer and Video	RGB analog, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N, 60), SECAM, SDTV / EDTV (480i/p, 576i/p), HDTV (720p, 1080i/p)
	Frequency	Fh: 15-100 KHz, Fv: 43-85 Hz
COMPATIBILITY	PC	Analog / : VGA up to SXGA (scaled)
	Mac	Analog / : up to XGA (scaled)
CONNECTOR	RGB Input / Output	2 x in / 1 x out (15-pin D-sub)
	Composite Input	1 x RCA jack
	S-Video Input	1 x 4-pin mini-DIN
	Audio Input / Output	in x1 / out x1 (3.5mm Mini Jack)
	USB	1 x USB type B (firmware upgrade only)
	Control	1 x RS232 (6 pin D-Sub)
	Network	1 x RJ-45
POWER	Voltage	100~240VAC (Auto Switching), 50/60Hz (universal)
	Consumption	350W (typ.) / 9W (Stand-by mode)
CONTROLS	Basic	Standby / On, input, menu
	OSD	<p>Picture: brightness, contrast, color setting, keystone, aspect ratio, image, white intensity, gamma</p> <p>Computer image: frequency, tracking, H position, V position</p> <p>Video image: saturation, sharpness, tint</p> <p>Sound: volume, mute</p> <p>Setting: menu position, projection, signal type, lamp hour, lamp hour reset, power saving, auto source, ECO mode, high altitude, OSD timeout</p> <p>Option: blank screen, start-up screen, screen capture, password, DCR, closed caption, network control, BrilliantColor™</p> <p>Network config: DHCP, IP address, subnet mask, gateway</p> <p>Factory default</p>
OPERATING CONDITION	Temperature	32°F-104°F (0°C-40°C)
	Humidity	10% - 80% (non-condensing)
	Altitude	0 to +30,000 ft (9,144 m)
NOISE LEVEL		39 (Normal) / 36 (Eco-mode)
DIMENSIONS	W x H x D	8.93" x 4.3" 8.77" (271mm x 110mm x 223mm)
WEIGHT	Net	6.7 lbs (3.0 kg)
	Gross	11.2 lbs (5.1 kg)
REGULATIONS		CB, UL/cUL, FCC-B, ICES-003, IRAM, NOM, CE, GS, GOST- R, Hygienic, SASO, UKrSEPRO, CCC, C-tick, EK
PACKAGE CONTENTS		Projector, Power cable, VGA cable, Remote control with batteries, Composite cable, S-video cable, Soft carrying case, Lens cap, Quick Start Guide, ViewSonic Wizard CD (with User Guide), VGA-component adapter
WARRANTY	Projector Warranty	3 years limited
	Lamp Warranty	1 year or 1,000 hours

Sales: (888) 881-8781 • SalesInfo@ViewSonic.com • ViewSonic.com

*Running eco-mode exclusively can extend lamp life. DLP® and the DLP logo are registered trademarks of Texas Instruments and BrilliantColor™ is a trademark of Texas Instruments. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2008 ViewSonic Corporation. All rights reserved. [14116-00B-08/08] PJD6240-1

For more product information, visit us on the web at ViewSonic.com