

HD22 - Home Theater Projector

Dynamic Performer

The Optoma HD22 performs flawlessly and delivers a dynamic big-screen experience! With 1900 ANSI lumens and 5000:1 contrast, the HD22's true 1080p resolution brings excellent color saturation and subtle details to dazzling life. Weighing only 6.4 lbs., this sleek performer is perfect for sharing entertainment - big-screen movies, sporting events, concerts and video gaming.





- Bright at 1900 ANSI lumens and high contrast ratio of 5000:1
- Native 1080p DLP® chipset and BrilliantColor™ technology by **Texas Instruments**
- Zero dead pixel guarantee for additional peace of mind
- ISF Certified Calibration Controls with Day & Night modes
- Perfect for connecting to any home entertainment device with HDMI, component, composite and VGA
- Project up to 300" screen size for large group viewing















Specifications

Display Type Single 0.65" 1080p DMD DLP Technology by Texas Instruments

Resolution Native 1080p (1920x1080)

Brightness (Typical) 1900 ANSI Lumens

Contrast Ratio 5000:1 (Full On/Full Off)

Lamp Life and Type 4000/3000 Hours (STD/Bright) 230W P-VIP

Throw Ratio 1.5 to 1.8:1 (Distance/Width)

Projection Distance 4.92' to 32.8' (1.5 to 10m)

Image Size (Diagonal) 37.6" to 301.1" (0.95 to 7.64m)

Aspect Ratio 16:9 Native, 4:3 and LBX Compatible

Displayable Colors 1.07 Billion

Uniformity 70%

Remote Control Backlit Remote Control

User Controls Complete On-Screen Menu Adjustments in 21 Languages Computer Compatibility

HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible

Video Compatibility NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)

Projection Lens F= 2.55-2.87, f= 22.4-26.8mm, 1.2x Manual Zoom and Focus

Horizontal Scan Rate 15.3 to 91.1 KHz

Vertical Refresh Rate 24 to 85 Hz

I/O Connectors

Two HDMI, VGA-In, Component Video, Composite Video and +12V Trigger

Security

Kensington® Lock Port, Security Bar and Keypad Lock

Projection Method Front, Rear, Ceiling Mount, Table Top

Offset 116%

Weight 6.4 lbs (2.9kg)

Dimensions (W x H x D) 12.76" x 3.82" x 9.21" (324 x 97 x 234 mm)

Noise Level (STD/Bright) 29dB/31dB

Keystone Correction ± 5° Vertical

Operating Temperature 41° to 95°F (5° to 35°C), 80% Max Humidity

Power Supply AC Input 100-240V, 50-60Hz, **Auto-Switching**

Power Consumption 308 Watts (Bright), 254 Watts (STD), <1 Watt (Standby)

Standard Accessories

AC Power Cord, Composite Video Cable, Remote Control, Batteries for Remote, Lens Cap, User's Manual, Quick Start Card and Warranty Card

Optional Accessories

Ceiling Mount, Component Cable, HDMI Cable, Composite Video Cable and Panoview™ Series Screens

Warranty

Up to 3 Years Optoma Express Replacement Service, Up to 1 Year on Lamp

UPC 796435 81 113 6

Accessory Part Numbers

Lamp: BL-FP230D Remote: BR-3042B Mount:BM-5001U Case: BK-4028

