

Key Features

- Full HD 1080p with 3 SXRD[™] 1920x1080 Panels
- Up to 60,000:1 Contrast Ratio² (Advanced Iris On)
- Brightness of 800 ANSI lumens³
- 200W Ultra-High-Pressure Lamp
- BRAVIA Engine[™] 2 fully digital video processing
- Advanced Iris 2
- 24p True Cinema[™]
- = x.v.Color^{™ 4}
- Deep Color
- ARC-F (All Range Crisp Focus) Lens
- Noise reduction functions
- Panel Alignment function (Shift & Zone)
- Anamorphic Zoom Mode
- = 1.6x Zoom Lens

Key Technologies



Full HD 1080p with 3 SXRD[™] 1920 x 1080 Panels Three SXRDTM 1920 x 1080p micro-display panels support Full HD 1080p resolution for an impressive combination of vivid color, film-like image quality, and high-definition brilliance. Enjoy cinematic-quality images.

200W Ultra-High-Pressure Lamp A 200W Ultra-High-Pressure Lamp delivers natural color with a brightness of 800 ANSI lumens³.

BRAVIA Engine[™] 2 BRAVIA Engine 2 fully digital video processor uses a collection of unique Sony[®] algorithms to significantly reduce noise, enhance overall image detail, and optimize contrast so every scene produces sharp, vibrant, life-like images.

Advanced Iris 2 The Advanced Iris 2 function provides up to a 60,000:1 contrast ratio² by optimizing both dark and bright scenes to produce deep black levels with stunning details.

24p True Cinema[™] 24p True Cinema technology provides a direct connection to 24p video sources so you can avoid conversions and enjoy films at their intended 24 fps (frames per second).

x.v.Color[™] x.v.Color technology takes HD color expression to new levels. When connected to x.v.Color capable video sources, such as select Sony[®] camcorders, the VPL-VW70 can display nearly twice as many (1.8x) viewable colors as the existing RGB color standard, resulting in more natural, life-like images.

Deep Color By combining a 10-bit processor with 10-bit SXRD[™] panels, the VPL-VW70 can create and display 64 times the level of color expression of 8-bit projectors, resulting in smoother color gradations and helping to avoid a "paint-by-numbers" look.

ARC-F (All Range Crisp Focus) Lens A specially developed ARC-F (All Range Crisp Focus) lens takes full advantage of the SXRD[™] panels to deliver Full HD 1080p resolution with superior clarity and focus.

Noise reduction functions The VPL-VW70 features noise reduction functions that analyze scenes in real time to identify various types of noise and reduce unwanted artifacts, such as mosquito noise and block noise, without compromising the video signal.

Panel Alignment function A Panel Alignment function enables pixel alignment to within 1/10th of a pixel⁶, making it possible to shift the entire picture or specific zones to adjust for color gaps and produce a brighter, clearer, and more detailed picture.





🛛 x.v.Color



SXRD

VPL-VW70

Features

General

Vertical Keystone: Yes

High Altitude Mode: Off. On

Information Menu: Horizontal and Vertical frequency display

Acceptable Computer Signals: fH: 19 to 72 kHz, fV: 48 to 92 Hz, fV: 60 Hz

Input A: 15 Pin Auto, Computer, Component, Video GBR Display

Display Technology: SXRD[™] Technology

Video

Video Processing: BRAVIA Engine™ 2 Technology

Vertical Position: Yes

Dot Phase: Yes

Title Area Control: Yes

Film Mode: Yes

Acceptable Video Signals: Composite video, Y/C video, 15 kHz (RGB/Component) 50/60Hz; Progressive component 50/60 Hz; DTV (480/60i, 480/60p, 575/50i, 575/50p, 720/50p, 720/60p, 1080P24sF(48i),1080/50i, 1080/50p, 1080/60i), HDMI inputs only: 1080/60p, 1080/24p

10-bit Video Processing: Yes

3D Comb Filter: Yes

x.v.Color[™] Technology: Yes

Lens Shift Function: Via Lens Shift Vertical Size: Yes

Convenience

Multiple Language Display: 15 languages (including English, French, Spanish, German and Chinese) Auto Input Search: Yes Test Pattern: Yes Image Flip: HV, H, V, Off IR Receiver: Front & Rear, Front, Rear Illumination: Logo (Off, On) Remote Control: Yes (RM-PJVW70)

Specifications

General

Projection Picture Size: 40" to 300" measured diagonally Television Type: HD Front Projectors

Display

Screen Size (measured diagonally): 40" to 300" measured diagonally (projected)

Native Resolution: 1080p

Display Resolution: 1920 x 1080 (Full HD) Aspect Ratio: 16:9

TV System

Color System: Auto, NTSC, PAL, SECAM

Video

Contrast Ratio: Up to 60,000:1 (with Advanced Iris Auto ON)

Brightness: 800 Lumens

Inputs and Outputs

Component Video (Y/Pb/Pr) Input(s): 2 (Side): 1 (RCAx3), 1 (15 Pin HD)

Composite Video Input(s): 1 (Side) Vp-p+/-2 dB sync negative (75 ohms terminated)

S-Video Input(s): Y/C mini DIN 4-pin type, Y (luminance): 1 Vp-p+/-2 dB sync negative (75 ohms terminated) C (chrominance): burst 0.286 1 Vp-p+/-2 dB (NTSC) sync negative (75 ohms terminated) burst 0.3 1 Vp-p+/-2 dB (PAL) sync negative (75 ohms terminated)

PC Video Input(s): Yes

- 40" to 300" (Diagonally) BRAVIA® SXRD[™] VW Series Projector
- Remote Network Connection(s): 1 (Side) RS-232C: Dsub 9-pin (female)
- HDMI[™] Connection(s) (Total): 2 (Side) Digital RGB/Y/Cb (Pb)Cr(Pr) with PC timing support¹
- RS-232C Input(s): Yes
- 12V Trigger Output(s): 2 Mini Jack Power On: DC 12V. output impedance: 4.7 kilohms Power Off: 0V

Power

Power Consumption (in Operation): 320W max

Power Consumption (in Standby): 8W; 0.5W in low mode

Power Requirements: AC 100-240V, 1.4-3.2A, 50/60Hz

Operating Conditions

Operating Temperature: 5°C to 35°C (41°F to 95°F)

Operating Humidity: 35% to 85% (condensation)

Service and Warranty Information

Limited Warranty Term: Product Warranty - 2 Years Parts and Labor except the lamp. Lamp Warranty - 90 Days from date of purchase.

Dimensions

Weight: 26 lbs Measurements: 16 1/8 x 7 1/8 x 18 3/8 in

Supplied Accessories

Remote Control (RM-PJVW70) Instruction Manual AC Cord CD ROM (Image Director 3) Size AA (R6) batteries x2

Optional Accessories

Ultra High Pressure Replacement Lamp (LMP-H201) Black Ceiling Mount (PSS-H10)

UPC Code: 027242754416

owners

- 1. Anamorphic lens is not available from Sony®. 2. 60,000:1 contrast ratio achieved with Advanced Iris Auto ON.
- ANSI lumens is a measuring method of the American National Standards Institute IT7.228. Since there is no uniform method of measuring brightness, specifications will vary among manufactures. 4. When used with supporting video sources such as select Sony
- camcorders. 5. Pixel convergence to 1/10th inch is calculated as ± 2.0 dot by 0.1 dot pitch. Depending on the adjustments made, the number of display
- pixels may decrease. Also, colors may become uneven or the resolution may change 6. BRAVIA Sync™ works with select Sony® HDTVs, front projectors, and
- home theater products. Check owners' manuals for compability © 2009 Sony Electronics Inc. All rights reserved. Reproduction in whole or

2009 Softy Electionics in C. Alinghis testeved, Reproduction in whole on in part without written permission is prohibited.
Sony, HDNA, BRAVIA, BRAVIA Engine, Remote Commander, SXRD, 24p True Cinema, xv. Color, Handycam and their respective logos are trademarks of Sony, HDMI, the HDMI logo, and High-Definition Multimedia Interface are trademarks of HDMI Licensing LIC. Burray Disc is a trademark. All other trademarks are trademarks of their respective

Non-metric weights and measurements are approximate and may vary.