



Key Features

- 3,500 ANSI Lumens with native Full HD 1080p
- Energy-efficient SuperEco+ Mode for lamp life up to 20,000hrs
- Vertical lens shift
- vColorTuner to exchange color profile and adjustment easier
- Projector software update tool to easily upgrade your functionality up to date



Product Description

The ViewSonic PX701HDH is a high brightness 3,500 ANSI lumens projector featuring a Full HD 1080p resolution that offers impressive visual performance in a brightly lit living room or meeting room. The projector adopts the latest lamp design to extend lamp life of up to 20,000 hours under SuperEco+ mode, effectively reducing lamp replacement and maintenance costs. A digital lens shift allows users to make adjustments by remote control, it's also compatible with the vColorTuner function for color profile exchange and adjustments. The dual HDMI inputs and USB power supply allow users to connect to a multitude of multimedia devices for gaming, movies, or a wireless dongle for wireless presentation.



1. Keypad
2. LED Indicator
3. Power Key
4. Zoom/Focus
5. Projection Lens
6. Front IR
7. Audio In/Out

8. HDMI
9. USB Type A
10. RS232
11. Kensington Lock

VENDOR

Vendor: Qisda

SPECIFICATION

Native Resolution: 1920x1080
 DMD Type: DC3
 Brightness: 3500 (ANSI Lumens)
 Contrast Ratio with SuperEco Mode: 12000:1
 Display Color: 1.07 Billion Colors
 Light Source Type: Lamp
 Light Source Life (hours) with Normal Mode: 5000
 Light Source Life (hours) with SuperEco Mode: 20000
 Lamp Watt: 203W
 Lens: F=2.0-2.05, f=15.843-17.445mm
 Projection Offset: 110% +/-6%
 Throw Ratio: 1.5-1.65
 Optical Zoom: 1.1x
 Digital Zoom: 0.8x-2.0x
 Image Size: 30"-300"
 Throw Distance: 1m-10.96m(100"@3.32m)
 Keystone: +/- 40° (V)
 Lens Shift V. Range: +/- 5% (Digital)
 Audible Noise (Normal): 31dB
 Audible Noise (Eco): 27dB
 Input Lag: 16ms
 Resolution Support: VGA(640 x 480) to WUXGA_RB(1920 x 1200)*RB-Reduced Blanking
 HDTV Compatibility: 480i, 480p, 576i, 576p, 720p, 1080i, 1080p
 Video Compatibility: NTSC, PAL, SECAM
 Horizontal Frequency: 15K-102KHz
 Vertical Scan Rate: 23-120Hz

INPUT

HDMI: 2 (HDMI 1.4/ HDCP 1.4)
 Audio-in (3.5mm): 1

OUTPUT

Audio-out (3.5mm): 1
 Speaker: 10W
 USB Type A (Power): 1 (5V/1.5A)

CONTROL

RS232 (DB 9-pin male): 1
 USB Type A (Services): 1(share with USB A Output)

OTHERS

Power Supply Voltage: 100-240V+/- 10%, 50/60Hz(AC in)
 Power Consumption: Normal: 300W Standby: <0.5W
 Operating Temperature: 0~40°C
 Carton: Brown
 Net Weight: 2.59kg
 Gross Weight: 3.75kg
 Dimensions (WxDxH) with Adjustment Foot: 312x222x108mm
 Packing Dimensions: 415x168x297mm
 OSD Language: English, French, Spanish, Thai, Korean, German, Italian, Russian, Swedish, Dutch, Polish, Czech, T-Chinese, S-Chinese, Japanese, Turkish, Portuguese, Finnish, Indonesian, India, Arabic, Vietnamese, Greek, Total 23 languages
 User Guide Language: English, S-Chinese, T-Chinese, Indonesian, Finnish, French, German, Italian, Japanese, Korean, Polish, Portuguese, Russian, Spanish, Swedish, Turkish, Arabic, Czech, Thai, Vietnamese, Total 20 languages

STANDARD ACCESSORY

Power Cord: 1
 Remote Control: 1
 QSG: Yes
 Warranty Card: Yes (CN Only)

OPTIONAL ACCESSORY

Lamp/Light Source: RLC-119
 Wall/Ceiling Mount: PJ-WMK-007
 Carry Bag: PJ-CASE-008