



PS600W

Key Features

SuperColor: Amazing Color Accuracy | Large Images In Small Spaces | 3,500 Lumen Brightness | Horizontal and Vertical Keystone | Long Lamp Life



Product Description

The ViewSonic® PS600W networkable projector features 3,500 lumens, native WXGA 1280x800 resolution, and an intuitive, user-friendly design. Exclusive SuperColor™ technology offers a wide color gamut for beautiful image production in nearly any environment, and a 10W speaker delivers incredibly clear and audible sound. A short throw lens with a 0.49 throw ratio offers large projection images for smaller rooms. With HV keystone, corner adjustment, and easy network management, the PS600W provides flexible setup. Designed with smarter features and extensive connectivity, the networkable short throw PS600W is ideal for use in education and corporate environments.



1. Menu Controls
2. Elevation Feet
3. Zoom Ring
4. IR Remote Sensor
5. Projection Lens
6. USB Mini
7. USB 2.0 Type A
8. HDMI (x2)
9. Audio In
10. Audio Out
11. AC In
12. VGA In (x2)
13. Monitor Out
14. LAN
15. Video
16. Kensington® Lock Slot
17. RS232

Display:

Type:	DLP
Resolution Type:	WXGA
Resolution:	1280 x 800
Brightness (Lumens):	3,500 ANSI
Display Size (in.):	30 - 300 in. / 0.76 - 7.62 m
Throw Distance:	2.1 - 6.2 ft / 0.6 - 1.9 m
Throw Ratio:	0.5
Keystone:	Vertical ($\pm 40^\circ$) / Horizontal ($\pm 26^\circ$)

Lens:	Fixed Zoom
Light Source (watt):	200
Light Source Life, Normal (hours):	5000
Light Source Life, Dynamic Eco-Mode (hours):	15000
Color Depth:	1.07B Color (R/G/B 10bit)
Dynamic Contrast Ratio:	22,000:1
Aspect Ratio:	16:10

Video Signal:

Frequency Horizontal:	15K~102KHz
Frequency Vertical:	23~120Hz

Compatibility:

PC Resolution (max):	1920 x 1080
PC Resolution (min):	640 x 480
Mac® Resolution (max):	1920 x 1080
Mac® Resolution (min):	640 x 480

Connector:

USB 2.0 Type A(1), Ethernet LAN (RJ45)(1), 3.5mm Audio Out(1), 3.5mm Audio In(1), Control (RS232)(1), HDMI 1.4(2), VGA In(2), VGA Out(1), Composite RCA Video In(1), Mini USB(1)

Audio:

Internal Speakers:	10W
--------------------	-----

Power:

Voltage:	100-240V+/- 10%, 50/60Hz AC
Consumption (typical):	260W
Stand-by:	<0.5W

Controls:

Physical Controls:	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, mode/enter, auto, source
On Screen Display:	Display, Image, Power Management, Basic, Advanced, System, Information (See user guide for full OSD functionality)

Operating Conditions:

Temperature:	32-104° F (0 - 40° C)
Humidity (non-condensing):	0-90%

Additional Hardware:

Kensington Lock Slot: Copyright © ViewSonic Corporation 2000-2018. All rights reserved. (06/14/2018 07:17 AM PST)

Weight (imperial):

Net (lbs):	5.7
Gross (lbs):	7.2

Weight (metric):

Net (kg):	2.6
Gross (kg):	3.3

Dimensions (imperial) (WxHxD):

Packaging (in.): 14.4 x 7.4 x 11.8

Physical (in.): 11.5 x 4.5 x 9.3

Dimensions (metric) (WxHxD):

Packaging (mm): 365.0 188.0 x 300.0

Physical (mm): 292.0 x 115.0 x 236.0

General:

Regulations: FCC, cTUVus, ROHS

PACKAGE CONTENTS: PS600W projector, power cable, VGA cable, remote control, Quick Start Guide

Warranty: Three-year limited warranty on parts and labor, 1-year limited warranty on lamp, 1st year free Express Exchange® service. (One year

Recycle/Disposal: Please dispose of in accordance with local, state or federal laws.

UPC: 766907958416

Accessories:

HB10B, PGD-350, PJ-IWBADP-006, PJ-SCW-1001W, PJ-VTOUCH-10S, PJ-WMK-007, PJ-WMK-305, RLC-109, VC10, VCB10