





Key Features

- Digital Home Entertainment LCD Projector
- Three WVGA LCD Panels, Single Lens Projection System .62" p-si TFT Panels
- Resolution: 858 x 484 Dots x 3 (1,245,816 pixels (415,272 pixels x 3)
- Lens: Manual Zoom Focus F. No. 1.85-2.2/ f. 33.6-42mm
- Zoom 1.2 Times
- Side Shot[™] 2 Digital Keystoning
- CineMotion[™] Reverse 3-2 Pulldown Technology
- ANSI Lumens: 1000
- Contrast Ratio: 600:1

Additional Features

General Features

- Ultra-Quiet Fan (30db)
- Built-In Speaker (2W x 1 Mono)
- Lamp: 150W UHP Type
- Optical Engine Power: 1000ANSI Lumen (Cinema Black Off)
- Contrast Ratio 600:1
- Screen Size: 40-150"
- Input Video Signals: 480i/480p/1080i/720p
- Scanning Frequency: fh 19-72khz/fv48-92hz up to XGA VESA85
- Color System : NTSC, PAL, SECAM, PAL-M, PAL-N
- Composite Video Input
- S Video Input: Mini Din 4 Pin

 PJ Multi Input: RGB/Component/Progressive Component, DTV (480i/480p/720p/1080i) HDTV (RGB, Y/Pb/Pr) S Video/Composite Audio Input: Stereo Phono Pluq

Preliminary and Confidential











Key Technology



Side Shot™ 2 Digital Keystoning

Digital horizontal and vertical keystone adjustment capabilities with the press of a button to align the picture effortlessly. This technology allows you to place the projector off axis to the screen in order to save space in the center of the room.

Picture Modes

Choose from 3 preset picture modes that best suit the source and viewing environment (Standard/Dynamic/Cinema)

Cinema Filter

This filter enhances skin color fidelity and black level reproduction by structure of 25% reduction of green color element. We offer it to users as one of the picture adjustments according to their preference and sources.

Wide Modes

Allow the user to toggle through seven wide modes using the remote control. For 4:3 sources the choices are NORMAL THROUGH, NOR-MAL, FULL, ZOOM, SUBTITLE, and WIDE ZOOM. For 16:9 sources the choices are FULL THROUGH, NORMAL, and FULL

Specifications

Inputs and Outputs

- Composite Video Input
- S Video Input: Mini Din 4 Pin
- PJ Multi Input: RGB; Component; Progressive Component; DTV (480i/480p/720p/1080i) HDTV (RGBY/Pb/Pr)
 S Video; Composite Audio Input: Stereo Phono Plug

Accessories

Supplied Accessories

- Instruction Manual
- Remote Control (RM-PJHS2)
- Signal Interface Cable (SIC-HS50)
- Air Filter
- Lens Cap
- AA Batteries x 2
- Cinema Filter

Optional Accessories

- Easy Setup Signal Interface (IFU-HS1
- Projector Stand (SV-HS1)
- V/L/R Signal Interface Cable (SIC-HS10)
- Y/Pb/Pr/S/L/R Signal Interface (SIC-HS20)
- HD15/LR (SIC-HS30)
- Y/Pb/Pr/S/V (SIC-HS40)
- Short Focus Conversion
- Lens (VPLL-CW20) • Replacement Lamp
- (LMP-H150) • Replacement Air Filter
- (PK-HS1FL)

- Weights & Measures
- Approx. Dimensions (w/h/d): 17" x 2.4" x 10"
- Approx. Weight: 5.06 lbs.
- Approx. Box Dimensions (w/h/d):
 - 19.7" x 6.22" x 15.1"
- Approx. Box Weight: 8.8 lbs.

©2003 Sony Electronics Inc. All rights reserved. Reproduction in whole or in part without written permission is prohibited. Sony and Sideshot are registered trademarks of Sony Corporation. Any other trademarks referenced herein are either the property of Sony or their respective owners.