



## **Specifications Digital Projector PE8720**

| Display Technology                   | DLP (Digital Light Processing)   |   |
|--------------------------------------|--|---|
| Panel                                | Darkchip 720P DMD chip   |   |
| Native Resolution                    | WXGA (1280 × 720)  |   |
| Brightness                           | 1000 ANSI lumens<br>(Market claim at High Brightness Mode)   |   |
| Uniformity                           | 85%  |   |
| Contrast Ratio                       | 6200:1 (Full on/Full off)(At High Contrast Mode)   |   |
| Aspect Ratio                         | Native 16:9  |   |
| Color                                | Full 16.7 million color palette  |   |
| Lens                                 | F=2.4 to 2.8, f=32.1(wide) ~ 43 mm(tele)   |   |
| Image Size (Diagonal)                | 23.5"~300"   |   |
| Throw Ratio                          | 100"@4 m   |   |
| Zoom Ratio                           | 1.35×  |   |
| Lamp                                 | 250W   |   |
| Lamp Life                            | 2000 hours (3000 hours under ECO mode)   |   |
| Compatibility                        | XGA, SVGA, VGA, Macintosh*,<br>HDTV (1080i, 720p, 576p, 576i, 480p, 480i)  |   |
| H-Synch Range                        | 15 ~ 75 kHz  |   |
| V-Synch Range                        | 50 ~ 100Hz   |   |
| Video Compatibility                  | NTSC, PAL, SECAM, EDTV,<br>HDTV (1080i, 720p, 576p, 576i, 480p, 480i)  |   |
| Input Sources                        | A/V - S-Video: Mini DIN 4 pin ×1<br>A/V - Composite-Video RCA jack ×1<br>A/V - RCA jack ×3<br>A/V -BNC (x 5) ×1<br>HDMI (with HDCP) ×1 |   |
| Output Sources                       | 12V Trigger ×1   |   |
| Control Sources                      | RS232 (Serial) ×1  |   |
| Dimensions                           | $492 \times 195 \times 393 \text{ mm (W} \times \text{H} \times \text{D)}$   |   |
| Weight                               | 9 kg   |   |
| Power Supply                         | 100 to 240 V ac, 50 to 60 Hz (auto switching)  |   |
| Power Consumption                    | 320W (Max.)  |   |
| Audible Noise                        | Normal mode<26 dB, Economic mode < 23db  |   |
| OSD<br>(On-Screen Display) languages | English/French/German/Italian/Spanish/<br>Japanese/Russian/Dutch/Simplified Chinese/<br>Traditional Chinese                            |   |
| Features                             | Professional AV input<br>(HDMI)<br>Dust Proof with Air-Filter<br>PIP, POP<br>HDTV Compatible   | Vertical lens shift<br>Faroudja DCDi<br>processing<br>(3:2 pull down) |
| Accessories (Standard)               | User Manual<br>Remote Control<br>Batteries<br>Warranty information<br>book   | Air Filter Power Cord Video Cable S-Video Cable Component Cable       |
| Accessories (Optional)               | Ceiling Mounting Kit<br>Spare Lamp Kit<br>HDMI Cable<br>BNC to D-sub Cable   |   |

## BenQ Europe B. V.

BenQ-eu.com

Ekkersrijt 4130, 5692 DC Son, The Netherlands Tel: +31-(0)499-750-500 Fax: +31-(0)499-750-599

\* The  $DLP^{\scriptscriptstyle{\text{TM}}}$  logo and  $DLP^{\scriptscriptstyle{\text{TM}}}$  medallion are trademarks of Texas Instruments.

© BenQ Corporation. All rights reserved. Corporate names and trademarks are the property of their respective companies. Specifications subject to change without notice.