

Notevision C60



XG-C60X

Ideal for basic installation, the XG-C60X Conference / Classroom LCD projector has it all. 3500 ANSI Lumens of brightness, compact slim design, ultra-quiet fan and simple easy operation.

Presentations are a pleasure with this native XGA, 11.3 pound projector. Two separate RGB inputs, including loop out as well as separate S-video and composite video inputs provide flexibility and connectivity. Powerful presentation tools such as variable audio output, picture-in-picture and Color Management will keep your audience engaged.

The high brightness, full features you expect from a portable, but in a compact projector - the XG-C60X. For unforgettable presentations.

EXCLUSIVE FEATURES

- ▶ High Brightness using the high efficiency "L" type Optical System. 3500 ANSI Lumens with 85% Uniformity (CCR)
- ▶ Color Management System individually adjusts lightness, chroma and hue for red, green, blue, cyan, yellow and magenta.
- ▶ Variable Audio Output
- ▶ Quick release lens mechanism for 3 optional lenses
- ▶ Security and theft deterrent systems:
 - ⇒ Key code (password) startup
 - ⇒ One touch custom startup image
 - ⇒ Notevision Lockdown-through optical block ceiling mount stud
 - ⇒ Optional Ceiling Mount Cable Lock System
- ▶ Rear change lamp and side change air filter
- ▶ S.A.P.S. for Remote Projector Control and Self Diagnostics

ADVANCED FEATURES

- ▶ CV-IC System II Processing, Sharp GUI Menu, s-RGB Color Management
- ▶ Two Separate Data Inputs for PC or Mac plus Monitor Out
- ▶ Two Separate Video Inputs (Composite and S-Video)
- ▶ "autoSYNC" for Automatic Image Perfection
- ▶ Intelligent ImageACE Resizing
- ▶ High Speed "autoSYNC" for Automatic Image Perfection
- ▶ Digital Keystone Correction
- ▶ PresenterPak, The Sharp Exclusive Feature-set - Making it Simple to "Connect, Perfect, Project"

PROJECTION DISTANCES

Screen Diagonal	Screen Width	Screen Height	Minimum Distance	Maximum Distance
40"	32"	24"	4'8"	6.1'
60"	48"	36"	7'1"	9'2"
72"	58"	43"	8'6"	11'
84"	67"	50"	10'	12'11"
100"	80"	60"	11'11"	15'4"
150"	120"	90"	17'11"	23'1"
200"	160"	120"	24'	30'10"
250"	200"	150"	30"	38'7"
300"	240"	180"	36'	46'4"

Approx. Min / Max Projection Distance from Screen to Front of Lens

*Design and specifications are subject to change. All trademarks are property of their respective holders.

SPECIFICATIONS

Native Resolution	XGA (1024 x 768)
Resizing	Advanced ImageACE Resizing - up to UXGA
TV Lines	750 TV Lines (DTV 720p input, dot by dot)
Panel Type	3 - 0.99" Polysilicon TFT LCD (with MLA)
H & V Frequency	fH 15-126 kHz / fV 43 - 200 Hz
Dot Clock	230 MHz
PC Compatibility	UXGA (1600 x 1200) w/ ImageACE Resizing
Mac Compatibility	21" up to 1280x1024 w/ ImageACE Resizing
WS Compatibility	1280 x1024 (various modes w/ ImageACE Resizing)
Video System	NTSC/DTV/PAL/SECAM - Interlaced or Progressive Scan DTV/HD Compatible 480i/480p/540p/580i/580p/720p/1035i/1080i
Brightness	3500 ANSI Lumens w/ 85% CCR 2800 ANSI Lumens in Low Power Mode
Contrast Ratio	350:1
Lens Type	Recessed 1.27:1 Manual Zoom Focus
PC Control	RS-232C - 9 pin DIN
Remote Control	IR Remote w/wired capability (3.5mm connector)
IR Carrier Frequency	38 kHz
Audio System	3 Watt Monaural
Lamp Lamp Life*	SHP 300 Watt 2000 Hours Standard Mode 3000 Hours Low Power Mode
Lamp Module No.	BQC-XGC55X/1
Fan Noise	37dB / 35 dB Low Power Mode
Power Source	100-240V AC, 50/60Hz
Power Consumption	400 Watt / 325 Watt Low Power Mode
Heat Dissipation	1505 BTU hr / 1225 BTU hr Low Power Mode
Dimensions(w x d x h)	15.4" x 3.9" x 11.6"
Weight	11.3 lbs.
Limited Warranty	3 Yrs. Parts/Labor & 3 Yrs. Sharp Express Repair, *Lamp 90 Days

INPUTS/OUTPUTS

- Input 1** (1) Computer - RGB / Component (Audio shared 1 & 2)
Input 2 (1) Computer - RGB / Component (Audio shared 1 & 2)
Input 3 Composite Video (RCA), (Audio L/R shared 3 & 4)
Input 4 S-Video (4 pin DIN), (Audio L/R shared 3 & 4)
Outputs Computer - RGB / Component with Audio (fixed or variable)
 (1) - RS-232C Serial Port (9pin DIN)
 (1) - Wired Remote (3.5mm MiniJack)

INCLUDED ACCESSORIES

Remote Receiver, 3' USB cable, Remote control, RGB Signal Cable, Grounded AC Cord, DIN D-Sub RS-232C Adapter, Lens Cap, Sharp Advanced Presentation Software (S.A.P.S. ver.1.60), Quick Reference Label, CD-ROM Manual, Two AA Batteries, Air Filter

OPTIONAL ACCESSORIES

AN-C300WCC	Hard Sided Carry Case w/wheels (projector only)
AN-C300SC	"ATA" Shipping Case w/wheels (projector only)
AN-C300BAG	Soft Sided Carry-on Bag (projector only)
AN-C12MZ	Short Throw Lens (1.18 - 1.48 throw ratio)
AN-C27MZ	Telephoto Zoom (1.27 - 43. throw ratio)
AN-C41MZ	Telephoto Zoom (4.1 - 5.8 throw ratio)
AN-XGCM55	Ceiling Mounting Bracket
AN-EP101B	Extension Tube for Ceiling Mount (24.75" - 36.5")
AN-CMCS16	16" Security Cable System
AN-CMCS46	46" Security Cable System for use with AN-EP101B
AN-JT200	Angle Mount Joint for Ceiling Mount
AN-C3CP	Component (3 RCA) to 15 pin HD Cable 10'
AN-GYRO1	RF Wireless Mouse System
AN-LS1	Ethernet to RS-232C Network Converter
AN-A1RS	RS-232C Adapter

SHARP ELECTRONICS CORPORATION
 LCD Products Group, Sharp Plaza, Mahwah, NJ 07430-2135
 E-mail: ProLCD@SharpSEC.com
 1-866-4-VISUAL (866-484-7825)
www.SharpLCD.com/Notevision