


ViewSonic® PJ255D Projector

MICRO-PORTABLE FOR THE TRAVELING PROFESSIONAL



Remarkable performance in a surprisingly small package.

The ViewSonic PJ255D micro-portable DLP™ projector helps you **UNVEIL POWERFUL PRESENTATIONS ANYWHERE** your work takes you. While it weighs a mere 0.95kg, this powerful projector supports HD signals, and delivers a high contrast ratio and 1024x768 native resolution for crystal-clear images. Delivering remarkable multimedia presentations with the flexibility of PC and video inputs, image reversing and a wireless remote control. A zoom lens and vertical keystone correction guarantee a **PERFECT IMAGE IN VIRTUALLY ANY SETTING**. Unlock the power of your presentations with the microportable powerhouse PJ255D.



Micro-Portable Series

...✦ Light as a feather at 0.95kg

Fits easily in a briefcase when you are on the road.

...✦ Bright in any setting with 1,100 lumens

...✦ True 1024x768 XGA resolution

Produces clear, crisp images including detailed spreadsheets.



Easy-to-use remote included.

...✦ Vivid video images and photos

Beautiful life-like pictures with an incredible contrast and clarity.

...✦ Easy set-up and auto tuning

One-touch setup button for fast, easy sync and sharp focus.

...✦ Supports HD signals including 480i, 480p, 720p, 1080i

Capable of displaying HD signals as well as other video and data sources.²

...✦ The perfect image in any setting

Digital keystone correction and zoom function ensure the perfect size image in virtually any room.

...✦ Resolution of 1280x1024

Palm size



ViewSonic®
See the difference.™

ViewSonic® PJ255D Projector

MICRO-PORTABLE FOR THE TRAVELING PROFESSIONAL

Specifications



- 1. Menu
- 2. Keystone
- 3. Security Lock Port
- 4. Zoom and focus ring
- 5. Carl Zeiss optics
- 6. Leg adjust button

MICRO-PORTABLE PROJECTOR

DLP	Type	0.7" XGA DLP™
	Pixel Format	1024 horizontal x 768 vertical (XGA)
	Lens	Manual focus, manual zoom
DISPLAY	Size	0.7 - 6.79m (measured diagonally)
	Throw Distance	1.2 - 10.0m
	Lamp	120W, 2000 hour rating
	Brightness	1,100 Lumens
	Contrast Ratio	2000:1
INPUT SIGNAL	Video	RGB analogue, NTSC M, NTSC 4.43, PAL (B, D, G, H, I, M, N), SECAM (B, D, G, K, K1, L), 480i/p, HDTV 720p, 1080i
	Sync Frequency	Separated F _H :15-100kHz; F _V :43-120Hz
COMPATIBILITY	PC	Analogue: VGA to SXGA (scaled)
	Mac® 3	Analogue: to SXGA (may require Mac adapter)
CONNECTOR	RGB	DB-15
	Composite Video	RCA
	S-Video	Mini DIN 4-Pin
POWER	Component Video	VGA to component adapter ²
	Voltage	100-240 VAC, 50-60Hz (universal)
CONTROLS	Consumption	170 watts (typ)
	OnView®	Brightness, contrast, aspect ratio, menu location language, sharpness, colour temp, tint, V/H position, PIP, zoom, keystone correction front, rear, front ceiling, rear Ceiling
OPERATING CONDITIONS	Projection Remote	Power, source, PIP, keystone, zoom, hide, freeze, menu
	Temperature	41°-95° F (5°-35° C)
	Humidity	10%-85% (non-condensing)
DIMENSIONS (W x H x D in mm)	Noise Level	36 dB (typ)
	Physical	198mm x 57mm x 148mm (excluding lens and leg)
WEIGHT	Net	0.95kg
REGULATIONS		CE, TÜV/GS, UL, C-UL, FCC-Class B, CB, NOM, PSB/S-mark, C-Tick, CCC, VCCI, GOST
OTHER		Front and rear projection, zoom feature, PIP, wireless remote control, soft carrying case.
WARRANTY		Please see: http://www.viewsoniceurope.com/UK/Support/warranty.htm

Projection Distance	Min. Diagonal Image Size	Max. Diagonal Image Size	Min. Horiz. Image Size	Max. Horiz. Image Size
1.20	0.70	0.82	0.56	0.65
2.00	1.17	1.36	0.93	1.09
3.00	1.75	2.04	1.40	1.63
4.00	2.34	2.72	1.87	2.17
5.00	2.92	3.40	2.34	2.72
6.00	3.50	4.08	2.80	3.26
7.00	4.09	4.76	3.27	3.80
8.00	4.67	5.43	3.74	4.35
9.00	5.26	6.11	4.21	4.89
10.00	5.84	6.79	4.67	5.43

Accuracy of the calculations are +/- 5%.



ViewSonic Corporation's QMS/EMS has been registered to ISO 9001 & ISO 14001 by the British Standards Institution.



ViewSonic®
See the difference.™

ViewSonic Europe Limited/UK
ViewSonic House
Fleming Way, Crawley
West Sussex, RH10 9GA
United Kingdom

Tel: +44 (0) 12 93 64 39 00
Fax: +44 (0) 12 93 64 39 10

ViewSonic Germany
Hanns-Martin-Schleyer-Straße 18A
47877 Willich
Germany

Tel: +49 (0) 21 54 91 88 0
Fax: +49 (0) 21 54 91 88 10

ViewSonic France
Parc des Barbanniers
1 allée des Bas Tilliers
92230 Gennevilliers
France

Tel: +33 (0) 1 41 47 49 00
Fax: +33 (0) 1 41 47 49 10

ViewSonic Corporation
381 Brea Canyon Road
Walnut
California 91789-0708
USA

Tel: +1 909 869 7976
Fax: +1 909 869 7958

ViewSonic Benelux
ViewSonic Denmark
ViewSonic Finland
ViewSonic Italy
ViewSonic MEA
ViewSonic Norway
ViewSonic Spain
ViewSonic Sweden

Tel: +32 056/85 26 27
Tel: +45 70 22 11 71
Tel: +358 (9) 54 06 40 70
Tel: +39 0289 079 340
Tel: +971 (0) 4 88 11 871
Tel: +47 (0) 22 88 17 60
Tel: +34 (0) 91 63 05 339
Tel: +46 (0) 8 50 71 30 00

¹ The warranty for all ViewSonic LCD and DLP projectors (except PJ250) from 1 April 2004 is valid for three years, and includes an on-site exchange service during this period in the most European Union (France, Belgium, Netherlands, Luxembourg, United Kingdom, Ireland, Sweden, Denmark, Finland, Germany, Austria, Greece, Italy, Spain, Portugal) and EFTA countries (Switzerland, Liechtenstein, Norway, Iceland). ² Optional cables required. ³ May require Mac adapter
Copyright © 2004, ViewSonic Corporation. All rights reserved. Specifications subject to change without notice. Corporate names and trademarks stated herein are the property of their respective companies. VS PJ255D-04/04-UK.