

ViewSonic® PJ400 Projector

LIGHT, BRIGHT AND PORTABLE



Portable, multifunctional projector.

The ViewSonic PJ400 weighs only 4.8 pounds but packs big power into its compact package. With native SVGA 800x600 resolution and 1,600 lumens, the PJ400 is **BRIGHT AND POWERFUL ENOUGH FOR VIRTUALLY ANY SITUATION.**

Advanced video features such as progressive scan and 3:2 pull down deliver smooth, crisp video performance. Project sharp, precise images from your data applications as well.

DELIVER DYNAMIC MULTIMEDIA PRESENTATIONS with multiple inputs and HDTV signal support. This full-featured, projector is an excellent choice for professional presentations or home entertainment use.

ViewSonic® has the **best warranty** and **service support** in the business!



3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

And we offer free 24/7 technical support[†] for the life of your Product, just in case.

Deliver bright, powerful presentations.

◆ Bright in virtually any setting with 1,600 lumens

Packs 1,600 lumens in just 4.8 lbs. It's the bright choice for mobile presenters.

◆ Ultimate video source flexibility

Connect a computer or add a video source for dynamic meetings and presentations.



Easy-to-use remote included.

◆ Supports HD signals including 720p and 1080i

Capable of displaying HDTV signals as well as other video and data sources*.

◆ Advanced video features

Progressive scan and 3:2 pull down for superior video performance.

◆ Whisper-mode extends lamp life

Extend the life of your lamp up to 4,000 hours** and reduce noise output.

◆ OnView® controls plus ViewMatch® color for superior screen adjustability

Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.



◆ The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year lamp warranty. ***

Superb Value

ViewSonic® 
the choice of professionals

ViewSonic® PJ400 Projector

LIGHT, BRIGHT AND PORTABLE



1. Stand by/on
2. Menu
3. Kensington security port
4. RGB input and component through RGB
5. Composite and S-video input
6. Focus ring

PJ400 Distance Calculator			
Image Size (Diagonal in.)	Height (in.)	Width (in.)	Throw Distance (in.)
40	24	32	57
60	36	48	87
100	60	80	145
150	90	120	218
200	120	160	291

Throw ratio: 1.49–1.79:1 (distance:width)

Accuracy of the calculations are +/- 5%.

For additional calculations visit Viewsonic.com.

Optional Accessories

- Replacement lamp RLC-004
- Hard case with wheels PRJ-HCA-001
- Extended Express Exchange® PRJ-EE-05-03
- Soft case with wheels and laptop bag PRJ-SCA-004
- Universal ceiling mount kit WMK-005
- VGA to component video cable ADPT-002

PORTABLE PROJECTOR

	Type	0.55" Poly-Si TFT with micro-lens
	Pixel Format	800x600 SVGA
	Lens	Manual zoom/focus
	Zoom Factor	1.2 (digital)
	Keystone	Vertical ± 15°
DISPLAY	Size	40"–200" (diagonally)
	Throw Distance	57"–292"
	Throw Ratio	1.8
	Lamp	165W, 2,000 hours**
	Brightness	1,600 lumens
	Contrast Ratio	300:1
	Aspect Ratio	4:3 (native), 16:9
AUDIO	Speakers	1x1 watts
INPUT SIGNAL	Video	RGB analog, NTSCM, NTSC 4.43, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)
	Frequency	F _H : 15–91kHz; F _V : 56–120Hz
COMPATIBILITY	PC	Analogue: from VGA up to UXGA (scaled)
	Mac®**	Analogue: up to SXGA (may require a Mac adapter)
CONNECTOR	RGB (input)	15-pin HD, D-sub cable (x1)
	Composite Video (input)	RCA jack (x1)
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input)	VGA DB-15 to HDTV/component cable*
	Audio (input)	Stereo mini-jack (x1)
	Control	9-Pin D-sub for RS232 control
POWER	Voltage	100–240 VAC, 50–60Hz (universal)
	Consumption	240 watts (typ)
CONTROLS	Physical	Standby, input, reset, H/V keystone
	OnView®	Language, brightness, contrast, gamma, color temperature, color, tint, sharpness, progressive, My Memory, aspect, overscan, V. position, H. position, H. Phase, H. size, auto adjust, color space, component, video format, information, V. keystone, whisper, mirror, volume, language, menu position, OSD bright, blank color, start up, My Screen, My Screen Lock, message, auto search, lamp time, filter time, service menu
OPERATING CONDITIONS	Temperature	32–95°F (0–35° C)
	Humidity	10–85% (non-condensing)
NOISE LEVEL	Normal	38 dB (typ)
	Whisper mode	33 dB (typ)
DIMENSIONS (WxDxH)	Physical	11.2" x 2.9" x 8.0" 285mm x 73mm x 202mm
WEIGHT	Net	4.8 lb. (2.2 kg)
	Gross	13.9 lb. (6.3 kg)
REGULATIONS		UL 60950, C-UL, FCC-B, UL-DEMKO/GS, CCC, CB, CE, C-TICK, GOST, NOM, PSB, TUV-S
OTHER		Vertical digital keystone correction, progressive scan, 3:2 pull down, auto adjust, remote control
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year warranty on lamp.***

specifications

ViewSonic®

the choice of professionals

ProSelecta

View :: Compare :: Select - www.ProSelecta.com