ViewSonic® PJ502 Projector

PORTABLE AND AFFORDABLE

A full-featured, versatile and affordable projector.

The ViewSonic PJ502 is light, bright, affordable and versatile. The PJ502 packs an amazing **1,600 LUMENS IN JUST 5.4 POUNDS.** True 800x600 SVGA native resolution, scalable to 1600x1200, produces crystal-clear images. **WHISPER MODE EXTENDS LAMP LIFE AND REDUCES NOISE OUTPUT** so your audience focuses only on your presentation. Dynamic presentations and home theater installations benefit from multiple video inputs, zoom lens, digital keystone correction and easy one-touch set up and auto tuning. The PJ502 is an excellent choice for home theater installations, classroom applications and corporate training or boardrooms.

ViewSonic has the **best warranty** and **service support** in the business!

3-Year *Parts and labor limited warranty*

1-Year *Free Express Exchange®*

1-Year *Limited Lamp warranty*

And we offer free 24/7 technical support† for the life of your product, just in case.

The portable performance projector.

⋯⊹Ideal for mobile professionals
Packs 1,600 lumens in just 5.4 lbs. It's the bright choice for the mobile professional.

⋯⊹Clear, crisp images
True 800x600 SGVA resolution produces clear, crisp images for data and video.

⋯⊹The perfect image in any setting
Digital keystone correction and zoom function ensure the perfect size image in any room.

Easy-to-use remote included.

⋯⊹Supports HD signals including 720p and 1080i
Capable of displaying HDTV signals as well as other video and data sources.*

⋯⊹Whisper-mode extends lamp life
Extend the life of your lamp up to 4,000 hours** and reduce noise output.

⋯⊹OnView® controls plus ViewMatch® color for superior screen adjustability
Screen geometry and color adjustments are precisely made via an easy-to-use on-screen menu.

⋯⊹The best warranty in the business
Covered by a three-year parts and labor limited warranty, first-year Express Exchange Service and one-year lamp limited warranty.††

Light Idea

ViewSonic®

ViewSonic® PJ502 Projector

PORTABLE AND AFFORDABLE

1. Input select
2. Power button
3. Menu
4. Component, composite, and S-video input
5. RS-232
6. RGB input
7. Zoom and focus rings

PJ502 Distance Calculator

Image Size (Diagonal in)	Height (in.)	Width (in.)	Throw Distance (in.)
40 - 27	24 - 16	32 - 22	50
60 - 40	36 - 24	48 - 16	74
100 - 68	60 - 41	80 - 54	123
150 - 101	90 - 61	120 - 81	185
200 - 136	120 - 82	160 - 108	248
300 - 199	180 - 123	240 - 160	370
400 - 264	240 - 158	320 - 211	492
500 - 336	300 - 202	400 - 267	615

Throw ratio: 1.49~1.79:1 (distance:width)

Accuracy of the calculations are +/- 5%.
For additional calculations visit Viewsonic.com.

Optional Accessories

- Replacement lamp — PRJ-RLC-015
- Extended Express Exchange® — PRJ-EE-05
- Ceiling/wall mount — PRJ-WMK-013
- Rolling hard case — PRJ-HCA-001
- Rolling soft case — PRJ-SCA-004

PORTABLE PROJECTOR

	Type	0.7" P–Si TFT
	Pixel Format	800x600 SVGA
	Lens	Zoom lens/manual focus
	Zoom factor	1.2
DISPLAY	Size	30"–300" (measured diagonally)
	Throw Distance	35"–433"
	Throw Ratio	1:49– 1.79:1
	Lamp	165W, 4,000 hour rating**
	Brightness	1,600 lumens
	Contrast Ratio	400:1
	Aspect Ratio	4:3 (native), 16:9
	Digital Keystone Correction	±15° vertical
AUDIO	Speakers	1x1-watt
INPUT SIGNAL	Computer	RGB analog
	Video	NTSC, NTSC 4:3, PAL, SECAM, 480i/p, HD signals 720p, 1080i
	Frequency	F_h: 15–91kHz; F_V:50–120Hz
COMPATIBILITY	PC	Analog: VGA to UXGA (scaled)
	Mac®††	Analog: up to SXGA
CONNECTOR	RGB	15–pin HD, D–sub cable
	Video Input	S-video, composite, component
	Audio Input	RCA (x1)
	Control	RS-232
POWER	Voltage	100–240 VAC, 50–60Hz (universal)
	Consumption	220 watts (typ)
USER CONTROLS	Physical	Standby on/off, menu, input
	Remote	Standby on/off, page up, page down, enter, volume, mute, blank, auto adjust, search, RGB, video, aspect, magnify on/off, freeze, position, keystone, reset, escape
	OnView®	Language [English, French, German, Spanish, Italian, Norwegian, Dutch, Japanese, Portuguese, Chinese, Korean, Swedish, Russian, Polish], Display [keystone, brightness, contrast, aspect, whisper, mirror, language, gamma, color], Balance (RGB) [sharpness, color, tint, my memory, H/V position, H phase, H size, overscan, color space, component, video, frame lock, 3D-YCS, video NR, progressive, information, S2-aspect, adjust, power-off, search, blank, start up, menu position, message, screen type, reset], Audio [volume, mute], Lamp [timer, timer reset], Filter [timer, timer reset]
OPERATING CONDITIONS	Temperature	32–95º F (0–30º C)
	Humidity	10–85% (non-condensing)
NOISE LEVEL	Normal	33dB (typ)
	Whisper mode	29dB (typ)
DIMENSIONS (WxDxH)	Physical	11.7" x 9.2" x 2.5" 297mm x 234mm x 64mm
WEIGHT	Net	5.4 lb. (2.4 kg)
	Gross	14.3 lb. (6.5 kg)
REGULATIONS		UL, C-UL, FCC-Class B, CB, CE, TUV/GS, C-Tick, NOM
OTHER		Front and rear projection, overscan, frame lock, 3D-YCS, video NR, progressive scan, soft carrying case, remote control
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange® Service. One-year limited warranty on lamp.††

specifications

ViewSonic®