

ViewSonic® PJ520 Projector

LIGHT, BRIGHT AND PORTABLE



Versatile, portable, multimedia projector.

The ViewSonic PJ520 is the perfect union of form and function with 800x600 native resolution. It **WEIGHS IN AT LESS THAN 6 POUNDS** while its **2,000 LUMENS DELIVER ULTRA-BRIGHT, CRISP, CLEAR IMAGES**. Unveil dynamic multimedia presentations in any setting. The multiple video inputs allow connectivity from different sources while one image can be output on an additional display. Rich in features and light on the wallet, the PJ520 is an excellent choice for business or home use.

ViewSonic® has the **best warranty** and **service support** in the business!



3-Year Parts and labor limited warranty

1-Year Free Express Exchange®

1-Year Limited lamp warranty

And we offer free 24/7 technical support† for the life of your Product, just in case.

Sharper presentations, brighter images.

❖ Ideal for mobile professionals

Packs 2,000 lumens in just 5.9 pounds It's the bright choice for the mobile professional.

❖ Bright in virtually any setting with 2,000 lumens

❖ Ultimate flexibility with multiple RGB inputs

Connect two computers simultaneously or add a video source for dynamic meetings.



Easy-to-use remote included.

❖ Supports HD signals including 480i, 480p, 720p, 1080i

Capable of displaying HD signals as well as other video and data sources.*

❖ Whisper-mode extends lamp life

Extend the life of your lamp up to 4,000 hours** and reduce noise output.

❖ The perfect image in any setting

Horizontal and vertical digital keystone correction, short focal length, and zoom function ensure the perfect size image in virtually any room.

❖ Free industry-leading 24/7 customer support†

Technical support wherever, whenever, just in case.

❖ The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange® and one-year limited lamp warranty.***

Light Idea



ViewSonic®
See the difference.®

ViewSonic® PJ520 Projector

LIGHT, BRIGHT AND PORTABLE

specifications



- 1. Stand by/on
- 2. Menu
- 3. Kensington security port
- 4. Dual RGB inputs and RGB output
- 5. Component, composite, and S-video input
- 6. Zoom and focus rings

PJ520 Distance Calculator			
Image Size (Diagonal Inches)	Height (Inches)	Width (Inches)	Throw Distance (Inches)
40	24	32	47 - 57
60	36	48	71 - 85
100	60	80	119 - 143
150	90	120	180 - 216
200	120	160	240 - 288
250	150	200	300 - 361
300	180	240	360 - 433

Accuracy of the calculations are +/- 5%.
For additional calculations visit ViewSonic.com.

Optional Accessories

- Replacement lamp RLU-150-001
- Rolling hard case PRJ-HCA-001
- Rolling soft case PRJ-SCA-001
- Ceiling/Wall Mount PRJ-WMK-005
(not compatible w/ PM-FCP and PRJ-ECM-001)
- Extended Express Exchange® EE-LB-02

ULTRA-PORTABLE PROJECTOR

	Type	0.7" Poly-Si TFT with micro-lens
	Pixel Format	800x600 (native resolution)
	Lens	Manual zoom/focus
	Zoom Factor	1.2
DISPLAY	Size	30"-300"
	Throw Distance	35"-433"
	Lamp	150W, 4,000 hours**
	Brightness	2,000 lumens
	Contrast Ratio	350:1
	Aspect Ratio	4:3, 16:9
AUDIO	Speakers	1x1 watts
	INPUT SIGNAL	
	Video	RGB analog, NTSCM, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 720p, 1080i)
	Sync	Separated
	Frequency	F _H :15-91kHz; F _V :56-120Hz
COMPATIBILITY	PC	Analog: VGA to UXGA (scaled)
	Mac[®]††	Analog: up to SXGA (may require Mac adapter)
CONNECTOR	RGB Input	15-pin HD, D-sub cable (x2)
	Video Input	Composite, component, S-video
	RGB Output	15-pin HD, D-sub cable (x1)
	Audio Input	RCA (x1)
	USB (Remote control mouse)	USB upstream (x1)
	Control	RS232
POWER	Voltage	90-264 VAC, 50-60Hz (universal)
	Consumption	240 watts (typ)
CONTROLS	Basic	Standby, menu, input, reset, H/V keystone
	OnView[®]	Language, display (keystone, brightness, contrast, aspect, picture position, gamma, mirror, language, color bar (R,B) sharpness, color, tint, H/V position, H. phase, H. size, over scan, auto adjust, video, HDTV, sync on green, blank, start up, myscreen, myscreen size, myscreen lock, whisper, auto off, audio (volume, mute), projection (front, rear, front ceiling, rear ceiling, lamp (lamp timer, lamp timer reset, filter (filter timer, filter timer reset).
OPERATING CONDITIONS	Temperature	32-95° F (0-35% C)
	Humidity	10-85% (non-condensing)
NOISE LEVEL	Normal	39 dB (typ)
	Whisper mode	34 dB (typ)
DIMENSIONS (WxHxD)	Physical	295mm x 76mm x 231mm 11.6" x 3.0" x 9.1"
	WEIGHT	
	Net	5.9 lb. (2.7 kg)
	Gross	14.5 lb. (6.6 kg)
REGULATIONS		UL, UL60950 C-UL, FCC B, TUV/GS, CB, CE, C-TICK, TUV-S, NOM
OTHER		H/V digital keystone correction, soft carrying case, remote with mouse control, dual RGB input, RGB output, auto adjust
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange [®] Service. One-year warranty on lamp.**



ViewSonic[®]
See the difference.[®]