ViewSonic® PJ562 Projector

LIGHT, BRIGHT AND PORTABLE



The versatile, portable high-performance projector.

The ViewSonic PJ562 weighs in at just 5.6 pounds so it's small enough to take on the road with you, or between meeting rooms or classrooms. The 2,000 LUMENS WITH 1024X768 XGA NATIVE **RESOLUTION** make it bright and powerful enough for the most

demanding professional. Project crisp, clear images in virtually any setting with the optical zoom lens, short focal length and digital keystone

correction. MULTIPLE INPUTS allow you to connect two PCs or add a video source for DYNAMIC MULTIMEDIA PRESENTATIONS. This fullfeatured projector makes the most of your presentations and your budget.



labor limited warranty

1-Year Free Express Exchange®

1-Year Lamp warranty

And we offer free 24/7 technical support[†] for

Bright, powerful, mobile.

- ***Bright in virtually any setting with 2,000 lumens Packs 2,000 lumens in just 5.6 lbs. It's the bright choice for the mobile professional.
- ··· Ultimate video source flexibility

Connect two computers simultaneously or add a video source for dynamic meetings. Add another monitor output to view the same projected image on the display.



Easy-to-use remote included. Capable of displaying HDTV signals as well as other video and data sources*.

··· Advanced Video Features

Progressive scan and 3:2 pull down for superior video performance.

··· Whisper-mode extends lamp life

Extend the life of your lamp up to 4,000 hours** and reduce noise output.

superior screen adjustability

Screen geometry and color adjustments are precisely made via an easy-to-use, on-screen menu.



··· The best warranty in the business

Covered by a three-year parts and labor limited warranty, first-year Express Exchange $^{\! \rm B}$ and one-year lamp warranty. ****





Decilications

ViewSonic® PJ562 Projector

PORTABLE AND AFFORDABLE







- 1. Stand by/on
- 2. Menu
- 3. Kensington security port
- 4. Dual RGB inputs and RGB output
- 5. Component, composite, and S-video input
- **6.** Zoom and focus rings

PJ562 Distance Calculator					
Image Size (Diagonal in)	Height (in.)	Width (in.)	Throw Distance		
40 - 27	24 - 16	32 - 22	50		
60 - 40	36 - 24	48 - 16	74		
100 - 68	60 - 41	80 - 54	123		
150 - 101	90 - 61	120 - 81	185		
200 - 136	120 - 82	160 - 108	248		
300 - 199	180 - 123	240 - 160	370		
400 - 264	240 - 158	320 - 211	492		
500 - 336	300 - 202	400 - 267	615		

Throw ratio: 1.49~1.79:1 (distance:width)

Accuracy of the calculations are +/- 5%.

For additional calculations visit Viewsonic.com.

Optional Accessories

Replacement lamp	PRJ-RLC-015
 Hard case with wheels 	PRJ-HCA-001
• Extended Express Exchange®	PRJ-EE-05
 Soft case with wheels and laptop bag 	PRJ-SCA-004
 Ceiling mount kit 	PRJ-WMK-013
Universal ceiling mount kit	WMK-005

PU	KIA	RFF	PK	UJ	EC	IU	K

PUKIABLE PK	OJECIOK	
	Туре	0.7" P–Si TFT with micro-lens
	Pixel Format	1024x768 XGA
	Lens	Manual zoom/focus
	Zoom Factor	1.2
	Keystone	Vertical ± 15°
DISPLAY	Size	30"-300" (diagonally)
	Throw Distance	35"-433"
	Throw Ratio	1.5~1.8:1
	Lamp	165W, 4,000 hours**
	Brightness	2.000 lumens
	Contrast Ratio	400:1
	Aspect Ratio	4:3(native), 16:9
AUDIO		1x1 watts
AUDIO	Speakers	
INPUT SIGNAL	Video	RGB analog, NTSCM, NTSC 4.45, PAL, SECAM, HDTV (480i, 480p, 576i, 720p, 1080i)
	Frequency	F _h :15–91kHz; F _V :50–120Hz
COMPATIBILITY	PC	Analog: VGA to UXGA (scaled)
	Mac [®] ^{††}	Analog: to SXGA
CONNECTOR	RGB (input/output)	DB-15 (x2)/(x1)
COMMECION	Composite Video (input	* " * "
	S-Video (input)	Mini-Din 4-pin (x1)
	Component Video (input	
	Audio (input/output)	
	, . ,	USB x 1 for mouse control
	USB (output)) Control	9-Pin D-Sub for RS232 control
	Control	9-PIII D-SUD IOF RS232 CONTROL
POWER	Voltage	100–240 VAC, 50–60Hz (universal)
	Consumption	240 watts (typ)
CONTROLS	Physical	Standby on/off, menu, input, reset, H/V keystone
	OnView [®]	Language, Display (brightness, contrast, gamma, color temperature,
		color, tint, sharpness), progressive, My Memory, aspect, overscan, V.
		position, H. position, H. Phase, H. size, auto adjust, color space, com-
		ponent, video format, frame lock, S-aspect, information, keystone,
		whisper, mirror, volume, language, menu position, OSD bright, blank
		color, start up, My Screen, My Screen Lock, message, auto search,
		auto power off, auto power on, lamp time, filter time, service menu
OPERATING	Temperature	32–95°F (0–30° C)
CONDITIONS	Humidity	10–85% (non-condensing)
NOISE LEVEL	Normal	38 dB (typ)
	Whisper mode	32 dB (typ)
DIMENSIONS	Physical	11.7" x 9.2" x 2.6"
(WxDxH)		297mm x 233mm x 65mm
WEIGHT	Net	5.6 lb. (2.5 kg)
	Gross	13.9 lb. (6.3 kg)
REGULATIONS		UL, C-UL, FCC-CLASS B, CB, CE, TUV/GS, C-TICK, NOM, TUV-S
OTHER		Digital keystone correction, soft carrying case, remote with
OIIIEN		mouse control, dual RGB input, RGB output, auto adjust, 3:2 pull down, progressive scan, frame lock, overscan
WARRANTY		Three-year limited warranty on parts and labor, first-year Express Exchange* Service. One-year warranty on lamp.***



