

HITACHI

Inspire the Next

CP-X327W



- 1,800 ANSI Lumens
- Native XGA Resolution
- 6 lbs.
- 16:9 Mode
- Contrast Ratio 350:1
- 2 RGB Inputs/RGB Output
- Component/Composite/S-Video Input
- Reverse image function for ceiling mount
- Vertical & Horizontal Keystone Correction
- My Screen (user programmable start-up screen)
- HDTV Theater Ready
- Wireless remote controller with laser pointer
- 34dB (Whisper mode)
- Comes with carry case
- Color correction
- Kensington security slot
- Wide-angle lens
- FCC Class B
- Digital Zoom (x4)
- Picture freeze function
- Manual zoom & manual focus

SPECIFICATIONS

Model name	CP-X327W			
Liquid crystal panel structure	0.7" polysilicon active-matrix TFT x 3			
Number of pixels	786, 432 pixels (H 1,024 x V 768)			
Resolution	1,024 x 768 color pixels			
Colors	16.7 million colors			
Aspect ratio	Native 4:3/16:9 compatible			
Lens	Manual zoom 1:1.2 (F1.7 - 1.9), manual focus			
Throw ratio (distance:width)	1.47 ~ 1.79 : 1			
Lamp	150W UHB (130W in whisper mode)			
Brightness	1,800 ANSI lumens (1,440 ANSI lumens in whisper mode)			
Expected lamp life	2,000 hours			
Contrast ratio	350 : 1			
Speakers	1W x 1			
Power supply	AC100-120V/AC220-240V 50/60Hz			
Power consumption	240W			
Operating temperature	32°F ~ 95°F			
Input signals	RGB	VGA, SVGA, XGA, SXGA/UXGA (COMPRESSED), MAC13", MAC16"		
	Composite video	NTSC, NTSC4.43, PAL, SECAM, PAL-M, PAL-N, PAL60		
	Component video	480i, 575i, 480p, 1,080i, 720p		
Acoustic noise level	39dB (34dB in whisper mode)			
H sync	15kHz ~ 91kHz			
V sync	50Hz ~ 120Hz			
Vertical keystone correction	Digital keystone +/- 15°			
Horizontal keystone correction	Digital keystone +/- 5°			
Approvals	UL, C-UL, FCC Class B			
Input/Output terminals	RGB input	Analog RGB	15-pin D-sub connector x 2	
	RGB output	RGB	15-pin D-sub connector x 1	
	Video input	S-video		Mini DIN 4-pin connector x 1
		Composite video		RCA jack x 1
		Component video		RCA jack x 3
	Audio		RCA jack x 2 (L/R)	
Control terminals		15-pin D-sub connector x 1		
Chassis	Compatible controls		USB connector (USB mouse) x 1 PS/2, ADB serial, RS-232C (serial)	
	Dimensions		11.6" x 3.0" x 9.1" (W x H x D)	
	Weight		6 lbs.	
Replace-ment Parts	Supplied accessories		Wireless remote control with laser pointer, batteries (AA), RGB cables, RCA video/audio cable, power cord (US, UK, Euro), operator/safety manual, carrying case	
	Lamp		CPX327 LAMP (Part #: DT00521)	
	Wireless remote		Wireless remote (Part #: HL01891)	



Screen Size 4.3		Throw distance	
Diagonal*	Width*	Min*	Max*
40	32	47	55
60	48	71	87
80	64	95	114
100	80	118	142
120	96	142	173
150	120	181	217
200	160	240	287

Throw ratio: 1.47-1.79:1 (distance:width)

*: Measured in inches

CP-S317/CP-X327 Dimensions (incl.protruding part)

