

## PLC-SL20



Model	SANYO PLC-SL20
Panel	0.8" TFT p-Si x 3
Number of pixels	480.000 x 3 (800 x 600)
Resolution	S-VGA
Lamp	200 W UHP
Brightness	1700 ANSI-Lumens
Lamp life	3000
Uniformity	85%
Contrast ratio	350:1
Keystone correction	vertical +/-40°, horizontal +/- 20°
Lens	F=1.7-2.5, f=20-30 mm
Picture size	1.02 m – 7.62m (diagonal)
Throw ratio	1.2-1.9:1
Throw distance	1.0m – 7.7m
Input (Computer)	Computer in 1: DVI-I (digital/analog) Computer in 2: D-sub15 (RGB/ component/SCART-RGB) or monitor out Audio in: Mini jack
Input (Video)	Video in: 1xMini DIN 4-pin (S-Video) 1x RCA x 1 (Video) Audio in: RCA x 2 (R,L-mono)
Audio	Audio out:Mini jack (stereo with variable)
Control Port	1x Mini DIN8-pin (serial)
Mouse Control Port	1x USB (Type B)
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M&N
Computer compatibility	XGA(kompr.) /SVGA/VGA
Dimensions (W x H x D)	29,8cm x 7,1cm x 21,8 cm
Weight	2,8kg
Carton size	42cm x 34cm x 36,5cm
Package weight	5,2kg
Standard accessory	Wireless remote control with mouse control and laser pointer; owners manual; computer cable (DVI-D-Sub15); mouse control cable for USB port; Lens cap with strap and screw; air filter; AC cord
Optional accessory	Component (3RCA) –D-sub15 cable; Multi Card Imager unit (PC BOX20); CF-W-LAN Card for MCI (POA-WLC20); CF-LAN-Card MCI (POA-WDC20); 32M CF memory card for MCI (POA-CFC20 SCART-D-Sub15-cable; MAC-VGA-Adapter