



## VT45K

# Lightweight. High Performance.

Up to 3,500 hour lamp life

Manual lens shift technology

Automatic set-up

Broad computer compatibility

Monitor output

Remote control operates computer and projector

sRGB color setting

Exclusive VORTEX<sup>™</sup> Technology Plus<sup>™</sup> ensures the display of images with natural colors and exceptional clarity

Carrying case supplied

An idea is only as strong as its presentation.

Engaging any audience is always a challenge. From classrooms to conference rooms, sharing ideas in captivating ways is never easy, especially if you don't have the right tools. But with the NEC VT45 projector, you'll find the performance you need to make any presentation a success.

The VT45 combines unmatched features and functionality to project bright, bold and colorful images on large screens. Regardless of the level of ambient light, the VT45 is powerful enough to display images in medium-sized rooms without sacrificing color saturation, contrast or detail. In addition, the VT45 supports data sources from VGA to SXGA and contains the same video processing technology as NEC top-of-the-line models. So image quality is never an issue.

Aside from superior image performance, the VT45's features make it even easier for you to focus on giving a great presentation. AutoSense™ technology provides automatic set-up, so getting ready to present is as simple as plug in and play. And one-button source changes and image adjustments let the audience focus on your presentation, not your projector.

To ensure your audience stays captivated, NEC provides the InstaCare® service program for projector replacement and repair. Services include a help line, a two-year warranty and next business-day projector replacement free of charge.







## VT45K

11.8" (299mm)











#### Special Features

| Eco-Mode Technology    | Increase lamp life up to 60% through light output adjustments.                                                                                                                                                                                                                           |
|------------------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| VORTEX Technology Plus | Provides uncompromising display of video and data.<br>Improves white level, color accuracy, dynamic range,<br>and display of varying levels of black in an image.<br>Color correction system enables six-axis adjustment of<br>CMY and RGB for display of personal color<br>preferences. |
| Advanced AccuBlend     | Ensures detailed images when non-native resolution sources are connected to the projector.                                                                                                                                                                                               |
| AutoSense              | Automatic set-up and one touch adjustments for ease of use                                                                                                                                                                                                                               |
| Manual Lens Shift      | Image can be shifted 1 /2 the height or 1 /3 the width of the projected image                                                                                                                                                                                                            |
| Image Magnification    | 64 step image magnification with location control                                                                                                                                                                                                                                        |
| Full Remote            | Provides projector and mouse control                                                                                                                                                                                                                                                     |
| Monitor Output         | Connect external monitor                                                                                                                                                                                                                                                                 |
|                        |                                                                                                                                                                                                                                                                                          |

#### **Optical**

| LCD Panel:              | 0.7 p-Si TFT                                                                            |
|-------------------------|-----------------------------------------------------------------------------------------|
| Native Resolution:      | 800x600 pixels native, up to SXGA with Advanced AccuBlend                               |
| Light Output:           | 1000 ANSI lumens standard, 900/800 ANSI lumens in Eco-mode                              |
| Lamp:                   | 135W NSH-P, 120W/110W Eco-mode                                                          |
| Lamp Life:              | 3500/2700 in Eco-mode, 2200 hours standard                                              |
| Contrast Ratio:         | 300:1                                                                                   |
| Lens                    | Manual zoom/focus with lens shift,                                                      |
|                         | f2.0-2.2, f26.7-29.3mm                                                                  |
| Image Size:             | 25 to 300 inches diagonal                                                               |
| Projection Distance:    | 3.3 to 36.7 feet (1.0m to 11.2m)                                                        |
| Keystone Correction:    | ±15 degrees digital                                                                     |
| Electrical              |                                                                                         |
| Inputs:                 | 1 computer, 1 video, 1 S-video, 2 audio                                                 |
| Outputs:                | 1 monitor out, 1 audio (variable audio output)                                          |
| Video Compatibility:    | HDTV (1080I, 720p, 480p, 480i), NTSC, NTSC 4.43, PAL, SECAM, PAL60, PAL-M, PAL-N, YCbCr |
|                         | Component (using optional cable), 350 TV lines for SECAM                                |
| Y/C Separation:         | 3-line digital                                                                          |
| Computer Compatibility: | IBM PC and compatibles, Apple Macintosh                                                 |
| Synchronization Range:  | Horizontal: 15-100kHz (non-interlaced)                                                  |
| Vertical:               | 50-120Hz                                                                                |
| Color Reproduction:     | 16.7 million colors displayed simultaneously                                            |
| External Control:       | RS232, IR (AMX and Crestron compatibility)                                              |
| Built-In Speaker:       | 2 watt mono                                                                             |
| Power Requirements:     | 100-120 VAC/200-240 VAC, 50/60 Hz                                                       |
| Power Consumption:      | 200W (max)                                                                              |
| Fan Noise:              | 38dB Standard, 37dB ECO1, 36dB ECO2                                                     |
| Mechanical              |                                                                                         |
| Installation            | Front/Rear, Desktop/Ceiling                                                             |
| Dimensions:             | 11.8" (W) x 8.2" (D) x 3.4" " (H) 299mm(W) x 207mm(D) x 85mm(H)                         |
| Net Weight:             | 5.6 lbs. (2.5kg.)                                                                       |
| Operating Temperature:  | 32° to 95°F / 0° to 35°C                                                                |
| Regulations:            | USA UL 1950 FCC Class B                                                                 |
|                         | 0                                                                                       |

### Warranty

In the Box:

| Registered owners receive a 2-year limited parts and labor warranty including InstaCare.       |
|------------------------------------------------------------------------------------------------|
| InstaCare provides the original owner limited concurrent 3-business day repair/return or       |
| next business day exchange. The lamp, when used under normal operating conditions is warranted |
| for 1500 hours or 6 months, whichever comes first.                                             |
| Limited parts and labor for the first two years of ownership                                   |
|                                                                                                |

User's manual, full remote, batteries, power cable, 15-pin mini D-sub cable, carrying case,

quick connect guide, registration card, lens cap with attachment string, non-slip rubber pads,

Canada CSA950 (C-UL)

#### Product/Accessories

| i iouucij Accessories                                                     |  |
|---------------------------------------------------------------------------|--|
| Description                                                               |  |
| Component video adapter                                                   |  |
| Ceiling Mount                                                             |  |
| Replacement remote with mouse control                                     |  |
| Replacement lamp                                                          |  |
| 50" diagonal table top screen in compact carrying case                    |  |
| Rugged rolling case for shipping check-in and carry-on                    |  |
| Leather-like carry-on rolling case with laptop and projector compartments |  |
| Leather-like executive case with laptop and projector compartments        |  |
|                                                                           |  |







NEC 050212 15K

Empowered by Innovation

