3300 ANSI LUMENS • TRUE XGA • MULTIMEDIA PROJECTOR

PLC-XP41/L

XGA Portable Multimedia Projector



IMPRESSIVE 3300 ANSI LUMENS OF BRIGHTNESS

A 275W NSH lamp combined with Sanyo's new optical system delivers an impressive 3300 ANSI lumens of brightness.

INTELLIGENT DIGITAL SHARPNESS CONTROL

This high-performance image processing technology analyzes the incoming signal and controls the sharpness of picture data only, while text and other elements that are already sharp are left unprocessed.

ECO MODE FOR INCREASED LAMP LIFE

The PLC-XP41/L features a new Eco mode which switches the lamp ballast power from 275 watts to 220 watts, increasing lamp life while decreasing the brightness level approximately 20%.

3D DIGITAL PROGRESSIVE CIRCUIT

3D sampling for each pixel along with SANYO's unique movement detection algorithm program lead to increased vertical and diagonal resolution on moving video images.

NETWORK CONNECTIVITY

Sanyo's new optional PJ-Net Organizer system allows for operation and administration of a projector via a network. Presentations can be run, projector status can be checked, and projector functions can be controlled through a web browser. An alarm and notification can be automatically sent via E-mail whenever the projector encounters a problem, allowing the administrator to act quickly to resolve the issue.

HDTV COMPATIBLE

The SANYO PLG XP41/L is High Definition Television Compatible, accepting the 1080i, 1035i, 720p, 575p, 575i, 480p and 480i HDTV resolution standards.

DIGITAL KEYSTONE CORRECTION

SANYO's new X-Y digital keystone correction feature compensates for angled projector placement by digitally altering the pixels to produce undistorted images both horizontally and vertically.

WHISPER QUIET FAN

The PLC-XP41/L employs a new Whisper Quiet fan producing an amazingly low noise level of only 35 dBA (Eco mode).



Specifications

Resolution	XGA (1024 x 768)		
Brightness (typical)	3300 ANSI Lumens		
Uniformity	90%		
LCD Panel System	1.3" TET Poly x 3		
Number of Pixels			
Contrast Ratio	2,359,296 (/86,432 x 3)		
	550:1 (tull on/ott)		
Projection Image (diagonal)	31″-400″		
Aspect Ratio	4:3		
Throw Distance	4.6'-47'		
Zoom/Focus	Powered (1:1.3 zoom)		
Up/Down Ratio	10:0 – 1:1		
Digital Keystone Correction	Vert. +/- 40°, Horiz. +/- 10°		
Projection System	Polarized Beam Splitter optical system		
Projection Lens	F 1.8-2.1 / f1.9"-2.5"		
Lens Throw Ratio	1.82.4:1		
Projection Lamp	275W NSH		
Scanning Frequency	H 15-100kHz; V 50-100Hz (auto sense/select)		
Dot Clock	160 MHz		
Color System	PAL/PAL-M/PAL-N/SECAM/NTSC/NNTSC4.43		
Computer Compatibility	SXGA, XGA , SVGA, VGA		
Sound Output	l wo piece stereo 2W rms		
Voltage	100-240V AC; 50/60/Hz (auto sense/select)		
BTU Rating	1297		
dB Rating	35.0 (Eco mode)		
Power Consumption	380W		
Dimensions (WxHxD)	12.6" x6.6"x16.9"		
Net Weight	PLC-XP41: 17.4 lbs.; PLC -XP41L: 15.0 lbs.		
User Maintenance	Clean air filters, replace lamp assembly		
Input Terminal Panel 1	1 D-Sub 15 •1 DVI •1 audio (stereo mini jack)		
Input Terminal Panel 2	5 BNC (RGBHV) or 3BNC (Video/Y, Cb/Pb, Cr/Pr)		
	1 audio (stereo mini jack)		
Input Terminal Panel 3	3 RCA (Video/Y, Cb/Pb, Cr/Pr)		
	2 RCA Audio (L & R)1 S-Video		
Additional Input Terminals	1 Wired remote control jack (stereo mini jack)		
	 1 USB ●1 Control Port (Mini Din 8-pin) 		
Included Accessories	Wired/Wireless I/R Remote Control w/Mouse Pad		
	and Laser Pointer • AC power cord • VGA Cable		
	 Wired remote cable PS/2, Serial, MAC Control 		
	Cables • MAC/VGA Adapter • Dust cover		
	 Lens cover ● Owner's manual 		
Optional Accessories	Optional Lenses (see below)		
Warranty	Three years parts and labor; 90 days lamp;		
•	Quick Repair Program under warranty		

Because its products are subject to continuous improvement, SANYO reserves the right to modify product design and specifications without notice and without incurring any obligations.

Optional Lens Specifications			
	9	1	
	On-Axis Short Fixed	Short Zoom	Long Zoom
Part No.	LNS-W32	LNS-W31A	LNS- T31A
Zoom	No	Power	Power
Throw Ratio	0.8:1	1.25–1.8:1	2.3–4.2:1
F Stop	2.6	2.5 – 3.1	2.0 - 2.9
	9.25"	7.6"	8.5"
Weight	3.5 lbs.	3.7 lbs.	4.2 lbs.
No. Zoom Throw Ratio F Stop Length Weight	No 0.8:1 2.6 9.25" 3.5 lbs.	Power 1.25–1.8:1 2.5 – 3.1	T31A Power 2.3–4.2: 2.0 – 2. 8.5" 4.2 lbs.



Optional PJ-Net Organizer Model# POA-PN01