

PLC-XU73 | PLC-XU70 | PLC-SU70

Brilliant Ideas for Your Business.

SANYO

- Brightness: 2,000 ANSI lumens (PLC-XU73/SU70), 1,500 ANSI lumens (PLC-XU70)
- XGA Resolution (PLC-XU73/70), S-VGA (PLC-SU70)
- U-XGA compatible (PLC-XU73/70)
- Onscreen menu in 16 different languages
- Key lock function, PIN-code lock
- Direct power On/Off, fan noise 29 dB (Eco)
- Presentation kit
- 3 years warranty



PLC-XU73 | PLC-XU70 | PLC-SU70

Brilliant Ideas for Your Business.



TECHNICAL DETAILS	PLC-XU73	PLC-XU70	PLC-SU70
Category	Business & Education		
Panel	3 x 0.6" TFT p-Si		
Lamp	200 W UHP	180 W UHP	200 W UHP
Brightness ANSI lumens	2,000	1,500	2,000
Lamp Service Life	3,000 Hours (Eco)		
Standard Lens	F = 1.65 – 1.81 / f = 22.5 – 27 mm		
Aspect Ratio	1.78 – 2.14 : 1		
Distance	1.43 – 13.19 m (dimensions 81 x 61 – 610 x 457 cm) (please use the three-dimensional distance calculator at www.sanyo.de)		
Contrast Ratio	400 : 1 (Auto Mode)		
Resolution in pixels	1,024 x 768 (XGA)		800 x 600 (S-VGA)
Horizontal Resolution	600 TV lines		
Uniformity	85 %		
Bandwidth / Frequency	140 MHz, horizontal 15 ~ 100 kHz, vertical 50 ~ 100 Hz		
Color Systems	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N		
Connections	Input 1: D-Sub15 (RGB/components/SCART-RGB), (components/SCART-RGB with corresponding adapter cable, see "Optional Accessories"), 3.5 mm stereo jack Input 2 / Output: D-Sub15 (RGB or monitor output); Audio: shared with Input 1 Input 3: 1x Cinch (Composite), Mini-DIN 4-pin (S-Video); Audio: 2x Cinch (R/L-mono) Audio Output: 3.5 mm Stereo Jack (variable) Control Input: Mini-DIN 8-pin (RS-232), USB Typ B		
Audio	1 W Mono		
Keystone Correction	vertical +/- 20°		
Lens-Shift	Fix U/D Ratio 10 : 1		
HDTV Signals	720p / 1,035i / 1,080i (HDTV-compatible)		
Computer Compatibility	U-XGA / W-XGA / S-XGA / XGA / S-VGA / VGA / Mac		S-XGA / XGA / S-VGA / VGA / Mac
Zoom / Focus	1.2x / manual		
Power Consumption	260 W / 100 – 240 V		
Warranty	3 years warranty		
Dimensions (W x H x D) in mm	294.4 x 69.5 x 208 mm		
Weight	2.4 kg		
Standard Accessories	IR remote control, batteries, operating manual, D-Sub15-cable, lens cover with fastener and cord, power cable		
Optional Accessories	Components/D-Sub15-cable (POA-CA-COMPVGA), SCART/D-Sub15-cable (POA-CA-SCART), Presentation kit (POA-RC KIT02), IR remote control with laser pointer (POA-RC KIT03), replacement lamp, carrying bag		



Technical specifications are subject to change without notice. Status 08/2005.

