



Product Information

Ultra Portable LCD Projector



PLC-XU86



Features

- Separate LCD panels for faithful colour reproduction
- Quality Images in a compact stylish body
- Flexi lens
- Wireless USB LAN (802.11g)
- Wired LAN (Plink control)
- Viewer(Optional)USB Memory
- Power "off and go"
- Progressive scan
- 10-bit gamma correction
- Vertical digital keystone correction
- Digital and optical zoom
- Fan control system to reduce noise levels
- Pin code security function
- DVI-I (HDCP)
- User logo
- No show function

Specifications

Panel	0.7-inch TFT p-Si x 3
No. of pixels	2,359,296 (1024 x 768 dots)
Projection lamp	200W UHP 1.0 mm
Brightness	2500 lm
Contrast	500:1 (Lamp mode "AUTO" mode)
Uniformity	80% (corner to center)
Projection lens	F= 1.6 - 2.5 f= 17.7 - 28.3mm
Zoom	1.23 - 1.93:1, U:D = 10:1
Screen size	40"-300" 1.0~11.8m (100" at 2.5~3.9m)
Digital keystone correction	Vertical +/- 20°
HDTV signals	480i, 480p, 575i, 575p, 720p, 1035i and 1080i
Color systems	PAL / SECAM / NTSC / NTSC4.43 / PAL-M/N
Video Signal	PAL, SECAM, NTSC, NTSC4.43, PAL-M/N
Video Terminal	S-Video (Mini DIN4) Composite video(1 x RCA)
Computer compatibility	(UXGA/WXGA)/SXGA/XGA/SVGA/VGA/MAC
Computer Terminal	DVI-I for Input , D-sub15 pin for Input or out
Audio	RCA (L/R) for Video Input Mini-Jack(Stereo) for Computer Input Mini-Jack(Stereo) for output (variable)
Communication Terminal	Service Port(RS-232C) , USB type B RJ45 Plink
Presentation Tool	Freeze / Digital Zoom / No Show / Page up down
Other Feature	Progressive, 3-2 & 2-2 pull down, User Logo Security:PIN code lock , Key lock
Scanning frequency	H/V sync~100kHz,~100Hz Dot clock 140 MHz
Sound output	1.0 W Mono
Fan Noise	34/29 (eco) dB
Voltage	100V-240V AC (auto voltage)
Dimensions (W x H x D)	294.5 x 69.5 x 208 mm w x h x d
Weight	2.6 kg
Accessories included	Wireless-LAN USB-Key, Software DVI - D-Sub15 cable USB Cable (type A - type B) Soft carry bag

SANYO Oceania Pty Ltd. ABN 38 004 981 873
 211 Walters Road, Arndell Park, NSW 2148
 PHONE: (02) 8825-2822 FAX: (02) 9678-9381
www.sanyo.com.au