3M™ Digital Projector X68



- A great blend of features and performance!
- Powerful, bright performance.
- Ideal for medium sized rooms.
- Wide variety of computer and video connectivity.



CONNECTIONS

COMPUTER

- RGB (x2 input, x1 output)
- Audio (x2 input, x1 output)
- Serial Control

VIDEO

- Component Video
- S-Video
- RCA Composite
- RCA Audio (L,R)

BASIC SPECS

- 2500 lumens*
- XGA (1024x768)
- 7.7 lbs / 3.5 kg
- 400:1 Contrast ratio
- Vertical Digital keystone
- HDTV ready
- Whisper mode

*indicates maximum lumens rating

X68 Order Number: 78-9236-6848-3











1-800-328-1371 www.3m.com/meetings



3M™ Digital Projector X68



Optical

Brightness: typical: 2500 lumens*
Imager set: 0.7" Polysilicon LCD

Resolution (native): XGA (1024x768 pixels)
Resolution (maximum): SXGA (1280x1024 pixels)

Aspect ratio: 4:3 native, 16:9

• Colors: 16.7 million

• Screen size (range): 30-300 inches

Zoom / Focus: ManualZoom ratio: 1.2:1

Projection lens: F (focal length): (1.7-1.9) (f =21.8-26.2 mm)

Optional lenses: No

Contrast ratio (peak): 400:1

Lamp:230W UHB

· Lamp life (average): 2000

*indicates maximum lumens rating

Electrical

• Video compatibility: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM

HDTV: 480i, 480p, 525i, 525p, 720p, 1080i

• Keystone Correction: Vertical: ±15°

Audio: 1 x 1.0 w

Startup Screen: Customizable

Noise level: normal (whisper): 38 (33) dB

• Feature set: Auto off, 4x digital magnification, blank

Horizontal scan: 31-106 kHz

Vertical scan: 56-120 HzPower consumption: 370w

• Power supply: Universal: 100-120V / 220-240V

Regulatory approvals: UL, cUL, FCC Part 15 Class B, CE, EN60950

Operating temperature: 41 - 95 F (5 ~ 35 C)

• Storage temperature: -4 - 140 F (-20 - 60 C)

Size

Dimensions (W x H x D): 13.2 x 3.7 x 10.4 in. (33.6 x 9.5 x 26.5 cm)

Weight: 7.7 lbs / 3.5 kg

Warranties

Proiector: 3 Years Standard

 Ultra Value Warranty available—includes free lamp and free loaner while unit is repaired and expedited service.

· Lamp: 1 Year Prorated

3M Visual Systems Division

Building A145-5N-01 6801 River Place Blvd. Austin, TX 78726-9000

3M Mexico, S.A. de C.V.

Apartado Postal 14-139 Mexico, D.F. 07070 Mexico

3M Canada

P.O. Box 5757 London, Ontario, Canada N6A 4T1

© 3M 2005

78-6970-8581-5

Rev. September 2005

Accessories included

- Power Cords (x3 US, UK, Euro)
- RGB computer cable
- Remote control
- RCA audio & video cable
- Component video cable
- Multilanguage Quick Start Guide
- Multilanguage Operator's Guide CD
- Lens Cap

Optional Accessories

- Ultra Value Warranty X68 (WX68) 78-6969-9853-9
- Lamp for X68 (LKX75) 78-6969-9797-8
- Ceiling Mount, CMX75 (CM68) 78-6969-9802-6
- 26-47" Adjustable Extension for Ceiling Mount (HE100) 78-6969-9698-8

(a) Screen size [inch (m)]		4:3 screen							
		(b) Projection distance [m (inch)]				(c) Screen height [cm (inch)]			
		min.		max.		down		up	
30	(0.8)	0.9	(35)	1.1	(42)	5	(2)	41	(16)
40	(1.0)	1.2	(47)	1.4	(56)	6	(2)	55	(22)
50	(1.3)	1.5	(59)	1.8	(71)	8	(3)	69	(27)
60	(1.5)	1.8	(72)	2.2	(85)	9	(4)	82	(32)
70	(1.8)	2.1	(84)	2.5	(100)	11	(4)	96	(38)
80	(2.0)	2.4	(96)	2.9	(114)	12	(5)	110	(43)
90	(2.3)	2.7	(108)	3.3	(129)	14	(5)	123	(49)
100	(2.5)	3.1	(120)	3.6	(143)	15	(6)	137	(54)
120	(3.0)	3.7	(144)	4.4	(172)	18	(7)	165	(65)
150	(3.8)	4.6	(181)	5.5	(216)	23	(9)	206	(81)
200	(5.1)	6.1	(242)	7.3	(288)	30	(12)	274	(108)
250	(6.4)	7.7	(303)	9.2	(361)	38	(15)	343	(135)
300	(7.6)	9.2	(363)	11.0	(433)	46	(18)	411	(162)

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of 3 years from the time of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your

POSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.