

3M™ Digital Projector PX5



- Ultra portable and light DLP projector with incredible brightness and vibrant colors!
- Special unplug and go feature allows you to immediately take it on the go!
- Versatile-use on the road in the office, or at home.
- Superior security features with password protection and anti-theft lock.
- Dual Color Mode



CONNECTIONS

COMPUTER

- RGB
- PC Audio

VIDEO



- S-Video
- RCA Composite
- Audio (Stereo)

BASIC SPECS

- 1,300 lumens*
- XGA (1024x768)
- 2.9 lbs / 1.3 kg
- 2000:1 Contrast ratio
- Whisper mode
- Vertical Digital Keystone

* indicates maximum lumens rating

PX5 Order Number: 78-9236-6846-7



1-800-328-1371
www.3m.com/meetings

3M Innovation

3M™ Digital Projector PX5



OPTICAL

- Brightness: typical: 1,300 lumens*
- Imager set: DLP
- Resolution (native): XGA (1024x768 pixels)
- Resolution (maximum): UXGA (1600x1200 pixels)
- Aspect ratio: 4:3 native, 16:9
- Colors: 16.7 million
- Screen size (range): 26-300 inches
- Digital zoom: 1.2 times
- Projection lens: F (focal length): (2.6-2.9) (f =27.5-33.0mm)
- Optional lenses: No
- Contrast ratio (peak): 2000:1
- Lamp: 130W UHB
- Lamp life (average): 2000

*indicates maximum lumens rating

ELECTRICAL

- Video compatibility: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- HDTV: 480i, 480p, 720p, 1080i*
- Audio: 1 x 1w
- Noise level: normal 40 (38 in Eco-mode) dBA
- Feature set: Dynamic Color
- Horizontal scan: 15-68.7 kHz
- Vertical scan: 50-85 Hz
- Power consumption: 190w (170w in Eco-mode)
- Power supply: Universal: 100-240 VAC, 50/60 Hz
- Regulatory approvals: UL, cUL, FCC Part 15 Class B, CE, EN60950
- Operating temperature: 41 - 95 F (05 - 35 C)
- Storage temperature: 14- 140 F (-10 - 60 C)

SIZE

- Dimensions (W x H x D): (186 x46 x176 mm)
- Weight: 2.86 lbs / 1.3 kg

WARRANTIES

- Projector: 3 Years Standard
- Ultra Value Warranty available—includes free lamp and free loaner while unit is repaired and expedited service.
- Lamp: 1 Year Prorated

*Component Video is available through computer input. A VGA to RCA component video cable.

ACCESSORIES INCLUDED

- Power Cords (x3 - US, UK, Euro)
- RGB computer cable
- Remote control
- Multilanguage Quick Start Guide
- Multilanguage Operator's Guide CD
- Carrying Case

OPTIONAL ACCESSORIES

- Ultra Value Warranty PX5 (WPX5) 78-6969-9850-5
- Lamp for PX5 (LKPX5) 78-6969-9849-7

Screen Size Designation (inches)	Screen Size Width x Height		Projection Distance	
	(m)	(feet)	(m) Wide - Tele	(feet) Wide - Tele
40	0.81 x 0.61	2.67 x 2.00	1.54 - 1.85	5.04 - 6.08
60	1.22 x 0.91	4.00 x 3.00	2.33 - 2.80	7.64 - 9.19
80	1.63 x 1.22	5.33 x 4.00	3.12 - 3.75	10.23 - 12.30
100	2.03 x 1.52	6.67 x 5.00	3.91 x 4.70	12.82 - 15.41
120	2.44 x 1.83	8.00 x 6.00	4.70 - 5.64	15.42 - 18.52
150	3.05 x 2.29	10.00 x 7.50	5.89 - 7.07	19.31 - 23.18
180	3.66 x 2.74	12.00 x 9.00	7.07 - 8.49	23.20 - 27.84
200	4.06 x 3.05	13.33 x 10.00	7.86 - 9.44	25.79 - 30.95
250	5.08 x 3.81	16.67 x 12.50	9.84 - 11.81	32.28 - 38.73
300	6.10 x 4.57	20.00 x 15.00	11.81 - 14.17	38.76 - 46.50

There is a tolerance of + or - 5% due to design values. This table uses the lens apex and lens center as references and requires that the projector be in a horizontal condition (with front and rear adjusters fully withdrawn).

Important Notice

All statements, technical information, and recommendations related to 3M's products are on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publication, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized office of 3M.

Warranty, Limited Remedy, Limited Liability

This product will be free from defects in material and manufacture for a period of three years from the time of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss of damage arising from this 3M product, regardless of the legal theory asserted.

3M Visual Systems Division
Building A145-5N-01
6801 River Place Blvd.
Austin, TX 78726-9000

3M Mexico, S.A. de C.V.
Apartado Postal 14-139
Mexico, D.F. 07070
Mexico

3M Canada
P.O. Box 5757
London, Ontario, Canada
N6A 4T1

Litho in U.S.A. © 3M 2005
78-6970-8615-1
Rev. September 2005

www.3m.com/meetings

Specifications subject to change without notice.
3M is a trademark of 3M Company. Used under license in Canada. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

Hg—LAMP CONTAINS MERCURY. Manage in accord with disposal laws. See www.lamprecycle.org or call 1-800-328-1371 (USA), 1-800-364-3577 (Canada). For product disposal see www.elae.org (USA) or www.epsc.ca (Canada).

3M Innovation