

## SD205U SVGA DLP<sup>TM</sup> PROJECTOR



The SD205U is designed to be small and lightweight, but is powerfully enough at 2000 ANSI lumens to impress any audience.

## Value for the Cost Concious

The SD205U is an excellent choice for the cost conscious user who does not want to compromise on performance, quality and reliability. This ultra-portable DLP™ projector only weighs 5.3 lbs, supports native SVGA resolution, an amazing 2000:1 contrast ratio and shines bright at 2000 ANSI lumens for an impressively bright picture. It supports flexible connectivity options for both video and data, and is backed by Mitsubishi's exclusive ERA and Warranty programs.


- DLP™ technology
- Native SVGA (800x600) resolution
- 2000 ANSI lumens and a contrast ratio of 2000:1
- Lightweight at only 5.3 lbs
- 3-years or 10,000-hours on the TI-DLP DMD Chip, 2-years parts and labor, 2-years Express Replacement Assistance (ERA), 90-days or 300-hours lamp warranty





## **SD205U** SVGA DLP™ PROJECTOR

		DISPLAY TECHNOLOGY					
		RESOLUTION	800 x 600 (Total 480,000 pixels), 500 Video Lines				
		BRIGHTNESS	2000 ANSI lumens				
TOP VIEW	BACK VIEW	CONTRAST RATIO	2000 : 1 (on/off)				
		ZOOM/FOCUS	Manual Focus & Zoom Lens				
		PROJECTION LENS	F= 2.4 (Wide) 100"@3.2 m (Wide)				
		THROW RATIO					
		OFF SET AXIS	7.9 : -1 up (No variable lens shift)				
		PICTURE SIZE	40-300 diagonal inches				
		SOURCE LAMP	205W (Shut Off Time 2000 Hrs) with Low Mode (164W: Shut Off Time 3000 Hrs)				
		PC COMPATIBILITY	Resolution: 640 x 400 - 800 x 600 + Compressed 1024 x 768 Sync on Green available NTSC/NTSC 4.43/PAL (including PAL-M, N) /SECAM/PAL-60, Component Video; 480i/p				
A MITSUBISH		VIDEO COMPATIBILITY					
			(525i/p), 576i/p (625i/p), 720p (750p), 1080i (	1125i 60Hz), 1080i (1125i 50Hz)			
		INPUT TERMINALS	RGB: Mini D-sub 15pin x 1				
-(3, 3)-			Audio: Stereo Mini Jack (ø 3.5mm	i) x 1			
*©*			Video: RCA x 1 + S-VIDEO x 1				
		OUTPUT TERMINAL	RGB: Mini D-sub 15pin x 1				
ar	100 C		Audio: Stereo minijack (ø 3.5mm)	x 1 (variable lineout)			
		COMMUNICATION TERMINAL	USB terminal for Page Up/Down (with optional cable)				
		SCANNING RATE	[H] 15 - 80 kHz, [V] 50 - 85 Hz, [Dot Clock] max 110 MHz				
		AUDIO SPEAKER	2 W Mono				
		HEIGHT ADJUSTER	Rearward lifting leg x 2				
		HAND REMOTE UNIT	1) Projector fully control, 2) Power Point™ Page Up/Down via USB (with optional cable)				
	All Annual An	POWER CONSUMPTION					
		DIMENSION	10.28 x 8.58 x 3.42 inches (L x W x H)				
		WEIGHT	5.29 lbs.				
		POWER REQUIREMENTS	AC 100-240V, 50/60 Hz				
		FAN NOISE	36 dBA (Low mode: 30 dBA)				
TO STATE	TARABARANA AND A	SUPPLIED ACCESSORIES	Soft carrying bag	Composite cable			
000		Soft Eleb Accessiones	Remote control	Owner's manual (CD-ROM)			
41124			Power cable	Safety manual			
			VGA (D-sub) cable	Quick start manual			
		OPTIONAL ACCESSORIES	Replacement Lamp (VLT-XD205LP)				
SIDE VIEW	FRONT VIEW						
		WARRANTY	3-years or 10,000-hours on the TI-DLP DMD Chip, 2-years parts and labor, 2-years				
			Express Replacement Assistance (ERA), 90-da	ays or 300-hours lamp warranty			

SCREEN						DISTANCE FROM SCREEN (L)			Hd				
Diagor	nal Size	Wi	dth	He	ight	Max.Zoom		Min.Zoom				1	
inch	cm	inch	cm	inch	cm	inch	m	inch	m	inch	m	Ŧ	
40	102	32	81	24	61	50	1.3	60	1.5	3.5	8.8	Height	
60	152	48	122	36	91	76	1.9	91	2.3	5.2	13.3	Т	
80	203	64	163	48	122	101	2.6	121	3.1	7.0	17.7		
100	254	80	203	60	152	126	3.2	151	3.8	8.7	22.1		5
150	381	120	305	90	229	189	4.8	227	5.8	13.1	33.2		PH
200	508	160	406	120	305	252	6.4	302	7.7	17.4	44.2		1
250	635	200	508	150	381	315	8.0	378	9.6	21.8	55.3		
300	762	240	610	180	457	378	9.6	-	-	26.1	66.3		







MITSUBISHI ELECTRIC MITSUBISHI DIGITAL ELECTRONICS AMERICA, INC. Presentation Products Division Toll Free: 888.307.0349 Email: ppdinfo@mdea.com www.mitsubishi-presentations.com

Canada Mitsubishi Electric Sales Canada Inc. Information Technologies Group Phone: 905.475.7728 www.mitsubishielectric.ca



©2005 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. The DLP<sup>TM</sup> logo and DLP<sup>TM</sup> medallion are trademarks of Texas Instruments. Microsoft, Windows, and the Windows logo are registered trademarks of Microsoft Corporation. Mac and the Mac logo are trademarks of Apple Computer, Inc, registered in the U.S. and other countries. All other trademarks are the property of their respective holders. \*The projector lamp contains mercury. Please dispose of properly.

PP20069-11/05-15M-LITSD205U