



XJ-S30 & XJ-S35

- 2,000 ANSI Lumens
- Wide-angle 2X Optical zoom lens
- Native XGA Resolution
- Vertical Keystone Correction
- Size 10.6" Wide x 1.26" High x 7.83" Deep
- Weight Only 3.9 lbs.

XJ-S30 & XJ-S35

Ultra-Bright & Super Slim Portable Projector.

The XJ-S30 and XJ-S35 are high performance, super slim, portable, and compact projectors that set new standards with 2X wide-angle zoom lens. Choose any distance to the projection surface between 5.25 and 10.5 feet with optimum image quality in all cases. 2000 ANSI lumens mean you can project even in bright light.





Main Specifications

Model Name		XJ-S30	XJ-S35
Brightness		2000 ANSI lumens	2000 ANSI lumens
Lamp		200W high-pressure mercury lamp	200W high-pressure mercury lamp
Contrast ratio		1800:1 (In telephoto mode)	1800:1 (In telephoto mode)
Digital Vertical Keystone Correction		Auto: +30° Manual: ±30°	Auto: +30° Manual: ±30°
Focusing		Manual Focus (Electric)	Manual Focus (Electric)
Projection Lens		Optical 2X electric zoom	Optical 2X electric zoom
Projection Screen Size		15 inches to 300 inches	15 inches to 300 inches
Projection Range		Minimum: 2.8 feet 60" screen: 5.6 feet to 11.2 feet, 100" screen: 9.2 feet to 18.4 feet	Minimum: 2.8 feet 60" screen: 5.6 feet to 11.2 feet, 100" screen: 9.2 feet to 18.4 feet
Projection System		DLP® System	DLP® System
Display Element		0.55" DLP® chip 786,432 pixels (1,024 x 768)	0.55" DLP® chip 786,432 pixels (1,024 x 768)
Color Reproduction		Full color (16.77 million colors)	Full color (16.77 million colors)
RGB	Input Terminals	RGB Mini D-Sub 15 pin x 1 (YCbCr/YPbPr input, shared)	RGB Mini D-Sub 15 pin x 1 (YCbCr/YPbPr input, shared)
	True	XGA (1,024x768)	XGA (1,024x768)
	Compressed	Maximum - SXGA (1,280 x 1,024)	Maximum - SXGA (1,280 x 1,024)
Video	Signal Input	NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM	NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM
	Input Terminals	Composite: RCA pin terminal x 1 YCbCr/YPbPr: Mini D-Sub 15 pin x 1 (RGB input, shared)	Composite: RCA pin terminal x 1 YCbCr/YPbPr: Mini D-Sub 15 pin x 1 (RGB input, shared)
USB	Interface	N/A	TypeA x 1, USB (1.1) Host
	Connectable Equipment*	Supported by the YP-100 Multifunctional Presentation Kit	<ol style="list-style-type: none"> 1. Wireless (IEEE 802.11b) Adapter YW-2S 2. CASIO-brand digital cameras (supported models only) 3. USB memory (commercially available) 4. Multifunctional Camera YC-400
Power		AC100 to 240V, 50/60Hz	AC100 to 240V, 50/60Hz
Dimensions		10.6"(W) x 7.83"(D) x 1.7"(H) (excluding projections, 1.26" at thinnest part)	10.6"(W) x 7.83"(D) x 1.7"(H) (excluding projections, 1.26" at thinnest part)
Weight		Approximately 3.9 lbs.	Approximately 3.9 lbs.
Security compatibility		Kensington-compatible/Power On Password	Kensington-compatible/Power On Password
Other functions		Digital Zoom (4X), Freeze, Pointer, Color Mode, Direct Power On, Eco-Mode	Digital Zoom (4X), Freeze, Pointer, Color Mode, Direct Power On, Eco-Mode
Bundled Accessories		Wireless remote controller, AC cord, RGB cable, Video cable, CD-ROM, Soft case	Wireless remote controller, AC cord, RGB cable, Video cable, CD-ROM, Soft case

* Limited to CASIO-designated products. Information will appear on the CASIO website on supported digital camera models and USB memory devices that have been confirmed to work.

CASIO

All specifications and designs are subject to change without notice
DLP® and the DLP logo are registered trademarks of Texas Instruments.

CASSIOPEIA® PRO

Casio, Inc. | 570 Mt. Pleasant Ave. | Dover, NJ 07801
For more information and dealer locations, go to: www.casioprojector.com