

TOSHIBA



xd2000

Originals are detected
by design and brilliance.

- attractive design
- High security (password function and panellock)
- easy set-up and „easy to use“



LCD stands for
Liquid Cristal Display



xd2000



Immerse yourself in a world of colour.

Display 0,61" LCD Chip

Resolution XGA 1,024 x 768

Brightness 2,000 ANSI-lumens

Colour reproduction 16.7 mio. colours

Contrast 400 : 1

Projection format 4 : 3 switchable to 16 : 9

Lamp 210 W (TLPLW11LAMP)

Max. lamp life up to max. 2,000 hours/
um to max. 3.000 hours in ECO mode

Lens F = 1.6 - 1.89 / f = 18.6 - 22.3 mm,
manual zoom and focus

Zoom 1.2 x

Frequency (hor./vertical) 15 - 120 kHz / 30 - 150 Hz

Projection front, rear and ceiling

Digital keystone correction auto vertikal

Input signals NTSC / PAL / SECAM, 480i, 480p, 576i, 576p,
720p, 1,080i, VGA / SVGA, XGA / SXGA / UXGA (compr.)

Inputs RGB (D-sub 15), S-video, composite video (1 x RCA),
RGB audio (stereo mini jack), video / S-video audio (1 x RCA L/R)

Outputs RGB (D-sub 15), audio (stereo mini jack)

Serial interface RS-232C (mini DIN8 pin)

Power supply AC 100 - 240 V, 50 / 60 Hz

Loudspeaker 1 W mono

Dimensions (W x H x D) 295 x 81 x 255 mm

Weight 2.5 kg

Operation noise standard 34 dB / ECO mode 29 dB

Specials security-functions, user logo, password, panellock

Accessories remote control with batteries, owners
manual (CD ROM), quick reference, RGB and power cable,
softcase

Options ceiling mounting, trolley, spare lamp, camera c001

