

you can  
**Canon**

MULTIMEDIA PROJECTOR

**LV-7265**

Stunning performance.  
Exceptional value.



With a Canon wide-angle 1.6x zoom lens, the LV-7265 is ideal for spaces of any size - from corporate boardrooms to smaller meeting rooms. XGA resolution, powerful brightness and a DVI port ensure crisp, clear images even in broad daylight.

- Native XGA resolution for crisp image detail
- 2500 lumens for ultra bright images even in daylight
- High 600:1 contrast ratio for brighter whites, darker blacks and vivid colours
- Near-silent 30dBA Quiet Mode
- Flexible placement and short throwing distances with Canon wide 1.6x zoom lens
- Automatic Vertical Keystone Correction, ensures image edges stay parallel
- HDCP-enabled DVI port for razor-sharp images from digital sources, including encrypted content
- Built-in 5W speaker for convenient, powerful sound
- Screen Colour Correction for natural colours when projecting onto coloured surfaces
- Fast 8 second start up and just 30 second cool down
- Lightweight - weighs just 3.1kg.



# Specifications LV-7265

<b>LCD PANEL</b> Type Size and Number Aspect Ratio Native Resolution	Transmissive LCD, Poly-silicon TFT Active Matrix 0.63" diagonal with microlens, 3 panels 4:3 1024 x 768 (XGA), 786432 pixels
<b>OPTICS</b> Light Source Lens F Number & Focal Length Zoom Magnification & Control Focus Control Lens Shift	200W NSH lamp F1.6 - F2.5; f=17.7 - 28.3mm 1.6x Manual Manual 8.4 : 1.6 (fixed)
<b>IMAGE AND AUDIO</b> Brightness Brightness Uniformity Contrast Ratio Projection Distance Coverage Screen Size Digital Zoom Magnification Keystone Correction Range Digital RGB Compatibility Analogue RGB Compatibility Digital Video Scan Systems Component Video Scan Systems Video / S-Video Colour Systems Digital Scanning Frequency Analogue Scanning Frequency Display Modes Image Enhancement Built-in Speaker	2500 lumens (1875 lumens in Quiet Mode) 85% 600:1 (full on / full off) 1.0m - 8.4m (2.8m - 4.3m for a 100 inch image) 25" - 300" (51 x 38cm - 610 x 457cm) 1x - 4x (16x Area Ratio) Vertical: +/- 30° (Auto / Manual) SXGA+ / SXGA / XGA / SVGA / VGA / MAC UXGA / SXGA / XGA / SVGA / VGA / MAC 1080i / 720p / 575p / 480p 1080i / 720p / 575p / 575i / 480p / 480i PAL / PAL-M / PAL-N / PAL-60 / NTSC / NTSC4.43 / SECAM Horizontal: 31-90kHz, Vertical: 50-85Hz, Clock: 108MHz Horizontal: 15-100kHz, Vertical: 50-120Hz, Clock: 108MHz Standard, Presentation, Movie, Video, sRGB, Custom Digital Gamma Correction 5.0W RMS, Monaural

<b>CONNECTORS</b> Analogue RGB Input 1 Digital RGB Input / Analogue RGB Input 2 Analogue RGB Output S-Video Input Composite Video Input Audio Input 1 Audio Input 2 Audio Output Service Port / Projector Control	Mini D-Sub 15-pin (Component Video via optional cable)  DVI-I 29-pin, HDCP compatible Mini D-Sub 15-pin Mini DIN 4-pin RCA x 1 3.5mm2 stereo mini-jack x 1 RCA x 2 (L/R) 3.5mm2 stereo mini-jack x 1 (variable level) Mini-DIN 8-pin
<b>MECHANISMS</b> Front Elevation Mechanism	Mechanical foot, 10° maximum image elevation
<b>RATINGS</b> Dimensions (W x H x D) Weight Power Source Power Consumption  Noise Level Operating Environment Storage Environment Warranty	310mm x 109mm x 265mm 3.1kg 100V - 240V AC, 50/60Hz Normal Mode: 285W Quiet Mode: 220W Standby: 9W Normal Mode: 35dBA, Quiet Mode: 30dBA +5°C to +40°C -10°C to +50°C 3 years (90 days for lamp)
Some images are simulated for clarity of reproduction. All data is based on Canon's standard testing methods. This leaflet and the specifications of the product have been developed prior to the date of product launch. Final specifications are subject to change without notice. ™ and ©: All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries	

## Accessories

In-box	Optional					
<ul style="list-style-type: none"> <li>- Soft Carrying Case</li> <li>- Remote Control Unit</li> <li>- AAA Alkaline Batteries x 2</li> <li>- Lens Cap</li> <li>- AC Mains Power Cable</li> <li>- VGA Computer Connection Cable</li> <li>- USB Infrared Mouse Receiver</li> <li>- DVI to VGA Adaptor</li> </ul>						
	Replacement Lamp LV-LP26	Canon Ceiling Mounting Bracket LV-CL11	DVI Cable LV-CA29	Component Video Adapter Cable LV-CA32	RS-232C Control Cable LV-CA34	VGA Extension Cable, 10 metres LV-CA02

TRUE THROW DISTANCES								
Screen Size	25		40		80		100	
inches	25	40	80	100	150	200	300	
cm	51 x 38	81 x 61	163 x 122	203 x 152	305 x 229	406 x 305	610 x 457	
Projection Distance								
Zoom max	-	1.1m	2.2m	2.8m	4.2m	5.6m	8.4m	
Zoom min	1.1m	1.7m	3.5m	4.3m	6.5m	-	-	

For more information regarding throw distances, please visit: [www.canon.com/lcd-sim](http://www.canon.com/lcd-sim)

