



Performance, Reliability and Quality at a Value Price

The Mitsubishi XD206U (XGA) is a DLP® projector that offers great value, with a bright 2000 ANSI lumens and a rich 2000:1 contrast ratio in a small, lightweight package just over six pounds.

Presenters will enjoy the versatile features the XD206U has to offer, such as the flexible connectivity options for both video and data sources, time-saving instant shut down, and a lightweight design for quick and simple show and go portability. School administrators will especially enjoy how the XD206U can be fully integrated into classrooms or meeting rooms for seamless interaction with smart boards or remote control systems via RS232C communication, as well as its cost saving, low maintenance filter-free design. Built-in security features such as password-protected menus and an anti-theft security bar can deter any unauthorized projector removal from classrooms or media carts. External monitor hookup also enables teachers to face the class during lecture.

The XD206U includes a lamp life rating of up to 3000-hours*, the proven durability of DLP® technology, and Mitsubishi's exclusive Express Replacement Assistance (ERA) warranty. The XD206U is built with the high quality standards you expect from Mitsubishi projectors and is an excellent choice for cost conscious users.

**low mode rating*



- Native XGA resolution
- DLP® technology
- Bright 2000 ANSI lumens and 2000:1 contrast ratio
- RS232C Communication Support
- Anti-theft security bar
- Cost-saving filter-free design
- Up to 3000-hour lamp life (low mode)
- 6.4 lbs. portable design




XD206U

DLP® ULTRAPORTABLE PROJECTOR



XD206U: SCREEN					DISTANCE FROM SCREEN (L)				Hd	
Diagonal Size		Width		Height	Max.Zoom	Min.Zoom		Hd		
inch	cm	inch	cm	inch	inch	m	inch	m	inch	cm
40	102	32	81	24	63	1.6	54	1.4	-3.5	-8.8
60	152	48	122	36	95	2.4	82	2.1	-5.2	-13.3
80	203	64	163	48	127	3.2	109	2.8	-7.0	-17.7
100	254	80	203	60	160	4.1	137	3.5	-8.7	-22.1
150	381	120	305	90	229	6.1	206	5.2	-13.0	-33.1
200	508	160	406	120	320	8.1	275	7.0	-17.4	-44.2
250	635	200	508	150	400	10.2	344	8.7	-21.7	-55.2
300	762	240	610	180	-	-	413	10.5	-26.1	-66.3

Unit measured in inches. *Hd is distance from lens axis to image bottom.



Unit measured in millimeters (mm)

DISPLAY TECHNOLOGY	0.55", 1-Chip DMD, 12 deg. DDR, DDP2000
RESOLUTION	1024 x 768 (Total 786,432 pixels), 550 Video Lines
BRIGHTNESS	2000 lumens
CONTRAST RATIO	2000 : 1
COLOR	16,777,000 colors
ZOOM/FOCUS	Manual Focus & Zoom Lens (Zoom Ratio 1.2 : 1)
PROJECTION LENS	f=19.0-21.9mm, F=2.4-2.6, 138"-161"@100" diagonal
THROW RATIO	1.7-2.0
OFF SET AXIS	7.9 : -1 up (No variable lens shift)
PICTURE SIZE	40-300 inches diagonal
SOURCE LAMP	205W (Shut Off Time: 2000hrs), Low Mode:164W (Shut Off Time: 3000hrs)
PC COMPATIBILITY	Resolution: 640 x 400 - 1024 x 768 + Compressed 1280 x 1024; Sync on Green available
VIDEO COMPATIBILITY	NTSC/NTSC 4.43/PAL (including PAL-M, N) /SECAM/PAL-60, Component Video; 480i/p (525i/p), 576i/p (625i/p), 720p (750p), 1080i (1125i 60Hz), 1080i (1125i 50Hz)
INPUT TERMINALS	RGB: Mini D-sub 15pin x 1 Audio: Stereo Mini Jack (ø 3.5mm) x 1 Video: RCA x 1 + S-VIDEO x 1
OUTPUT TERMINAL	RGB: Mini D-sub 15pin x 1 Audio: Stereo minijack (ø 3.5mm) x 1
COMMUNICATION TERMINAL	RS-232C (D-sub), Page Up/Down (USB)
SCANNING RATE	[H] 15 - 80 kHz, [V] 50 - 85 Hz, [Dot Clock] max 110 MHz
AUDIO SPEAKER	2W Mono
HEIGHT ADJUSTER	Front lifting leg x1
HAND REMOTE UNIT	Full Projector Control, MS PowerPoint™ page up/down
POWER CONSUMPTION	300W 2.9A, Standby Less than 10W
DIMENSION	10.08" x 3.46" x 8.78" (256 x 88 x 223 mm) (W x H x D)
WEIGHT	6.4 lbs. (2.9 kg.)
POWER REQUIREMENTS	AC 100-240V, 50/60 Hz
FAN NOISE	37 dBA (Low mode: 34 dBA)

SUPPLIED ACCESSORIES	<ul style="list-style-type: none"> • Carrying bag • Remote Unit (incl. Battery) • Power cable • VGA cable • Composite cable • Owner's manual (CD-ROM) • Quick Start guide • Safety Manual • Lens cap
OPTIONAL ACCESSORIES	Replacement Lamp (VLT-XD206LP), Hard Shell Rolling Case (XD10-ATAC)
WARRANTY	3-years or 10,000-hours on the TI-DLP DMD Chip, 3-years part and labor, 3-Years Express Replacement Assistance (ERA), 90-days lamp warranty
OUTSTANDING FEATURES	<ul style="list-style-type: none"> • Anti-theft security bar • Digital keystone correction (vertical) • Video line doubler - 2:3 pull-down • Password lock • Instant shutdown • 10 Language OSD



MITSUBISHI DIGITAL ELECTRONICS AMERICA, INC.
Presentation Products Division
Toll Free: 888.307.0349
Email: pppinfo@mdea.com
www.mitsubishi-presentations.com

Canada
Mitsubishi Electric Sales Canada Inc.
Information Technologies Group
Phone: 905.475.7728
www.mitsubishielectric.ca



©2007 Mitsubishi Digital Electronics America, Inc. Standard features, options and specifications subject to change without notice. All trademarks are the property of their respective holders.

PP7001-1/06-15M-LTXD206U