

3M™ Digital Projector S55 and X55



- Take your presentation to a new level with our sophisticated new design!
- Relax. Backed by 3M's quality, reliability and **3yr warranty**
- Versatile — use on the road, in the office, or at home.
- Expanded range of computer and video connections.

DESIGN BY

pininfarina

Official Designer of Ferrari for over 50 years.



CONNECTIONS

COMPUTER


- RGB (x2 input, x1 output)
- USB mouse emulation
- Serial Control

VIDEO

- Composite Video
- Component Video
- S-Video

BASIC SPECS

- **S55:** 2000 lumens | **X55:** 2000 lumens
- **S55:** SVGA (800x600) | **X55:** XGA (1024x768)
- 2.65 kg
- Vertical Digital keystone
- HDTV ready



S55 Order Number: 78-9236-6836-8
X55 Order Number: 78-9236-6838-4



UK: 01234 229695/7 Ireland: 01 280 3555
www.3m.com/meetings

3M Innovation

3M™ Digital Projector S55 and X55



Optical

- Brightness: typical : **S55:** 2000 lumens
X55: 2000 lumens
- Imager set: 0.7" Polysilicon LCD
- Resolution (native): **S55:** SVGA (800x600 pixels)
X55: XGA (1024x768 pixels)
- Resolution (maximum): UXGA (1600x1200 pixels)
- Aspect ratio: 4:3 native, 16:9
- Colours: 16.7 million
- Screen size (range): 30-301 inches
- Zoom / Focus: Manual
- Zoom ratio: 1.2: 1
- Projection lens: F (focal length): (1.7-1.9) (f =21.8-26.7 mm)
- Optional lenses: No
- Contrast ratio (peak): 400:1
- Lamp: W, Type: 165w UHB
- Lamp life (average): 2,000

Electrical

- Video compatibility: NTSC, NTSC 4.43, PAL, PAL-M, PAL-N, SECAM
- HDTV: 480i, 480p, 525i, 525p, 720p, 1080i
- Keystone Correction: Vertical: ±10°
- Audio: 1 x 1w
- Startup Screen: customisable
- Noise level: normal (whisper): 41 (35) dB
- Feature set: Auto off, 4x digital magnification, blank, mouse emulation, progressive scan
- Horizontal scan: 31-91 kHz
- Vertical scan: 56-120 Hz
- Power consumption: 240w
- Power supply: Universal: 90-132V / 198-264V (50/60 Hz)
- Regulatory approvals: UL, cUL, FCC Part 15 Class B, CE, TUV, EN60950
- Operating temperature: 32 - 95 F (0 - 35 C)
- Storage temperature: -4 - 140 F (-20 - 60 C)

Size

- Dimensions (W x H x D): 12.2 x 10 x 3.5 in. (30.8 x 8.6 x 25.2 cm)
- Weight: 2.65 kg

Warranties

- Projector: 3 Years Standard

3M United Kingdom PLC
Hudson Road
Bedford
Bedfordshire MK41 0HR

3M Ireland
3M House
Adelphi Centre
Dun Laoghaire, Co. Dublin

Accessories included

- Power Cords (x3 - US, UK, Euro)
- RGB computer cable
- Remote control
- Swivel Base
- Multilanguage Quick Start Guide
- Multilanguage Operator's Guide CD
- Soft side bag

Optional Accessories

- Lamp S55 (LKS55) 78-6969-9790-3
- Lamp X55 (LKX55) 78-6969-9790-3
- Ceiling Mount, Gyrolock style (CM45/55) 78-6969-9791-1
- 26-47' Adjustable Extension for Gyrolock (HE100) 78-6969-9698-8
- Wheeled Softcase FB.1100.0733.3
- Deluxe Leather Case FB.1100.0795.2

PROJECTION DISTANCE CHARTS — 3M S55 AND X55

Distance to Screen		Screen Size		
Minimum	Maximum	Diagonal	Width	Height
3.92ft. 1.2m	4.67ft. 1.4m	40in. 101.6cm	32in. 81.3cm	24in. 61.0cm
5.92ft. 1.8m	7.08ft. 2.2m	60in. 152.4cm	48in. 121.9cm	36in. 91.4cm
7.87ft. 2.4m	9.51ft. 2.9m	80in. 203.2cm	64in. 162.6cm	48in. 121.9cm
9.8ft. 3.0m	11.81ft. 3.6m	100in. 254.0cm	80in. 203.2cm	60in. 152.4cm
11.92ft. 3.6m	14.4ft. 4.4m	120in. 304.8cm	96in. 243.8cm	72in. 182.9cm
15ft. 4.6m	18ft. 5.5m	150in. 381.0cm	120in. 304.8cm	90in. 228.6cm
20ft. 6.1m	24ft. 7.3m	200in. 508.0cm	160in. 406.4cm	120in. 304.8cm

Note: These sizes are ±10 percent. This is due to variations in the manufacture of the lens. If you are close to one of the endpoints you should verify with your unit that the image is the proper size at the proper distance.

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.

Warranty; Limited Remedy; Limited Liability

This product will be free from defects in material and manufacture for a period of 3 years from the time of purchase. 3M MAKES NO OTHER WARRANTIES or CONDITIONS INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE. If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.