








DX319

DLP® Projector

Your best partner for presentations

-  Bright projection – 2500 ANSI Lumens
-  XGA resolution, 2500:1 contrast ratio for sharp, detailed presentations and graphics
-  Energy saving <1W standby mode
-  Security bar and password protection for added security
-  RS232 for meeting room control systems
-  Low ownership costs – up to 4000hrs lamp life
-  DLP® filter-free design – Virtually no maintenance



Interact with your audience

From boardroom to classroom, the DX319 delivers bright, high contrast presentations and images with crystal clarity. Vibrant, life-like colours using BrilliantColor™ technology will ensure your audience is left speechless every time the DX319 is turned on.

The environmentally friendly DX319 has energy saving features including <1W standby mode. Long lamp-life of 4000hrs combined with our unique Optoma Colour guarantee saves you both time and money whilst ensuring hassle-free, long lasting projection.

CLEAR, FOCUSED IMAGES

Technology from Texas Instruments produces a stunning 2500:1 contrast ratio for pin sharp graphics and crystal clear text. Crisper whites, ultra-rich blacks makes images come alive and text easier to read - ideal for business and education presentations.



1000:1 contrast ratio

2500:1 contrast ratio

*Simulated Image

AMAZING COLOURS

The DX319 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

Preset display modes allow you to achieve a perfect image on a variety of surfaces including screens and interactive whiteboards.

COLOUR PERFORMANCE

Optoma guarantees colour quality will remain as new for 5 years*

Once you've purchased the DX319, Optoma guarantees that the colours will not fade for a minimum of 5 years.



Interact with your students
in the classroom

MAINTENANCE FREE = LOWER TOTAL COST OF OWNERSHIP (TCO)

DLP® technology ensures lower cost of ownership, longer life and improved reliability compared to other technologies.

The filter-free projector design means no more regular filter cleaning or replacements, saving you time and money.



TIME AND ENERGY SAVINGS

The DX319 incorporates energy saving features to conserve power and extend the lamp life:



The timer control functions can automatically switch the projector off to standby mode <math>< 1W</math>, conserving power and extending the lamp life to an astonishing 4000 hours**.



It takes less than 10 seconds for the projector to power up and shutdown, so the DX319 not only saves time but energy too.

CONTROL

The extensive RS232 command set makes it simple and easy to control the DX319 with any control system.



AMX Compatibility – Dynamic Discovery Protocol is incorporated into the DX319. This feature allows for easy installation with AMX control systems.

SMOOTH, SEAMLESS PROJECTION

Even in the fastest moving scenes, the DX319 will project a smooth and seamless image. The rapid response of DLP® technology ensures that the projected movie or video game remains perfect and precise.



With



Without

FEATURES

- 6 preset display modes
- Classroom mode - 1500 ANSI Lumens
- Quick keystone correction
- Security bar and password protection for added security
- Easy to use remote with direct source control



Enjoy big colourful presentations
with the lights on

DX319 SPECIFICATIONS

Native Resolution	XGA 1024 x 768
Compressed Resolution	UXGA (1600 x 1200)
Brightness	BRIGHT mode 2500 ANSI Lumens Classroom mode 1500 ANSI Lumens
Contrast	2500:1
Noise Level	28dB
Lamp Life**	4000/3000 (STD/BRIGHT mode)
Projection Lens	F/2.41~2.55; f=21.8~24mm, 1.1x Manual Zoom
Throw Ratio	1.95 - 2.15:1 (Projection Distance:Image Width)
Projection Distance	1.2 - 12m
Image Size	0.70 – 7.70m (27.49" - 303.12") Diagonal 4:3
Display Technology	Single 0.55" XGA DMD chip DLP® Technology by Texas Instruments
Weight / Dimensions (W x D x H)	2.3 kg / 286 x 192 x 84mm
Remote Control	Full function remote with direct source selecting
INPUTS	2 x 15 Pin D-Sub VGA (SCART & Component via adaptor) S-Video 4 Pin Mini Din Composite RCA 3.5mm Audio Mini Jack
CONTROL	RS232 - 3 Pin D-sub
OUTPUT	15 Pin D-Sub VGA Stereo Audio Mini Jack
Audio	2W Speaker
Aspect Ratio	4:3 Native, 16:9 Compatible
Keystone Correction	± 40° Vertical
On Screen Display	18 Languages: English, German, French, Italian, Spanish, Portuguese, Polish, Dutch, Russian, Finnish, Swedish, Greek, Norwegian, Danish, Hungarian, Czech, Turkish & Arabic
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p
Uniformity	85%
Displayable Colours	1.07 Billion
Horizontal Scan Rate	15.3 - 91.1kHz
Vertical Scan Rate	24 - 85Hz
Power Supply	100 - 240V, 50 - 60Hz
Power Consumption	233W BRIGHT mode < 1W Standby mode 207W STD mode < 1W Standby mode
Operating Conditions	Operating: 5 - 40°C, 85% Humidity (Max), 3000m Altitude (Max)
Security	Security Bar, Kensington Lock Port, Password Protection
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, Full Function Remote, Batteries x 2, Quick Start Guide, CD User Manual, Warranty Card, WEEE Card
RoHS	Compliant
Lamp Warranty	6 months or 1000 hours - whichever comes sooner
Warranty	Warranty may vary by country. Please see www.optomaeurope.com or ask your local supplier for details
Colour Guarantee*	5 Years

EASY TO USE REMOTE CONTROL

DX319 Remote Control

- 1 Vertical Keystone Correction
- 2 Volume Control
- 3 Brightness Adjustment
- 4 Contrast Adjustment
- 5 AV Mute
- 6 Direct Input Source Selection



DX319 Connections

- 7 VGA 2
- 8 VGA 1 - SCART & Component
- 9 S-Video
- 10 Composite Video
- 11 RS232 - 3 Pin
- 12 VGA Out
- 13 Audio Out
- 14 Audio In
- 15 Kensington™ Lock
- 16 Security Bar

Exceptional Connectivity/ Multiple Terminals



Easy to use remote with buttons to change the input sources



DX319 Projection Distance 1.2 - 12m (4:3 Aspect Ratio)								
Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)	
1.20	0.62	0.56	0.46	0.42	0.77	30.31	0.07	
2.00	1.03	0.93	0.77	0.70	1.28	50.52	0.12	
2.50	1.28	1.16	0.96	0.87	1.60	63.15	0.14	
3.00	1.54	1.40	1.16	1.05	1.92	75.78	0.17	
4.00	2.05	1.86	1.54	1.40	2.57	101.04	0.23	
5.00	2.56	2.33	1.93	1.75	3.21	126.30	0.29	
6.00	3.08	2.79	2.31	2.10	3.85	151.56	0.35	
7.00	3.59	3.26	2.70	2.45	4.49	176.82	0.40	
8.00	4.10	3.72	3.08	2.80	5.13	202.08	0.46	
9.00	4.62	4.19	3.47	3.15	5.77	227.34	0.52	
10.00	5.13	4.65	3.86	3.50	6.42	252.60	0.58	
11.00	5.64	5.12	4.24	3.85	7.06	277.86	0.64	
12.00	6.15	5.58	4.63	4.20	7.70	303.12	0.69	

For guide purposes only

DX319 is capable of 16:9 aspect ratio projection. When projecting a 16:9 image the image sizes, screen height and offset information will differ from the above.