

# BenQ Digital Projector Specifications

## MP777



### HIGHLIGHTS

- **Filter Free Design**
- **4000 ANSI Lumens**
- **Crestron LAN Control**
- **RoomView®**
- **XGA Native Resolution**
- **3D Ready**
- **BrilliantColor™**
- **VIDI™**
- **No Color Decay**
- **3D Color Management**
- **6 Segments Color Wheel**
- **Auto Keystone (+/- 40 Degree)**
- **5W Speakers x 2**
- **HDMI (V1.3)**
- **Variable Audio Out**
- **Closed Captioning**
- **Panel Key Lock**
- **Quick Cooling**
- **Quick Auto Search**
- **Security Password**
- **12V trigger**

Projection System	DLP™ technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	4000 ANSI lumens	
Contrast Ratio	2600:1 (Full on/Full off)	
Aspect Ratio	4:3 Native (4 aspect ratio Selectable)	
Color	Full 16.7 million color palette	
Lens	F=2.56	
Zoom Ratio	Manual Zoom, 1.3:1	
Image Size (Diagonal)	25" to 300"	
Throw Ratio	1.51 to 1.96 (65"@2M)	
Lamp	280W, 3000/4000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 480) to UXGA(1600 x 1200)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080p	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-93 kHz	
Vertical Scan Rate	48-86 Hz	
Input Terminals	PC	D-sub 15 pin x 2
	A/V	HDMI(v1.3) x 1
		S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
Audio	Audio L/R x 2; Stereo mini jack x 1	
Output Terminal	PC	12V Trigger
		D-sub (15 pin) X 1
	Audio	Variable Audio Out: Stereo mini jack x1 5 Watt Speaker x 2
Control Terminal	LAN (RJ45); RS232 9 pin Type 1	
Dimensions(W x H x D)	11.4 x 3.7 x 9.9 inch (290 x 94 x 252 mm)	
Weight	7.7 lbs (3.5 kg)	
Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power Consumption	Max 425W, Standby<1W	
Audible Noise	34/29 dB (Normal/Economic mode)	
On-Screen Display Languages	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai/ Polish	
Application Modes	<b>PC Input:</b>	<b>A/V Input :</b>
	Dynamic Mode Presentation Mode sRGB Mode Cinema Mode User 1 Mode User 2 Mode	Dynamic Mode Presentation Mode sRGB Mode Cinema Mode User 1 Mode User 2 Mode
Other Functions	Digital Zoom (x2)	HDTV compatible
	Freeze	High Altitude Mode
	Auto off	"Q?" Hot Key for FAQ
	Blank	
Accessories (Standard)	Quick Start Guide	VGA cable
	Manual CD	Power cord
	Remote control w/Battery	Soft Carrying Case
Accessories (Optional)	Ceiling Mounting Kit	Spare Lamp Kit
	Presentation Plus	