

BenQ Digital Projector Specifications

MP776



HIGHLIGHTS

- **Filter Free Design**
- **3500 ANSI Lumens**
- **Crestron LAN Control**
- **RoomView®**
- **XGA Native Resolution**
- **3D Ready**
- **BrilliantColor™**
- **VIDI™**
- **No Color Decay**
- **3D Color Management**
- **6 Segments Color Wheel**
- **Auto Keystone (+/- 40 Degree)**
- **5W Speakers x 2**
- **HDMI (V1.3)**
- **Variable Audio Out**
- **Closed Captioning**
- **Panel Key Lock**
- **Quick Cooling**
- **Quick Auto Search**
- **Security Password**
- **12V trigger**

Projection System	DLP™ technology by Texas Instruments®	
Native Resolution	XGA (1024 x 768)	
Brightness	3500 ANSI lumens	
Contrast Ratio	2600:1 (Full on/Full off)	
Aspect Ratio	4:3 Native (4 aspect ratio Selectable)	
Color	Full 16.7 million color palette	
Lens	F=2.56	
Zoom Ratio	Manual Zoom, 1.3:1	
Image Size (Diagonal)	25" to 300"	
Throw Ratio	1.51 to 1.96 (65"@2M)	
Lamp	280W, 3000/4000 hours (Normal/Economic mode)	
Computer Compatibility	VGA(640 x 480) to UXGA(1600 x 1200)	
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080p	
Video Compatibility	NTSC, PAL, SECAM	
Horizontal Frequency	31-93 kHz	
Vertical Scan Rate	48-86 Hz	
Input Terminals	PC	D-sub 15 pin x 2
	A/V	HDMI(v1.3) x 1
		S-Video: Mini Din 4 pin x 1 Composite Video: RCA x 1
Audio	Audio L/R x 2; Stereo mini jack x 1	
Output Terminal	PC	12V Trigger
		D-sub (15 pin) X 1
	Audio	Variable Audio Out: Stereo mini jack x1 5 Watt Speaker x 2
Control Terminal	LAN (RJ45); RS232 9 pin Type 1	
Dimensions(W x H x D)	11.4 x 3.7 x 9.9 inch (290 x 94 x 252 mm)	
Weight	7.7 lbs (3.5 kg)	
Power Supply	100 to 240 VAC, 50 to 60 Hz	
Power Consumption	Max 425W, Standby<1W	
Audible Noise	34/29 dB (Normal/Economic mode)	
On-Screen Display Languages	English/ French/ German/ Italian/ Spanish/ Russian/ Traditional Chinese/ Simplified Chinese/ Japanese/ Korean/ Swedish/ Dutch/ Turkish/ Czech/ Portuguese / Thai/ Polish	
	Application Modes	PC Input: Dynamic Mode Presentation Mode sRGB Mode Cinema Mode User 1 Mode User 2 Mode
A/V Input : Dynamic Mode Presentation Mode sRGB Mode Cinema Mode User 1 Mode User 2 Mode		
Other Functions	Digital Zoom (x2)	
	Freeze	
	Auto off	
	Blank	
Accessories (Standard)	Quick Start Guide	VGA cable
	Manual CD	Power cord
	Remote control w/Battery	Soft Carrying Case
Accessories (Optional)	Ceiling Mounting Kit	Spare Lamp Kit
	Presentation Plus	