



2300 Lumens



At 3.96 pounds the Casio Super Slim™ projector won't weigh you down.

Casio Super Slim projectors take the hassle out of travel so you can be the ultimate road warrior. At just under four pounds, it's lighter than most laptops so it won't weigh you down. At 1.7" thick its thin profile will make packing for travel a breeze...forget the extra bags, just stow it away in your briefcase.



Traveling with the Casio Super Slim couldn't be easier - whether you use your laptop, or the PC free option.

**2X
Power Zoom**

Short Throw Power Zoom and Focus Lens

Whether you are in a small office or a large boardroom the Super Slim's 2X power zoom lens gives you the flexibility to easily position the projector. Large screen projection is possible in any room and the short throw lens (1.4-2.8 throw ratio) can project an image from as close as 3' and up to 28' back. Image adjustment can be easily made from the remote control or an RS-232 control system.

RS-232 Control Connectivity

No more compromising. Casio's Super Slim projectors incorporate RS-232C control for easy system integration. The Super Slim's low profile and elegant design looks great in any Boardroom Conference or Classroom. Compatible with industry standard control systems (AMX, Crestron and Extron) the Super Slim projectors boast an available command set which includes Power On/Off, Input select and Lens Zoom and Focus.



Ceiling mount commercially available (sold separately).



RS-232 cable optional and sold separately.

Key Features:

- XGA (1024 x 768) Native Resolution, UXGA max
- DTV/HDTV - 480i/480P/720P/1080i/1080p
- DLP Display Technology from Texas Instruments
- 2X Power Zoom and Focus Short Throw lens

Includes:

- Built-in 1watt Speaker
- Remote Control
- Storage Case for Projector and Cables
- Cables for PC, Power and Video
- 3 years Parts and Labor Warranty (180 day warranty on lamp)



BASIC SPECIFICATIONS		
* Brightness (lumens)	Eco-Mode: OFF	2300 lumens
* Contrast ratio	Telephoto mode	1800:1
Lamp	High-pressure mercury lamp	210W
Estimated Lamp life		Up to 2,000 hours
Keystone correction	Auto	+30°
	Manual	±30°
Projection lens		2X Power Zoom and Focus
Projection screen size		15 ~ 300-inch
Projection range	60-inch screen	5.57 feet to 11.15 feet
	100-inch screen	9.18 feet to 18.37 feet
	Minimum	2.75 feet
	Projection ratio	1.4-2.8:1
Projection system		DLP® system
Display element	Device Type	0.55-inch DLP® chip
	Native Resolution	XGA (1024 x 768) 786,432 pixels
Computer Signal Compatibility	Maximum	UXGA (1600 x 1200) (Compressed)
	Resolutions	SVGA, XGA, WXGA, SXGA, SXGA+, WXGA+, WSXGA+, UXGA
Video Signal Compatibility	Hor./Vert. Frequency	fH 31.5-91.1 kHz / fV 56-85 Hz
	Video Systems	NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM
	DTV/HDTV	480i/480P/576i/576P/720P/1080i/1080p
Color reproduction		Full color (16.77 million colors)
Power source		AC100~240V, 50/60Hz
Power consumption	Operating	270W (Eco-Mode:220W)
Usage environment	Operating temperature	41-95° F (5~35°C)
	Operating humidity	20~80% (non-condensation)
	High Altitude Mode	Yes (for operation 5000 ft to 10000 ft above sea level)
INTERFACE TERMINALS		
RGB/Component Video Input		mini D-Sub 15 pin x 1 Also use as YcbCr/YPbPr input
Audio	Input	3.5mm mini-jack
	Output	1 W speaker 3.5mm mini-jack (shared with Audio Input)
Video	Input terminals	Composite: 3.5mm mini-jack (sharing audio terminal), YCbCr/YPbPr
Control	Terminal	RS-232C Adapter cable (YK-5) required and sold separately
	System Compatibility	AMX, Crestron, Extron and SP Controls
OTHERS		
Dimensions		10.63" x 7.83" x 1.69" Including projections (1.26" at thinnest point)
Weight		3.96 lbs.
Security compatibility	Kensington compatible	Yes
	Power ON password	Yes
Ceiling mount		Yes
Full Function IR Remote Control		Yes
Remote controller range		16.40 feet maximum
Included Accessories		Wireless remote controller (YT-35), RGB cable, AV cable, AC Power Cord, Projector Soft Case, Accessory Soft Case, Manual on CD-ROM
Optional Accessories		Replacement Lamp (Part # YL-3B) RS-232C adapter (Part # YK-5)
UPC Code	0-79767-18413-1	
Carton Dimensions	11.9" W x 7.4" H x 15.4" D	
Carton Weight	8.6 Lbs.	

* Compliant with ISO 2118-2005