

SUPER SLIM





2500 Lumens WXGA/HDMI

WXGA—The native WXGA (1280 X 800) resolution of the Super Slim projector allows for optimal viewing of content created and formatted for today's widescreen displays. Whether it is viewing a spreadsheet or two applications side by side, the WXGA Super Slim provides more useable screen area and

Get the Whole Picture with WIDE SCREEN





displays more information on the same screen. Widescreen display formats have become the standard and now your projector can match the widescreen display of Notebook PC's and HD Video sources.

HDMI[™]—An HDMI (High Definition Multimedia Interface) input provides a direct digital input and allows connectivity with many Widescreen Notebooks now shipping with HDMI outputs. Compatible with HD Video formats, HD Video sources including Blu-Ray players, cable converter boxes and gaming systems can be connected to the Super Slim projector.



Traveling with the Casio Super Slim couldn't be easier - whether you use your laptop, or the PC free option.

At 3.96 pounds the Casio Super Slim[™] projector won't weigh you down.

Casio Super Slim projectors take the hassle out of travel so you can be the ultimate road warrior. At just under four pounds, it's lighter than most laptops so it won't weigh you down. At 1.7" thick its thin profile will make packing for travel a breeze...forget the extra bags, just stow it away in your briefcase.



Short Throw Power Zoom and Focus Lens

Whether you are in a small office or a large boardroom the Super Slim's 2X power zoom lens gives you the flexibility to easily position the projector. Large screen projection is possible in any room and the short throw lens (1.15-2.30 throw ratio) can project an image from as close as 3' and up to 28' back. Image adjustment can be easily made from the remote control or an RS-232 control system.



Ceiling mount commercially available (sold separately).



RS-232 cable optional and sold separately.

Key Features:

- WXGA (1280 x 800) 16:10 Native Resolution, UXGA max
- HDMI input
- DTV/HDTV 480i/480P/720P/1080i/1080p
- DLP Display Technology from Texas Instruments
- 2X Power Zoom and Focus Short Throw lens

Includes:

- Built-in 1watt Speaker
- Remote Control
- Storage Case for Projector and Cables
- Cables for PC, Power and Video
- 3 years Parts and Labor Warranty (180 day warranty on lamp)



XJ-S43W

BASIC SPECIFICATIONS	
* Brightness(lumens)	2500 lumens
* Contrast ratio	1800:1
Lamp	210W
Estimated Lamp life	Up to 2,000 hours
Keystone correction	+30°
	±30°
Projection lens	2X Power Zoom and Focus
Projection screen size	18 ~ 300-inch
Projection range	4.59 feet to 9.18 feet
	7.87 feet to 15.74 feet
	2.75 feet
	1.15-2.30:1
Projection system	DLP® system
Display element	0.65-inch DLP® chip
	WXGA (1280 x 800) 1,024,000 pixels
Computer Signal	UXGA (1600 x 1200) (Compressed)
Compatibility	SVGA, XGA, SXGA, SXGA+, WXGA, WXGA+, WSXGA+, UXGA
Company	fH 31.5-91.1 kHz / fV 56-85 Hz
Video Signal	NTSC/PAL/PAL-N/PAL-M/PAL60/SECAM
Compatibility	480i/480P/576i/576P/720P/1080i/1080p
Color reproduction	Full color (16.77 million colors)
Power source	AC100~240V, 50/60Hz
Power consumption	270W (Eco-Mode:220W)
Usage environment	41-95° F (5~35°C)
	20~80% (non-condensation)
	Yes (for operation 5000 ft to 10000 ft above sea level)
INTERFACE TERMINALS	
RGB/Component	mini D-Sub 15 pin x 1
Video Input	Also use as YcbCr/YPbPr input
Audio	3.5mm mini-jack
	1 W speaker
	3.5mm mini-jack (shared with Audio Input)
Video	Composite: 3.5mm mini-jack
	(sharing audio terminal), YCbCr/YPbPr
Digital input	HDMI
Control	RS-232C
	Adapter cable (YK-5) required and sold separately
	AMX, Crestron, Extron and SP Controls
OTHERS	
Dimensions	10.63" x 7.83" x 1.69"
	Including projections (1.26" at thinnest point)
Weight	3.96 lbs.
Security compatibility	Yes
	Yes
Ceiling mount	Yes
Full Function IR Remote Control	Yes
Remote controller range	16.40 feet maximum
Included Accessories	Wireless remote controller (YT-35), RGB cable,
	AV cable, AC Power Cord, Projector Soft Case, Accessory Soft Case, Manual on CD-ROM
Optional Accessories	Replacement Lamp (Part # YL-4B) RS-232C adapter (Part # YK-5)
UPC Code	
UI C COUE	
Carton Dimensions	

* Compliant with ISO 2118-2005

D