



Key Features

- Truly portable - pocket-sized, lightweight and rechargeable
- VGA cable adapter included – connect to PCs and laptops to make an impact presentation on the go
- Stores up to 6000 pictures or 8 hours of video on 4GB of internal memory
- Project large images of up to 60" diagonal
- 2000:1 contrast ratio for detailed images
- LED light source lasts over 20,000 hours while producing excellent color



With the Optoma PK102 pocket projector, add pizzazz to your life with new ways to share content both cool and critical. Easily connects to your favorite personal media player and features 4GB of internal memory – enough to hold up to 6000 pictures or 8 hours of video. You can even display right from your laptop's VGA connection. Fitting in the palm of your hand, the truly portable, battery-operated PK102 is perfect for sharing photos, videos and other images wherever you go!

Detail Specifications

Display Technology DLP	Aspect Ratio 3:2 Native and 4:3 Compatible	XVID (M-JPEG, MPEG2, MPEG4, RMVB, RM, WMV, DivX Files are Converted Using Optoma Pico Video Encoder*)
Resolution Native HVGA (480 x 320)	Battery Li-ion Rechargeable (3.7V, 1100mAh)	Image File Compatibility JPEG, BMP
Maximum Resolution SVGA (800 x 600) through VGA Adapter	Battery Life Up to 1.5 Hours	User Controls Complete On-Screen Menu Adjustments in 10 Languages
Contrast Ratio 2000:1 (Full On/Full Off)	Displayable Colors 100% NTSC Color Gamut	I/O Connectors 18-pin Universal Port, 2.5mm Jack AV Input (Composite Video and Stereo Audio-In), DC Input Jack
Light Source LED (RGB) Estimated at 20,000 Hours	Audio One 0.5-Watt Speaker	Projection Method Front, Rear, Upright, Inverted
Throw Ratio 1.9:1 (Distance/Width)	Computer Compatibility SVGA, VGA, VESA, PC and Macintosh Compatible w/Included VGA Adapter	Weight 4.4 oz (124g) with battery 3.2 oz (90g) without battery
Projection Distance 10" to 102" (0.25 to 2.6m)	Video Input Compatibility NTSC, PAL, SDTV (480i), EDTV (480p w/Optional Component Video Adapter)	Dimensions (W x H x D) 2" x 0.67" x 4.17" (51 x 17 x 106mm)
Image Size (Diagonal) 6" to 60" (0.15 to 1.5m)	Video File Compatibility	Noise Level Silent (No Fans or Moving)

Operating Temperature

41° to 95°F (5° to 35°C)

Power Supply

AC Input 100-240V,
Auto-Switching, 50-60 Hz DC
Output 5V/2A

Power Consumption

6 Watts (Maximum Run from
Battery)

Standard Accessories

Power Adapter, Rechargeable
Li-ion Battery, Universal to Male
USB Cable, Standard A/V Cable
(RCA to Mini-Jack), Universal to
VGA Cable, Tripod Adapter,
Bag

Warranty

1 Year Limited Parts and Labor,
90 Days on Battery

UPC

796435 41 124 4