

EW531 DLP® Projector

3D-Ready in **HD**



120Hz 3D Ready, DLP® Link™ enabled



Widescreen presentations and HD entertainment



Bright projection - 2600 ANSI Lumens



3000:1 contrast ratio for sharp, detailed presentations and graphics



Digital and Analogue connectivity includes: HDMI, VGA



Environmentally friendly design <1W standby mode



Portable – carry bag provided for easy transportation



Low ownership costs - up to 4000hrs lamp life



DLP® filter-free design – virtually no maintenance





Widescreen 3D projection

The bright 2600L, EW531 with 120Hz 3D-Ready technology is ideally partnered with a widescreen notebook and HD sources. Ceiling mounted or mobile this dual-purpose projector multi-tasks in both office, school and home environments.

The environmentally friendly EW531 has energy saving features including <1W standby mode and auto power off saving you both time and money. Long lamp-life of 4000hrs combined with our unique Optoma Colour and Imager guarantees ensure hassle-free, long-lasting projection.

3D TECHNOLOGY

Using the inherent speed of DLP technology, The Optoma EW531 can output video and images at an astonishing rate of 120Hz, allowing you to show full screen, full colour, stereoscopic 3D.

The 3D effect is generated by splitting this signal into two standard video streams, one for each eye. Using DLP® LinkTM technology, the 3D glasses synchronise with the image on screen to filter each stream to the correct eye. Your brain then combines the two streams to make them jump into life.



TRUE WXGA RESOLOUTION

The EW531 is the perfect companion for widescreen laptops. Your presentations will appear as sharp and detailed as they do on your widescreen laptop in WXGA (1280 \times 800). WXGA resolution gives 30% more pixels than XGA.





XGA

WXGA

CONTROL

The extensive RS232 command set makes it simple and easy to control the EW531 with any control system.



AMX Compatibility – Dynamic Discovery Protocol is incorporated into the EW531. This feature allows for easy installation with AMX control systems.


TRUE HDMI

Project crystal clear images using the latest HDMI v1.3 input.

Hassle-free projection from a widescreen computer/HD source with a single HDMI cable – no need for separate audio cables.

CLEAR, FOCUSED IMAGES

DarkChip3™ technology from Texas Instruments produces a stunning 3000:1 contrast ratio for pin sharp graphics and crystal clear text. Crisper whites, ultra-rich blacks makes images come alive and text easier to read - ideal for business and education presentations.



1000:1 contrast ratio

3000:1 contrast ratio

‡Simulated Image

AMAZING COLOURS

The EW531 incorporates BrilliantColor™ technology to produce stunningly bright images with perfectly balanced life-like colours.

Preset display modes allow you to achieve a perfect image on a variety of surfaces including screens and interactive whiteboards.

COLOUR AND IMAGE PERFORMANCE

Optoma guarantees colour and image quality will remain as new for 5 years*

Once you've purchased the EW531, Optoma guarantees that the colour and image performance will not fade or degrade for 5 years.







VIRTUALLY MAINTENANCE FREE = LOWER TOTAL COST OF OWNERSHIP

In many cases, Optoma projectors ensure lower cost of ownership, longer life and improved reliability compared to various competing products. The filter-free projector design means no more regular filter cleaning or replacements, saving you time and money.



Enjoy big bright 3D images

ENVIROMENTALLY FRIENDLY

The EW531 incorporates energy saving features to conserve power and extend the lamp life:



The timer control functions can automatically switch the projector off to standby mode <1W, conserving power and extending the lamp life to an astonishing 4000 hours**.



It takes less than 10 seconds for the projector to power up and shutdown, so the EW531 not only saves time but energy too.

FEATURES

- 6 preset display modes
- Classroom mode 1500 ANSI Lumens
- Quick keystone correction
- Security bar and password protection for added security
- Easy to use remote with direct source control



EW531 SPECIFICATIONS

Native December	WIVO A 1000 000				
Native Resolution	WXGA 1280 x 800				
Compressed Resolution	up to UXGA (1600 x 1200)				
Brightness	2600/2100 Lumens (BRIGHT/STD mode)				
Contrast	3000:1				
Noise Level	28dB				
Lamp Life*	4000/3000 (STD/BRIGHT mode)				
Projection Lens	F/2.5 ~ 2.67, f=21.86 ~ 24.0mm, 1.1x Manual Zoom				
Throw Ratio	1.55 - 1.7:1 (Projection Distance:Image Width)				
Projection Distance	1.2 - 12m				
Image Size	0.83 - 9.13m (32.77" - 359.44") Diagonal 16:10				
Display Technology	Single 0.65" WXGA DC3 DMD chip DLP® Technology by Texas Instruments				
Weight / Dimensions (W x D x H)	2.3 kg / 286 x 192 x 84mm				
Remote Control	Full function remote with direct source selecting				
INPUTS	HDMI (HDCP) - audio supported (DVI-D via adaptor)				
0.0	15 Pin D-Sub VGA (SCART & Component via adaptor)				
	S-Video 4 Pin Mini Din				
	Composite RCA				
	3.5mm Audio Mini Jack				
CONTROL	RS232 3 Pin Mini DIN				
OUTPUTS	15 Pin D-Sub VGA (monitor loop-through)				
0011 010	3.5mm Audio Mini Jack				
Audio	1 x 2W Speaker				
Aspect Ratio	16:10 Native, 4:3 & 16:9 Compatible				
Keystone Correction	± 40° Vertical				
On Screen Display	18 Languages: English, German, French, Italian, Spanish,				
on ocicen bispiay	Portuguese, Polish, Dutch, Russian, Swedish, Greek,				
	Norwegian, Danish, Hungarian, Czech, Turkish, Farsi & Arabic				
Video Compatibility	PAL SECAM 576i/p, NTSC 480i/p, HD 720p/1080i/1080p				
Uniformity	85%				
Displayable Colours	16.7 Million				
Horizontal Scan Rate	15.3 – 91.1kHz				
Vertical Scan Rate	24 – 85Hz				
Power Supply	100 - 240V, 50 - 60Hz				
Power Consumption	233W BRIGHT mode < 1W Standby mode				
Tower consumption	207W STD mode < 1W Standby mode				
Operating Conditions	Operating: 5 - 35°C, 85% Humidity (Max),				
operating conditions	3000m Altitude (Max)				
Security	One Kensington Lock Port, Password Protection				
Standard Accessories	Lens Cover, AC Power Cord, VGA Cable, Carry Bag, Full				
otandaru Accessories	Function Remote, Batteries x 2, Quick Start Guide, CD				
	User Manual, Warranty, WEEE Card				
RoHS	Compliant				
Lamp Warranty	6 months or 1000 hours - whichever comes sooner				
Warranty	Warranty may vary by country. Please see				
waiiaiiiy					
	www.optomaeurope.com or ask your local				
Colour Cuaranta -*	supplier for details				
Colour Guarantee*	5 Years				
Imager Guarantee***	5 Years				

EASY TO USE REMOTE CONTROL

EW531 Remote Control

- 1 Vertical Keystone Correction
- 2 Volume Control
- 3 Brightness Adjustment
- 4 AV Mute
- 5 Direct Input Source Selection

EW531 Connections

- 6 VGA 1 SCART & Component
- 7 VGA Out
- 8 HDMI (audio supported)
- 9 S-Video
- 10 Composite Video
- 11 RS232 3 Pin
- 12 Audio In
- 13 Audio Out
- 14 Security Bar
- **15** Kensington™ Lock



Exceptional Connectivity/ Multiple Terminals



Easy to use remote with buttons to change the input sources



EW531 Projection Distance 1.2 - 12m (16:10 Aspect Ratio)									
Projection Distance (m)	Max. Horizontal Image Size (m)	Min. Horizontal Image Size (m)	Max. Vertical Image Size (m)	Min. Vertical Image Size (m)	Max Diagonal Image Size (m)	Max Diagonal Image Size (inch)	Max. Image Offset (m)		
1.20	0.77	0.71	0.48	0.44	0.91	35.94	0.06		
2.00	1.29	1.18	0.81	0.74	1.52	59.91	0.10		
2.50	1.61	1.47	1.01	0.92	1.90	74.88	0.13		
3.00	1.94	1.76	1.21	1.10	2.28	89.86	0.15		
4.00	2.58	2.35	1.61	1.47	3.04	119.81	0.20		
5.00	3.23	2.94	2.02	1.84	3.80	149.76	0.25		
6.00	3.87	3.53	2.42	2.21	4.56	179.72	0.30		
7.00	4.52	4.12	2.82	2.57	5.33	209.67	0.35		
8.00	5.16	4.71	3.23	2.94	6.09	239.62	0.40		
9.00	5.81	5.29	3.63	3.31	6.85	269.58	0.45		
10.00	6.45	5.88	4.03	3.68	7.61	299.53	0.50		
11.00	7.10	6.47	4.44	4.04	8.37	329.48	0.55		
12.00	7.74	7.06	4.84	4.41	9.13	359.44	0.60		

For guide purposes onl

EW531 is capable of 4:3 and 16:9 aspect ratio projection. When projecting a 4:3/16:9 image the image sizes, screen height and offset information will differ from the above.

Optoma Europe Ltd.

42 Caxton Way, Watford Business Park, Watford, Hertfordshire, UK. WD18 8QZ





