

# PJL7211

## BRIGHT PERFORMANCE PROJECTOR

WITH 3LCD TECHNOLOGY

## A Perfect Presentation.

The ViewSonic® PJL7211 is an advanced 3LCD projector that delivers 2200 lumens with a 1024 x 768 XGA native resolution. Designed for table-top use or ceiling mount, this projector is perfect for classrooms and meeting rooms. The top load lamp and bottom filter with slide design provide for easy maintenance. With 7 default picture modes (Normal, Cinema, Dynamic, Blackboard, Greenboard, Whiteboard and Daylight modes) to choose from depending on the projected source. Whisper mode extends the lamp life and drops the fan noise down to 30dB. For increased security, a PIN lock feature allows you to set a password to prevent unauthorized use and Kensington security lock port provides for theft deterrence.



### VERSATILE PERFORMANCE

- > **Great Connectivity**  
Supports 720p and 1080i with VGA and Composite inputs.
- > **Easy, cost-effective maintenance**  
The sliding filter cover and simple lamp replacement from the top of the unit make maintenance a breeze, even when the projector is mounted.
- > **Eco-mode for green savings**  
Automatically dims projector lamp, lowers power consumption to <5w, which extends lamp life up to 6000 hrs. and lowers noise.
- > **Enhanced security features**  
PIN lock feature prevents unauthorized use. Kensington® security lock and a security bar allow you to secure the projector to deter theft.
- > **Off-to-Go feature**  
This feature allows the busy presenter to simply unplug the projector and go without waiting for the usual cool down phase. This feature also protects lamp life from sudden power blackout.
- > **One of the best warranties in the business**  
Covered by a 3-year limited parts, 1-year lamp and first year free Express Exchange® service.
- > **The perfect image in any setting**  
Digital keystone correction, and optical zoom ensure the perfect image in any venue.



**VIEWSONIC**  
PRODUCTS, PROGRAMS,  
AND SERVICES



**ViewSonic®**   
See the difference®

# PJL7211

## BRIGHT PERFORMANCE PROJECTOR WITH 3LCD TECHNOLOGY



### Optional Accessories

- > Replacement Lamp..... RLC-054
- > Universal Ceiling Mount Kit..... WMK-005
- > Wireless G Presentation Gateway..... WPG-350
- > Extended Express Exchange® ..... PRJ-EE-08-03

Projection Distance		4:3 Screen Size	
M	Feet	M	Inches
1.4	4.6	1.0-1.3	40-50
1.7	5.6	1.3-1.5	50-60
2.4	7.9	1.8-2.1	70-83
3.5	11.5	2.5-3.0	100-120
4.5	14.8	3.3-4.0	130-157
6	19.7	4.4-5.4	173-213
8.8	28.9	6.4-7.6	250-300

<b>DISPLAY</b>	Type	0.63" (x3) Poly-Si TFT with Micro Lens
	Resolution	XGA 1024x768 (Native) / UXGA 1600x1200 (compressed)
	Lens	1.2x Manual optical zoom / Manual focus
	Keystone	Vertical digital keystone correction: +/- 30 degrees
	Size	30"-300" / 0.8m-7.6m
	Throw Distance	0.8m-10.4m / 2.62ft.-34.5ft.
	Throw Ratio	1.4:1-1.7:1
	Lamp	190 watt
	Lamp Life (Normal / Eco-mode)	3000 / 6000* hours
	Brightness	2,200 Lumens
Contrast Ratio	400:1 (typ)	
Aspect Ratio	4:3 (native)	
<b>INPUT SIGNAL</b>	Computer and Video	NTSC M (3.58MHz), 4.43MHz, PAL (B, D, G, H, I, M, N), SECAM, SD (480i/576i), ED (480p/576p), HD (720p/1080i)
	Frequency	Fh: 31-106KHz, Fv: 56-120Hz
<b>COMPATIBILITY</b>	PC	Analog: VGA to UXGA
	Mac®	Analog: Up to SXGA
<b>CONNECTOR</b>	RGB Input	15-pin mini D-sub
	Composite Input/Output	RCA jack
	Component	Share with RGB
<b>POWER</b>	Voltage	90-132 VAC/198-264 AC (Auto Switching), 50/60Hz (universal)
	Consumption	250W (typ) / <5W (stand-by mode)
<b>CONTROLS</b>	Basic	Power, keystone/arrow keys, left/blank, menu/exit, right/panel key lock, auto, mode/enter, source
	OSD	<b>Picture Menu:</b> Brightest, contrast, gamma, color temp, color tint, sharpness, My Memory <b>Image Menu:</b> Aspect, over scan, V. position, H. position, H. phase, H. size, auto adjust execute <b>Input Menu:</b> Progressive, video NR, color space, video format, frame lock, computer in, resolution <b>Setup Menu:</b> Keystone V., eco-mode, mirror <b>Screen Menu:</b> Language, menu position, blank, start up, My Screen, My Screen lock, message, source name <b>Option Menu:</b> Auto search, auto on, auto off, lamp time, filter time, My Button, service (fan speed, auto adjust, ghost, filter message, key lock, remote frequency, information, factory reset) <b>Security Menu:</b> Security password change, My Screen password change, PIN lock, My Text
<b>OPERATING CONDITIONS</b>	Temperature	41°F-95°F (5°C-35°C)
	Humidity	10%-85% (non-condensing)
	Altitude	0 to 6,000 ft (1,800m), operational up to 10,000 ft (3048m) at reduced reliability and performance
<b>NOISE LEVEL</b>	Normal / Eco-mode	37dB / 30dB
	<b>DIMENSIONS (W x H x D)</b>	Physical
<b>WEIGHT</b>	Packaging	17.7 x 7.9 x 14.7 (in) / 450 x 200 x 372 (mm)
	Net	7.3 lb. (3.3 kg)
<b>REGULATIONS</b>	Gross	14.0 lb. (6.4 kg)
	UL60950-1/C-UL, FCC part 15 Class B, CE approval: EN61000-3-2, EN61000-3-3, EN55022, EN55024 (EMC directive), EN60950-1 (low voltage directive); DEMKO-GS (Germany), WEEE, RoHS, C-Tick (AS/NZS CISPR22 Class B) (Australia/New Zealand)	
<b>PACKAGE CONTENTS</b>	Projector, power cable, RGB cable, remote control with batteries, lens cap, strap, Quick Start Guide, ViewSonic Wizard CD (with User Guide)	
<b>WARRANTY</b>	3-year limited warranty on parts, 1-year limited warranty on lamp, 1st year Express Exchange® service.	



ViewSonic Corporation's QMS & EMS have been registered to ISO 9001 & ISO 14001, respectively, by TUV NORD.

Sales: (888) 881-8781 . SalesInfo@ViewSonic.com . ViewSonic.com

\*Running eco-mode exclusively can extend lamp life. See ViewSonic.com for full Express Exchange details. Specifications subject to change without notice. Selection, offers and programs may vary by country; see your ViewSonic representative for complete details. Corporate names, trademarks stated herein are the property of their respective companies. Copyright © 2009 ViewSonic Corporation. All rights reserved [14550-00B-09/09] PJL7211-1

**ViewSonic®**  
See the difference® 

For more product information, visit us on the web at ViewSonic.com