


P1200i PROJECTOR

DLP® 3D Ready Hi definition wireless


P1200i DLP® 3D Ready wireless projector offers flexible connections, including WiFi wireless, Ethernet and conventional cables. Not only the capability of projection from a PC or a DVD player, furthermore, the world leading MobiShow technology even allows the projection from a WiFi smart phone.

Why P1200i Projector?

- DLP® 3D Ready Wireless 802.11b/g/n wireless technology
- Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
- Contrast Ratio 3700:1
- Brightness 2,600 ANSI Lumens (Standard), 2,080 ANSI Lumens (ECO)
- Projection Distance 3.3' (1.0m) ~ 32.0' (9.8m)



SmartFormat



SmartFormat

Technical Specifications

Model Name	P1200i DLP® 3D Ready
Resolution	Native XGA (1,024 x 768), Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	3700:1
Displayable Colours	1.07 Billion Colours
Brightness	2,600 ANSI Lumens (Standard), 2,080 ANSI Lumens (ECO)
Projection Lens	F = 2.41 ~ 2.55, f = 21.79mm ~ 23.99mm / 1:1.1 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	3.3' (1.0m) ~ 39.0' (11.9m)
Throw Ratio	50"@2m (1.95 ~ 2.15:1)
Horizontal Scan Rate	30 ~ 100 kHz
Vertical Scan Rate	50 ~ 120 Hz
Lamp type / Lamp Life	Osram 180 W user replaceable P-VIP lamp / 4,000 Hours (Standard), 5,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical)
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Ceiling Mounting Capability	Yes
Audio	One Internal Speaker with 2 watts Output
IR Remote Control	IR remote control with laser pointer & PgUp/PgDn functions
Digital Zoom	2X
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	255 Watts (Operation), 1 Watt (Standby)
Operating Temperature	5°C ~ 35°C / 41°F ~ 95°F
Noise Level	28 dBA (Standard mode), 25 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1, HDMI (Video, HDCP) x 1, PC Audio (Stereo mini jack) x 1, USB (Type A) x 2, USB (Mini B) x 1
Output Interface	Analog RGB (D-sub) x 1
Control Interface	USB (Type B) x 1, RS232 (Mini DIN) x 1
Wireless / Network Interface	802.11b/g/n wireless technology, Ethernet port (RJ45) x 1, Wireless antenna connector (SMA) x 1
Weight and Dimensions	5.4 lbs (2.46 Kg) / 269 x 206 x 84 mm (10.6" x 8.1" x 3.3")
Compliance	C-Tick (AS/NZS 60950)
Standard Accessories	AC power cord, VGA cable, Remote control, Battery x 2 for remote control, Detachable antenna x 1, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein; nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.