



PLV-Z800

- Full HD LCD panel (1920 x 1080 pixel)
- High brightness 1200 ANSI Lumens
- Built in variable iris with maximum contrast of 10000:1
- Ultra Quiet: 21dBA operating noise at Eco mode
- Vertical and Horizontal lens shift function and 2x wide angle zoom lens for highest flexibility
- 2 x HDMI, 2 x Component, 1 x Data inputs
- Automatic shutter protects the lens from dust
- 3 Year Warranty

PLV-Z800

TECHNICAL DETAILS

Category	PLV-Z800 Home Cinema
Panel	3 x 0.74" TFT p-Si (16:9)
Lamp	165 W
Brightness ANSI lumens	1200
Lamp Service Life	3000h (Eco Mode), 2000h (Normal Mode)
Fan Noise	21dBA
Standard Lens	F=2.0 - 3.0 / f=22.3 - 45.3mm
Throw Distance Ratio	1.36 - 2.76:1
Throw Distance	1.2m – 18.4m
Contrast Ratio	10,000:1
Resolution in pixels	1920 x 1080
Image size min–max (diagonal)	40" - 300"
Uniformity	85%
Bandwidth/Frequency	100MHz, Horizontal 15-80kHz, Vertical 50Hz-100Hz
Colour Systems	PAL / NTSC / SECAM / NTSC4.43 / PAL-M / PAL-N
Connections	Input 1: HDMI Input 2: HDMI Input 3: 3 x RCA (Y-Pb/Cb-Pr/Cr) Input 4: 3 x RCA (Y-Pb/Cb-Pr/Cr) Input 5: Dsub-15 Input 6: RCA (composite) Input 7: S-Video Control: Mini DIN 8 pin
Keystone Correction	No
Lens-Shift	Manual Vertical -100%~+100% Horizontal -50%~ +50%
HDTV Signals	1080p, 1080i/50, 1080i/60,1035i,720p
Computer Compatibility	UXGA / WXGA / SXGA+ / SXGA / XGA / SVGA / VGA / MAC
Zoom/Focus	2 x / Manual Focusing
Power Consumption/Voltage	182 w (Eco Mode), 236 w (Normal Mode), 0.6 w (Standby Mode)
Warranty	3 Year
Dimensions (W x H x D)	400 x 154 x 346mm
Weight	7.5Kg
Standard Accessories	Remote Control, Power Cable, Owners Manual (CD ROM)
Optional Accessories	Scart-VGA cable (POA-CA-SCART)

* You can use the distance calculator at www.uk.sanyo.com to determine exact image sizes and distances



Technical specifications subject to change without notice. Status 04.2010

Telephone: 01923 246363

Email: info@sanyo.co.uk

Visit: www.uk.sanyo.com

