

X1230PS PROJECTOR

Short Throw Projection

The Acer X1230PS gives you the benefits of short-throw projection, enhancing flexibility and providing greater viewing comfort without sacrificing image precision. Packed with advanced features in a sleek, attractive design, the Acer X1230PS delivers excellent performance for different viewing scenarios and environments.

Display clear, large images up to 109 inches diagonal even while positioned as close as 2 meters from the screen. The short-throw distance maximizes space, as a long projection distance is no longer required. Viewing is also safer and more comfortable: presenters don't need to avoid harmful beams, and the audience won't experience heat released through the projector's vents. The Acer X1230PS features Acer ColorBoost II technology, XGA resolution, 2500 ANSI Lumens brightness and a 3000:1 contrast ratio for brilliant colors, clear details and lifelike images.

Why X1230PS Projector?

- Short Throw projection
- Resolution XGA (1,024 x 768),
Maximum UXGA (1,600 x 1,200),
1080p (1,920 x 1,080)
- Contrast Ratio 3000:1
- 2,500 ANSI Lumens (Standard),
2,000 ANSI Lumens (ECO)
- Projection Distance 1.6' (0.5m) ~ 18.0'
(5.5m)



SmartFormat

Technical Specifications

Model Name	X1230PS
Resolution	Native XGA (1,024 x 768) Maximum UXGA (1,600 x 1,200), 1080p (1,920 x 1,080)
Computer Compatibility	IBM PC and Compatibles, Apple iMac/MacBook, and VESA Standards 1080p (1,920x1,080), WSXGA+ (1,680 x 1,050), WXGA+ (1,440 x 900), WXGA (1,280 x 800, 1,280 x 768), UXGA (1,600 x 1,200), SXGA+ (1,400 x 1,050), SXGA (1,280 x 1,024), XGA (1,024 x 768), SVGA (800 x 600), VGA (640 x 480)
Video Compatibility	NTSC (3.58/4.43), PAL (B/D/G/H/I/M/N), SECAM (B/D/G/K/K1/L), HDTV (720p, 1080i, 1080p), EDTV (480p, 576p), SDTV (480i, 576i)
Aspect Ratio	4:3 (Native), 16:9
Contrast Ratio	3000:1
Displayable Colours	1.07 Billion Colours
Brightness	2,500 ANSI Lumens (Standard), 2,000 ANSI Lumens (ECO)
Projection Lens	F = 2.6 ~ 2.78, f = 10.20mm ~ 12.24mm 1:1.2 Manual Zoom and Manual Focus
Projection Screen Size	23" (58cm) ~ 300" (762cm)
Projection Distance	1.6' (0.5m) ~ 18.0' (5.5m)
Throw Ratio	109"@2m (0.90:1)
Horizontal / Vertical Scan Rate	30k ~ 100k Hz / 50 ~ 120 Hz
Lamp Type / Life	Philips 189 W user replaceable UHP lamp / 3,000 Hours (Standard), 4,000 Hours (ECO)
Keystone Correction	+/-40 Degrees (Vertical), Manual & Auto
Projection Mode	Front, Rear, Front-Ceiling, Rear-Ceiling
Audio	One Internal Speaker with 2 watts Output
IR Remote Control	IR remote control with mouse & PgUp/PgDn functions
Digital Zoom	2X
Power Supply	AC input 100~240V auto-switching power supply
Power Consumption	280 Watts (Operation), <5 Watts (Standby)
Operating Temperature	0°C ~ 40°C / 32°F ~ 104°F
Noise Level	33 dBA (Standard mode), 28 dBA (ECO mode)
Input Interface	Analog RGB/Component Video (D-sub) x 1, Composite Video (RCA) x 1, S-Video (Mini DIN) x1 PC Audio (Stereo mini jack) x 1
Output Interface	Analog RGB (D-sub) x 1
Control Interface	USB (Mini B) x 1, RS232 (Mini DIN) x 1
Weight and Dimensions	5.07 lbs (2.3 Kg) / 264 x 225 x 95 mm (10.4" x 8.6" x 3.7")
Compliance	C-Tick (AS/NZS 60950)
Standard Accessories	AC power cord, VGA cable, Composite video cable, Remote control, Battery for remote control, Lens cap, Carrying case, User's guide (CD-ROM), Quick start guide, Security card
Standard Warranty	2 year return to base

Product specifications are subject to change without prior notice. Acer & the Acer logo are registered trademarks of Acer Inc., and Acer America Corp. All other products, brand names, or company names are trademarks & registered trademarks of their respective companies. Acer shall not be liable for technical, editorial or pictorial errors, inaccuracies or omissions contained herein, nor for any consequential damage resulting from the furnishing, performance, or use of this material. * Maximum hours. Actual hours depend on usage and configuration. ** Contact Acer for warranty details.