



EPSON PowerLite® 810p

Powerful performance, value beyond compare

Get ready for 2000 lumens of brightness, XGA resolution, and a remarkable combination of features you won't find in competitive projectors. Available at an extraordinary value, the EPSON PowerLite 810p was engineered to deliver maximum power and flexibility.

Designed by the world leader in high performance projectors, this whisper-quiet portable offers striking color saturation across the screen. With its three EPSON 0.9" high-aperture LCDs, you get brightness and image quality that's sure to exceed your expectations.

But, that's not all you get with this versatile, 9.3 lb product. You get many new and unique features, without the need for costly expansion modules. Horizontal keystone correction provides additional positioning flexibility, while its conveniently placed lamp access enables easy changes, even when ceiling mounted. EPSON ColorReality™ color processing technology provides six selectable projection modes that no one else offers, including sRGB, which offers repeatable color from creation to projection.

A worldwide company known for unbeatable service and support, Epson also delivers unprecedented reliability, so you can be confident you won't be left in the dark. And, it's all available at a value that's hard to beat!

Superior Image Quality and Performance

- Unbelievable 2000 lumens in a 9.3 lb projector
- XGA (1024 x 768) resolution for sharp, vivid detail
- Three EPSON 0.9" high aperture LCDs for rich color saturation across the screen
- 400:1 contrast ratio for blacker blacks and whiter whites
- New EPSON ColorReality color processing technology provides 6 user-selectable modes for maximum flexibility, which presenters can choose from based on their presentation materials or environment. The modes are: sRGB, normal, meeting, presentation, theater and amusement

Powerful Feature Set


- No costly expansion modules necessary; complete set of computer and video connections included as standard
- Horizontal and vertical keystone correction (30° vertical, 10° horizontal)
- Quiet operation (38db) to eliminate excessive sound during presentations
- Multiple inputs and outputs, including component and DVI inputs (compatible with digital and analog signals)
- 5 watt audio so there's no additional audio expense

Reliable and Easy to Use

- 1.35x optical zoom ratio—position the projector closer to the screen for unobtrusive operation
- Full-featured remote control with easy-to-use page-up and page-down presentation control
- Conveniently placed lamp access on top of the projectors, designed for easy changes, even when the projector is ceiling-mounted
- Intuitive menu functions
- Start Here Kit gets first time users projecting in just minutes
- EPSON PrivateLine™ toll-free technical support, available from 6 a.m. to 6 p.m. PST Monday through Friday. Calls are typically answered within 45 seconds



Front View



Back View

EPSON PowerLite 810p Specifications

Projection System	EPSON original LCD prism technology	
Projection Method	Front/rear/ceiling mount	
LCD		
Size	0.9"	
Driving Method	EPSON Poly-Silicon TFT Active Matrix	
Pixel Number	786,432 dots (1024 x 768) x 3	
Native Resolution	XGA	
Aspect Ratio	4:3 (supports 16:9, 5:4)	
Pixel Arrangement	Stripe	
Projection Lens		
Type	Manual: zoom/focus	
F-number	1.74 to 2.06	
f-number	28.3mm to 37.98mm	
Zoom ratio	1:1.35	
Lamp		
Type	200W UHE	
Life (typical)	1500H (can last about 5 yrs. based on 6 hours/week x 50 weeks/year)	
Screen Width Ratio: (distance/width)	1.5 to 1.97:1	
Screen Size (projected distance)	30" to 300" (0.87m to 12.48m)	
Keystone Correction	Vertical: +/- 30 degrees, Horizontal: +/-10 degrees	
Brightness (typical)	2000 ANSI lumens	
Contrast Ratio	400:1	
Brightness Uniformity (typical)	85%	
Color Reproduction	24 bit; 16.7ml	
Sound Output	5W	
Operating Temperature	5°C to 35°C (41°F to 95°F)	
Power Supply Voltage	100-120V, 200-240V +/-10%, 50/60Hz AC	
Power Consumption	280W (5.5W at stand by mode)	
Maximum Dimensions D x W x H (include lens and feet)	10.87" x 13.75" x 4.5"	
Dimensions D x W x H (exclude lens and feet)	10.79" x 13.71" x 4.1"	
Weight	9.3 lbs/4.2kg	
Fan Noise	38db	
Effective Scanning Frequency Range		
Pixel Clock	14MHz to 230MHz	
Horizontal	15KHz to 107KHz	
Vertical	43Hz to 120Hz	
Remote Control Features		
Keystone (horizontal & vertical), Picture in Picture, special effects, source selection, power, resize, right/left mouse click, volume, presets		
RGB		
	Analog RGB I/O	Digital RGB Input
Display performance		
Native	1024 x 768	1024 x 768
Resize	1600 x 1200 1280 x 1024 800 x 600 640 x 480	1280 x 1024 800 x 600 640 x 480
Input terminal		
Video	Mini D-sub 15pin DVI Type I	DVI Type I
Audio	Stereo mini jack RCA x2	Stereo mini jack
Output terminal		
Video	Mini D-sub 15pin	

Video I/O	
Display performance	NTSC: 550 line, PAL: 550 line (Depend on observation of multi burst pattern)
Input signal	NTSC/NTSC4.43/PAL/M-PAL/ N-PAL/PAL60/SECAM
Input terminal	
Video	Composite Video: RCA x 1 S-Video: Mini DIN Video RGB: Mini D-sub 15pin Component Video: Mini D-sub 15pin
Audio	RCA x 2 (for composite video/S-video/ component video) Stereo mini jack (for video RGB)

Control I/O	
Mouse/USB I/O	Mini DIN 9pin (for PS/2 mouse) USB connector series A (for Hub) USB connector series B (for mouse, keyboard, audio control)
Serial I/O	Mini D-sub 9pin RS-232C
Input Terminal	Stereo mini jack (for remote control)

Security	Kensington®-style lock provision
-----------------	----------------------------------

Warranty
Standard two year limited warranty, international warranty, 90-day lamp warranty, EPSON Road Service Program and EPSON PrivateLine dedicated toll-free support (U.S. and Canada only)

Supplied Accessories
Power cord, RCA video/audio cable, remote control, 2 batteries, computer cable HD15/HD15, PS/2 mouse cable, USB mouse cable, Start Here kit

Product/Accessory Part Numbers	
EPSON PowerLite 810p projector	V11H047020
Replacement lamp	V13H010L15
Soft shoulder bag	ELPKS13
ATA shipping case	ELPKS41
ATA molded hardshell case	ELPKS40
Samsonite wheeled soft case	ELPKS35
Digital video cables	
DVI cable DVI to DVI, 3 meter	ELPKC20
DVI cable DVI to DFP, 3 meter	ELPKC21
DVI analog cable	V12H005C25
Component video cable	ELPKC19
Ceiling mount	ELPMB36
Mac adapter set	ELPAP01
Remote control receiver	ELPST02
Remote control receiver kit	ELPST04
Portable screens	
50" portable screen	ELPSC06
60" insta-theatre screen	ELPSC07
80" insta-theatre screen	ELPSC08
Wireless microphone system	ELPCVS1
Presentation audio system	ELPPAS1
Kensington security lock	ELPSL01
High resolution document imager	ELPDC02
Motion presentation camera	ELPDC03

Support-The Epson ConnectionSM
Pre-Sales Support U.S. and Canada 800-463-7766
Automated Technical Support 800-922-8911
www.epson.com
Presenters ONLINESM
presenteronline.com



Epson America, Inc.
3840 Kilroy Airport Way, Long Beach, CA 90806
Epson Canada, Ltd.
550 McNicoll, Willowdale, Ontario M2H 2E1
Epson Latin America
6303 Blue Lagoon Drive, Miami, FL 33126

Specifications and terms are subject to change without notice. EPSON is a registered trademark and EPSON ColorReality is a trademark of Seiko Epson Corporation. PowerLite is a registered trademark, SizeWise is a trademark and Epson Connection, PrivateLine and Presenters Online are service marks of Epson America, Inc. All other product and brand names are trademarks and/or registered trademarks of their respective companies. Epson disclaims any and all rights in these marks. © Copyright 2001 Epson America, Inc. CPD-12626 50K 8/01 CG Printed on Recycled Paper