


## Superior Visual Performance for Demanding Applications



The Optoma TX779 DLP projector is exceptionally bright at 4500 lumens to provide outstanding video and data display in large rooms and in rooms with high ambient light. Remotely monitor, manage and control the Optoma TX779 over the network via the integrated RJ45 Crestron RoomView® user-friendly interface. The environment-friendly TX779 has energy saving features including <1 watt standby mode, saving you money in the long run.

3D content can be viewed with active LCD shutter glasses when the projector is connected to a computer with a compatible 3D graphics card. Please visit [www.optoma.com](http://www.optoma.com) for more information.

### TX779 FEATURES


- ❑ Bright at 4500 ANSI lumens with high contrast ratio of 3000:1 (full on/off)
- ❑ Crestron RoomView® for projector management and control via RJ45 connection
- ❑ Presentation-friendly IR remote with USB mouse function and laser pointer
- ❑ Environment-friendly design - consumes <1 watt in standby mode
- ❑ Built-in closed captioning

# TX779 | Multimedia Projector

## Projection Distance/Image Size

Projection Distance (Feet)	Maximum Diagonal (Inches)	Minimum Diagonal (Inches)
6	50	43
8	67	57
10	83	71
12	100	86
14	117	100
16	133	114
18	150	129

## Control Panel



## Optional Accessories

Lamp:	BL-FP280E
Mount:	BM-5001U
Wireless Module:	BI-EXTGB
Remote:	BR-5033L
Carrying Case:	BK-4013
HDMI Cable (7.5m):	BC-DDHMX08
HDMI Cable (5m):	BC-HMHMX05
Component to VGA Adapter:	BC-CRVGYX00
Component Cable (2m):	BC-CRCRXX02
Composite Cable (2m):	BC-COCOXX02
100" 4:3 Manual Pull-Down Screen:	DS-3100PMG+
Power Cord (11m):	BC-PUPIX11

## Specifications

Display Technology:	Single 0.7" DC3 DMD DLP® Technology by Texas Instruments
Native Resolution:	XGA (1024 x 768)
Brightness (Typical):	4500 ANSI Lumens
Contrast Ratio:	3000:1 (Full On/Full Off)
Lamp Type:	280W P-VIP
Lamp Life (STD/Bright)*:	Estimated at 3000/2000 Hours
Throw Ratio:	1.8 to 2.1:1 (Distance/Width)
Image Size (Diagonal):	23.4" to 300" (0.59 to 7.62 m)
Projection Distance:	3.28' to 32.8' (1.0 to 10 m)
Noise Level (STD/Bright):	28dB/30dB
Remote Control:	IR Remote Mouse with Laser Pointer
Computer Compatibility:	HD, UXGA, WXGA, SXGA+, SXGA, XGA, SVGA, VGA Resized, VESA, PC and Macintosh Compatible
Video Compatibility:	NTSC, PAL, SECAM, SDTV (480i), EDTV (480p), HDTV (720p, 1080i/p)
3D Compatibility:	120Hz Frame Sequential 3D for Resolutions Up to 720p, 60Hz Field Sequential 3D for Resolutions Up to 480i
Aspect Ratio:	4:3 Native, 16:9 Compatible
Projection Lens:	F=2.6-2.81, f=26.9-29.8 mm, 1.15x Zoom & Focus
Offset:	112%
Monitor Loop Through:	D-Sub 15-Pin VGA Output (Functional in Both Normal and Standby Modes)
Audio:	3-Watt Speaker
Keystone Correction:	± 30° Vertical
Vertical Refresh Rate:	50 to 85 Hz
Horizontal Scan Rate:	15, 31 - 90 KHz
Power Supply:	AC Input 100-240V, 50-60 Hz, Auto-Switching
Power Consumption:	360 Watts Max (Bright), 290 Watts (STD) <1 Watt (Standby)
Weight:	7.8 lbs (3.53 kg)
Dimensions (W x H x D):	12.8" x 4.29" x 10.19" (326 x 109 x 259 mm)
Operating Temperature:	41° to 104°F (5° to 40°C), 85% Max Humidity, Adjustable Fan Speed for High Altitude Application
Displayable Colors:	1.07 Billion
Projection Method:	Front, Rear, Ceiling Mount, Table Top
Uniformity:	85%
Security:	Kensington® Lock and Keypad Lock
I/O Connectors:	HDMI, Two VGA-In, VGA-Out, DVI-D, S-Video, Composite Video, Stereo RCA Audio-In, Stereo Audio-In, Stereo Audio-Out, +12V Trigger, USB, RS-232 and RJ45
Standard Accessories:	AC Power Cord, VGA to VGA Cable, Remote Control, Batteries for Remote, Carrying Case, Lens Cap, Multilingual CD-ROM User's Manual, Quick Start Card and Warranty Card
Optional Accessories:	HDMI Cable, Ceiling Mount, VGA to Component Cable, S-Video Cable, Composite Video Cable, RS-232 Cable and Panoview™ Series Screens
Warranty:	Three Years Optoma Express Replacement Service, One Year on Lamp
UPC:	796435 11 271 4

www.optoma.com

\*Lamp life is dependent upon many factors, including lamp mode, display mode, usage, environmental conditions and more. Lamp brightness can decrease over time.

**Optoma**



All Specifications are subject to change without notice. ©2010 Optoma Technology, Inc. DLP® and the DLP logo are registered trademarks of Texas Instruments. All other names mentioned herein are property of their respective owners.