

Panasonic

ideas for life

Preliminary as of April 2010

LCD Projectors
PT-LB2/LB1
PT-ST10



Durable Multi Purpose Projector with Compact Body For All Kinds of Uses - From Education to Business

Light and Compact Portable Type

- The compact body is the size of an A4 file and weighs only about 2.3 kg.

PT-LB2 **2600 lm** **XGA**

PT-LB1 **2200 lm** **XGA**

The PT-LB2/LB1 are scheduled for release in early summer 2010.



Short Throw Type for Close-Range Projection

- Projects large, 80-inch images with a throw distance of only 82 cm.
- Reduces shadows on the screen.

PT-ST10 **2500 lm** **XGA**

The PT-ST10 is scheduled for release in summer 2010.

High Basic Performance

- The **Intelligent Power Management** function lets you use the projector even in places with unstable electrical power.

- The **Daylight View Basic** function ensures clear images even in brightly lit rooms.

- **Low standby power consumption of 0.4 W*** helps the environment.

Easy System Upgrading

- The projector comes with a **wired LAN terminal** and **Multi Projector Monitoring and Control software** that lets you monitor and operate multiple Panasonic projectors from a computer.

- **Top-panel lamp replacement and side air filter replacement** simplify maintenance even for a ceiling-mounted projector.

- **Optional air filter unit ET-KFB2** for use in dusty environment.

- **Various interfaces** allow use with a wide range of systems.

Special Convenient Functions

- With **Speed Start**, the image appears in a few seconds*2 after you press the power button.

- The **Start-Up Logo** function displays any desired logo as soon as projection begins.

- **Whiteboard and Blackboard modes** are convenient when projecting in rooms that don't have a screen.

- The **Direct Power-Off** function lets you immediately pull the plug from the power outlet when you are finished using the projector.

Specifications

Models		PT-LB2		PT-LB1		PT-ST10	
Power supply		100-240 V AC, 50/60 Hz					
Power consumption		300W (0.4 W ^{*1} in eco standby mode. 15 W in normal standby mode. 18 W in normal standby mode when set to audio monitor out and with fan stopped.)					
Optical system		Dichroic mirror separation/prism synthesis system					
LCD panel	Panel size	16 mm (0.63") diagonal, 4:3 aspect ratio					
	Display method	Transparent LCD panel (x 3, R/G/B)					
	Drive method	Active matrix					
	Pixels	786,432 pixels ((1,024 x 768) x 3 panels)					
Lens		Manual zoom (1:1-1:1.2), manual focus, F 1.65-1.93, f 18.53-22.18 mm		Manual zoom (1:1-1:1.2), manual focus, F 2.00-2.20, f 19.22-22.68 mm		Fixed, manual focus, F 1.80, f 6.74 mm	
Lamp		220 W UHM lamp					
Screen size		33-300 inches (4:3 aspect ratio)				60-110 inches (4:3 aspect ratio)	
Brightness		2,600 lumens ^{*2}		2,200 lumens ^{*2}		2,500 lumens ^{*2}	
Center-to-corner uniformity		85% ^{*2}					
Contrast		500:1 (full on/full off) ^{*2}					
Resolution		1,024 x 768 ^{*3}					
Scanning frequency	RGB	Horizontal: 15-91 kHz, Vertical: 50-85 Hz					
	YPaPs/YCaCs	480i(525i): fh 15.75 kHz; fv 60 Hz 576i(625i): fh 15.63 kHz; fv 50 Hz	480p(525p): fh 31.50 kHz; fv 60 Hz 576p(625p): fh 31.25 kHz; fv 50 Hz	720p(750p): fh 45.00 kHz; fv 60 Hz 720p(750p): fh 37.50 kHz; fv 50 Hz	1080i(1125i): fh 33.75 kHz; fv 60 Hz 1080i(1125i): fh 28.13 kHz; fv 50 Hz		
	S-Video/Video	NTSC, NTSC4.43, PAL-M, PAL60: fh 15.75 kHz; fv 60 Hz PAL, SECAM, PAL-N: fh 15.63 kHz; fv 50 Hz					
Optical axis shift		5:1 (fixed)				10:-0.5 (fixed)	
Installation		Front/rear ceiling/desk (menu selection)					
Built-in speaker		4cm-2cm (oval) x 1					
Terminals	COMPUTER 1 IN	D-sub HD 15-pin x 1 (RGB/YPaPs/YCaCs x 1)					
	COMPUTER 2 IN	D-sub HD 15-pin x 1 (RGB/YPaPs/YCaCs x 1)					
	VIDEO IN	RCA pin x 1 (Composite video x 1)					
	S-VIDEO IN	Mini DIN 4-pin x 1 (S-Video x 1)					
	AUDIO IN	M3 x 2 (L-R x 2)					
	VARIABLE AUDIO OUT	M3 x 1 (L-R x 1)					
	SERIAL	D-sub 9-pin x 1 (RS-232C)					
	LAN	RJ-45 x 1, compatible with PjLink™ (class 1), 10BASE-T/100BASE-TX					
Cabinet material		Moulded plastic (PC+ABS)					
Dimensions (W x H x D)		307 x 69 x 210 mm (12" x 2-5/7" x 8-1/14") ^{*4}				327 x 135 x 307 mm (12-7/8" x 5-5/16" x 12") ^{*4}	
Weight		Approx. 2.3 kg (5.07 lbs.) ^{*5}				Less than 3 kg (Less than 6.6 lb.) ^{*5}	
Operation environment		Temperature: 0°-40°C ^{*6} (32°-104°F), Humidity: 20%-80% (no condensation)					
Supplied accessories		Power cord, power cord secure lock, wireless remote control, batteries for remote control (AAA type x2 for North/South America, R03 type x2 for Europe/Asia), VGA cable, carrying bag, Application software (CD-ROM)				Power cord, power cord secure lock, wireless remote control, batteries for remote control (AAA type x2 for North/South America, R03 type x2 for Europe/Asia), VGA cable, Application software (CD-ROM)	

*1: In eco standby mode, network functions such as Standby On via LAN are not available, and only certain commands can be received from RS-232C control.

*2: Measurement, measuring conditions, and method of notation all comply with ISO 21118 international standards. *3: Input signals that exceed this resolution will be converted to 1,024 x 768 pixels. *4: Protruding parts not included. *5: Average value.

*6: The operating temperature range is 0°C (32°F) to 35°C (95°F) when used in High-Altitude mode (1,400 to 2,700 m (4,593 to 8,858 feet)). Also, in Lamp Normal mode, if the ambient temperature exceeds 35°C/95°F (30°C/85°F in High-Altitude mode), the light output may be reduced approximately 30% to protect the projector.

Projection Distance

PT-LB2/LB1 (Screen aspect ratio = 4:3)

Project size (diagonal)	[PT-LB2] Projection distance (L)		[PT-LB1] Projection distance (L)		Height from the edge of screen to center of lens (H)
	Min (wide)	Max (telephoto)	Min (wide)	Max (telephoto)	
0.84 m (33")	-	1.1 m (3.6')	-	1.1 m (3.6')	0.08 m (0.26')
1.02 m (40")	1.1 m (3.6')	1.4 m (4.6')	1.2 m (3.9')	1.4 m (4.6')	0.10 m (0.32')
1.27 m (50")	1.4 m (4.6')	1.7 m (5.6')	1.5 m (4.9')	1.8 m (5.9')	0.13 m (0.43')
1.52 m (60")	1.7 m (5.6')	2.1 m (6.9')	1.8 m (5.9')	2.1 m (6.9')	0.15 m (0.49')
1.78 m (70")	2.0 m (6.6')	2.4 m (7.9')	2.1 m (6.9')	2.5 m (8.2')	0.18 m (0.59')
2.03 m (80")	2.3 m (7.5')	2.8 m (9.2')	2.4 m (7.9')	2.8 m (9.2')	0.20 m (0.66')
2.29 m (90")	2.6 m (8.5')	3.1 m (10.1')	2.7 m (8.8')	3.2 m (10.5')	0.23 m (0.75')
2.54 m (100")	2.9 m (9.5')	3.5 m (11.5')	3.0 m (9.8')	3.5 m (11.5')	0.25 m (0.82')
3.05 m (120")	3.5 m (11.5')	4.2 m (13.8')	3.6 m (11.8')	4.3 m (14.1')	0.30 m (0.98')
3.81 m (150")	4.4 m (14.4')	5.2 m (17.1')	4.5 m (14.8')	5.3 m (17.4')	0.38 m (1.25')
5.08 m (200")	5.8 m (19.0')	7.0 m (23.0')	6.0 m (19.7')	7.1 m (23.3')	0.51 m (1.67')
6.35 m (250")	7.3 m (24.0')	8.7 m (28.5')	7.5 m (24.6')	8.9 m (29.2')	0.64 m (2.10')
7.62 m (300")	8.7 m (28.5')	10.5 m (34.4')	9.0 m (29.5')	10.7 m (35.1')	0.76 m (2.49')

PT-ST10 (Screen aspect ratio = 4:3)

Project size (diagonal)	Projection distance (L)	Height from the edge of screen to center of lens (H)
1.52 m (60")	0.60 m (1.97')	-0.05 m (-0.16')
1.78 m (70")	0.71 m (2.33')	-0.05 m (-0.16')
2.03 m (80")	0.82 m (2.69')	-0.06 m (-0.20')
2.29 m (90")	0.92 m (3.02')	-0.07 m (-0.23')
2.54 m (100")	1.03 m (3.38')	-0.08 m (-0.26')
2.79 m (110")	1.14 m (3.74')	-0.08 m (-0.26')

Optional Accessories

Air filter unit: ET-KFB2

Replacement filter for ET-KFB2: ET-RFB2

Replacement lamp unit: ET-LAB2

Ceiling mount bracket: ET-PKB2

NOTES ON USE

- The projector uses a high-voltage mercury lamp that contains high internal pressure. This lamp may break, emitting a large sound, or fail to illuminate, due to impact or extended use. The length of time that it takes for the lamp to break or fail to illuminate varies greatly depending on individual lamp characteristics and usage conditions.
- The brightness of the lamp will gradually decrease with use.
- The projector includes consumable parts. The frequency of replacement for the lamp and other consumable parts will increase if the projector is subjected to extended, continuous use. For details, please consult a service representative.

Panasonic®



JQA-0443



Factories of Systems Business Group have received ISO14001:2004 - the Environmental Management System certification. (Except for 3rd party's peripherals.)

Weights and dimensions shown are approximate. Specifications are subject to change without notice. This product may be subject to export regulations. An application has been filed for trademark rights, or trademark rights have been granted, for PjLink in Japan, United States of America and other countries and area. XGA is trademark of International Business Machines Corporation. All other trademarks are the property of their respective trademark owners. Projection Images simulated. © 2010 Panasonic Corporation All rights reserved.

All information included here is valid as of April 2010.

PT-LB2PRE1 Printed in Japan.