

MULTIMEDIA
PROJECTOR

MW512



Features

- Native WXGA (1280 x 800) Resolution
- 2800 ANSI Lumens, 4000:1 Contrast Ratio
- HDMI x1, Variable Audio Out
- 3D-Ready, Digital Zoom (x2)
- Quick Cooling, Closed Captioning

Side / Front-Left



Front-Right



Front-Left

Input and Output Terminals

Back



- | | |
|-----------------------|-----------------|
| 1 RGB In/Component x2 | 5 USB Type B x1 |
| 2 RGB Out x1 | 6 RS-232c x1 |
| 3 S-Video / Video | 7 Audio In/Out |
| 4 HDMI x1 | |

Specifications

SMB

Native Resolution	WXGA (1280 x 800)
Brightness	2800 ANSI Lumens
Contrast Ratio	4000:1 (Full on/Full off)
Keystone	Manual Vertical +/- 40 Degree
Aspect Ratio	16:10 Native. 5 Aspect Ratio Selectable
Color	Full 16.7 Million colors palette
Lens	F = 2.55 to 3.06, f=21~25.6mm
Zoom Ratio	Manual Zoom, 1.20:1
Image Size (Diagonal)	32" - 300"
Throw Ratio	1.49 - 1.79 (64" - 75"@ 6.5 feet)
Lamp Life	190W, 4500/6000 hours (Normal/Eco-Mode)
PC Compatibility	VGA (640 x 480) to UXGA (1600 x 1200)
HDTV Compatibility	480i, 480p, 576i, 576p, 720p, 1080i, 1080p
Video Compatibility	NTSC, PAL, SECAM
Horizontal Frequency	31-90 kHz
Vertical Scan Rate	50-120 Hz
Input Terminals PC/AV	Analog RGB/Component: D-Sub 15 Pin x2 HDMI (v1.3) x1 USB (Type mini B) x1 (Display) S-Video: Mini Din 4 Pin x1 Composite Video: RCA x1 Stereo Mini-Jack x1
Output Terminals PC/AV	Analog RGB: D-Sub 15 Pin x1 Variable Audio Out: Stereo Mini-Jack x1 Speaker: 2W Speaker x1
Control Terminals	RS-232c 9 Pin x1 (Male) USB Type B (Page Up/Down)
Dimensions (W x H x D)	10.4" x 3.9" x 8.3"
Weight	5.1 lbs (2.3kg)
Power Supply	100 to 240 VAC, 50/60 Hz
Power Consumption	265W (Max), Standby <1W
Noise Level	27/25 dBA (Normal/Eco-Model)
Display Languages	Bulgarian/Croatian/Czech/Danish/Dutch/English/Finnish/ French/German/Hungarian/Italian/Japanese/Korean/ Norwegian/Polish/Romanian/Russian/Simplified Chinese/ Spanish/Swedish/Turkish/Thai/Traditional Chinese
Picture Mode	Dynamic Mode/Presentation Mode/sRGB Mode/Cinema Mode/ User 1 Mode/ User 2 Mode
Functions	3D-Ready/Panel Key Lock/ "Q" Hot Key for FAQ/Security Password/Quick Cooling/Digital Zoom (x2)/Quick Auto Search/ High Altitude Mode/Closed Captioning/3D Color Management/ Variable Audio Out
Accessories (Standard)	Quick Start Guide/User Manual (CD)/Remote Control/Power Cord/VGA Cable
Accessories (Optional)	Presentation Plus/Spare Lamp Kit/Carrying Case
Lamp P/N	5J.J3S05.001
Limited Warranty	1-Year Parts & Labor / 1-Year or 2000 hours of lamp life

BenQ is a registered trademark of BenQ Corp. DLP® is a registered trademark of Texas Instruments. All rights reserved. Corporate and trademarks are the property of their respective companies. Specifications subject to change without notice.

